#### 1586824

https://www.phoenixcontact.com/us/products/1586824

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Box mounting base, with double locking latch, height 52 mm, with screw connection, 2x M20

## Commercial data

Item number	1586824
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	BF55
Product key	BF7AAC
Catalog page	Page 580 (PC-2011)
GTIN	4046356426916
Weight per piece (including packing)	274.7 g
Weight per piece (excluding packing)	274.7 g
Customs tariff number	85389099
Country of origin	DE

PHŒNIX



https://www.phoenixcontact.com/us/products/1586824



# Technical data

## **Product properties**

Product type	Housing with locking latch
Housing type	Box mounting bases
Application	Standard
Туре	B10
No. of cable outlets	2
Type of the screw connection	2x M20
Shielded	no
Cable outlet	lateral
Pg screw connection	with

### Dimensions

Dimensional drawing	
Width	52 mm
Height	52 mm
Length	93 mm
Wrench size, union nut	20 mm

### Material specifications

Material Screw connection	Brass, nickel-plated
Seal material Cable seal	NBR
Housing material	die-cast aluminum
Housing surface material	Powder-coated, gray
Locking latch material	Stainless steel, handle: PA

## Mechanical properties

Mechanical data	
Type of the screw connection	2x M20
Locking type	Latch
Cable/line External cable diameter Cable 1	5 mm 12 mm (Cable 1)
External cable diameter Cable 1	5 mm 12 mm (Cable 1)
External cable diameter Cable 2	5 mm 12 mm (Cable 2)
Connection data	

## External cable diameter 5 mm ... 12 mm (Cable 1)



https://www.phoenixcontact.com/us/products/1586824



### Environmental and real-life conditions


#### Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-40 °C 125 °C

1586824

https://www.phoenixcontact.com/us/products/1586824

# Drawings





PHŒN

IX

Dimensional drawing

1586824

https://www.phoenixcontact.com/us/products/1586824



# Classifications

### ECLASS

ECLASS-11.0	27440202
ECLASS-13.0	27440202

## UNSPSC

1586824

https://www.phoenixcontact.com/us/products/1586824



# Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

1586824

https://www.phoenixcontact.com/us/products/1586824



Accessories

G-INS-M20-S68N-NNES-S - Cable gland

1411163 https://www.phoenixcontact.com/us/products/1411163



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 6 mm ... 12 mm, shielding: no, connecting thread: M20 x 1.5, color: silver, with O-ring

## HC-M-KV-M20(11-16) - Cable gland

1645998

https://www.phoenixcontact.com/us/products/1645998



Metal screw connection up to 5 bar, thread length: 6 mm, cable diameter: 11 - 16 mm, WAF 27, screw connection: M20  $\,$ 

#### 1586824

https://www.phoenixcontact.com/us/products/1586824



HC-M-KV-M20(1ASI) - Cable gland

#### 1584017

https://www.phoenixcontact.com/us/products/1584017



Metal screw connection for an AS-Interface flat-ribbon conductor, thread type  $\mathsf{M20}$ 

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com