# RC-06S1N128049 - Cable connector



1593732

https://www.phoenixcontact.com/pc/products/1593732

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Cable connector, straight, shielded: no, Screw locking mechanism, No. of pos.: 6, Direction of rotation: Standard, contact connection type: Socket, Solder cup, cable diameter range:  $6.5 \,$  mm ...  $7.5 \,$  mm, coding: N

### Commercial data

| Item number                          | 1593732                        |
|--------------------------------------|--------------------------------|
| Packing unit                         | 20 pc                          |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Product key                          | ABRAFA                         |
| GTIN                                 | 4046356197793                  |
| Weight per piece (including packing) | 71.33 g                        |
| Weight per piece (excluding packing) | 71.33 g                        |
| Customs tariff number                | 85366990                       |
| Country of origin                    | DE                             |

# RC-06S1N128049 - Cable connector



1593732

https://www.phoenixcontact.com/pc/products/1593732

## Technical data

### Product properties

| Product type  | Circular connector (cable-side) |
|---------------|---------------------------------|
| 1 Toddet type | Circulal Connector (Cable-side) |

#### Connector

### Insulating body

| Coding                                      | N          |
|---------------------------------------------|------------|
| Insertion/withdrawal cycles                 | 50         |
| Connection method                           | Solder cup |
| Contact switching type                      | Socket     |
| Application                                 | Signal     |
| Number of positions                         | 6          |
| Direction of rotation                       | Standard   |
| Connection profile                          | 6          |
| Contact diameter Power contacts             | 2 mm       |
| Litz wire cross-section Power contacts min. | 0.08 mm²   |
| Litz wire cross-section Power contacts max. | 2.5 mm²    |
| Rated current Power contacts                | 20 A       |
| Rated voltage                               | 48 V AC    |
|                                             | 74 V DC    |
| Rated surge voltage                         | 1.5 kV     |
| Overvoltage category                        | III        |
| Degree of pollution                         | 3          |

#### Housing

| Order information:                | Order contact inserts separately |
|-----------------------------------|----------------------------------|
| Housing material                  | Metal                            |
| Type of locking                   | Screw locking mechanism          |
| Pg screw connection               | none                             |
| Degree of protection (plugged in) | IP65                             |
|                                   | IP67                             |
|                                   | IP68                             |
| Thread type                       | M23                              |

#### Seal

| External cable diameter | 6.5 mm 7.5 mm |
|-------------------------|---------------|
|                         |               |

# RC-06S1N128049 - Cable connector




https://www.phoenixcontact.com/pc/products/1593732



## **Drawings**

Schematic diagram



Connector pin assignment

Phoenix Contact 2024  $\ensuremath{@}$  - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstraße 8 D-32825 Blomberg +49 (0) 5235-3 00 info@phoenixcontact.com