RC-12P1N120000 - Contact insert



1596856

https://www.phoenixcontact.com/us/products/1596856

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Contact insert, M23, number of positions: 12, contact connection type: Pin, Solder cup, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1240736

Commercial data

Item number	1596856
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	AB31
Product key	ABRAFU
GTIN	4046356212960
Weight per piece (including packing)	9.12 g
Weight per piece (excluding packing)	9.07 g
Customs tariff number	85366990
Country of origin	DE

RC-12P1N120000 - Contact insert



1596856

https://www.phoenixcontact.com/us/products/1596856

Technical data

Product properties

Product type	Contact insert
Number of positions	12
Connection profile	12
Application	Signal
Series	RC
	CA
	NC
	RM
	TU
	UC
Coding	N
Thread type	M23

Electrical properties

Contact

Contact diameter	1 mm
Min. cross section	0.08 mm²
Max. cross section	1 mm²
Max. current	8 A
Nominal voltage U _N	48 V AC 74 V DC
Overvoltage category	III
Degree of pollution	3
Rated surge voltage	1.5 kV

Connection data

Connection method	Solder cup

Material specifications

Insulator material	PBT
Contact material	CuZn
Contact surface	Nickel-plated, gold coating

Connector

Direction of rotation	Standard
-----------------------	----------

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	100

Mounting

RC-12P1N120000 - Contact insert



1596856

https://www.phoenixcontact.com/us/products/1596856

Connection method Solder cup

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com