

RC-12P2N127K00 - Crimp contact

1597932

<https://www.phoenixcontact.com/gb/products/1597932>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Crimp contact, series: RC, straight, shielded: no, Screw locking mechanism, No. of pos.: 12, Direction of rotation: Counter direction, contact connection type: Pin, Solder cup, coding: N

Commercial data

Item number	1597932
Packing unit	20 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	ABRAFG
GTIN	4046356218566
Weight per piece (including packing)	135 g
Weight per piece (excluding packing)	135 g
Country of origin	DE

RC-12P2N127K00 - Crimp contact



1597932

<https://www.phoenixcontact.com/gb/products/1597932>

Technical data

Product properties

Product type	Circular connector (cable-side)
--------------	---------------------------------

Connector

Insulating body

Coding	N
Insertion/withdrawal cycles	50
Connection method	Solder cup
Contact switching type	Pin
Application	Signal
Number of positions	12
Direction of rotation	Counter direction
Connection profile	12
Contact diameter	1 mm
Litz wire cross-section	0.08 mm²
Litz wire cross-section	1 mm²
Rated current	8 A
Rated voltage	48 V AC 74 V DC
Rated surge voltage	1.5 kV
Overvoltage category	III
Degree of pollution	3

Housing

Housing material	Metal
Type of locking	Screw locking mechanism
Pg screw connection	Pg11
Degree of protection (plugged in)	IP65 IP67 IP68
Thread type	M23

RC-12P2N127K00 - Crimp contact




1597932

<https://www.phoenixcontact.com/gb/products/1597932>

Drawings

Schematic diagram



Connector pin assignment

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk