RC-12S1N8D0000 - Contact insert



1599343

https://www.phoenixcontact.com/us/products/1599343

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Contact insert, M23, number of positions: 12, contact connection type: Socket, Crimp connection, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241077

Commercial data

Item number	1599343
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB31
Product key	ABRAFU
GTIN	4046356225465
Weight per piece (including packing)	11.7 g
Weight per piece (excluding packing)	11.14 g
Customs tariff number	85389099
Country of origin	DE

RC-12S1N8D0000 - Contact insert



https://www.phoenixcontact.com/us/products/1599343



Technical data

Product properties

Product type	Contact insert
Number of positions	12
Connection profile	12
Application	Signal
Series	NC
	RC
	RM
	TU
	UC
Coding	N
Thread type	M23

Electrical properties

Contact

Contact diameter	1 mm
Min. cross section	0.14 mm²
Max. cross section	0.56 mm²
Max. current	8 A
Nominal voltage U _N	48 V AC 74 V DC
Overvoltage category	III
Degree of pollution	3
Rated surge voltage	1.5 kV

Connection data

Connection method	Crimp connection
-------------------	------------------

Material specifications

Insulator material	PA66
Contact material	CuZn
Contact surface	Nickel-plated, gold coating

Connector

Direction of rotation Standard

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	50

Environmental and real-life conditions

RC-12S1N8D0000 - Contact insert



1599343

https://www.phoenixcontact.com/us/products/1599343

Ambient conditions

Ambient temperature (storage/transport)	15 °C 25 °C
Permissible humidity (storage/transport)	50 % 65 %

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com