

1599740

https://www.phoenixcontact.com/pc/products/1599740

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Cable connector, straight, shielded: no, Screw locking mechanism, No. of pos.: 12, Direction of rotation: Counter direction, contact connection type: Socket, Solder cup, cable diameter range: 3 mm ... 10.5 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241130

### Commercial data

Item number	1599740
Packing unit	20 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	ABRAFA
GTIN	4046356227193
Weight per piece (including packing)	75.385 g
Weight per piece (excluding packing)	75.385 g
Customs tariff number	85366990
Country of origin	DE



1599740

https://www.phoenixcontact.com/pc/products/1599740

### Technical data

### Product properties

Product type	Circular connector (cable-side)
--------------	---------------------------------

### Connector

### Insulating body

Coding	N
Insertion/withdrawal cycles	50
Connection method	Solder cup
Contact switching type	Socket
Application	Signal
Number of positions	12
Direction of rotation	Counter direction
Connection profile	12
Contact diameter Power contacts	1 mm
Litz wire cross-section Power contacts min.	0.08 mm <sup>2</sup>
Litz wire cross-section Power contacts max.	1 mm²
Rated current Power contacts	8 A
Rated voltage	48 V AC
	74 V DC
Rated surge voltage	1.5 kV
Overvoltage category	III
Degree of pollution	3

### Housing

Order information:	Order contact inserts separately
Housing material	Metal
Type of locking	Screw locking mechanism
Pg screw connection	none
Degree of protection (plugged in)	IP65
	IP67
	IP68
Thread type	M23

### Seal

External cable diameter	3 mm 10.5 mm
Seal material	NBR




https://www.phoenixcontact.com/pc/products/1599740



### Drawings

Schematic diagram



Connector pin assignment



1599740

https://www.phoenixcontact.com/pc/products/1599740

### Classifications

UNSPSC 21.0

### **ECLASS**

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116
ETIM	
ETIM 8.0	EC002635
UNSPSC	

39121400



1599740

https://www.phoenixcontact.com/pc/products/1599740

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	4e4c48a3-8959-4023-ae3a-3e570d3bf6f0



1599740

https://www.phoenixcontact.com/pc/products/1599740

### Accessories

PROT-M23-SG-IT-IP20 - Plastic protective cap

1577206

https://www.phoenixcontact.com/pc/products/1577206



Plastic protective cap, M23, degree of protection: IP20, series: CA, RC, RF, UC, RM

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstraße 8 D-32825 Blomberg +49 (0) 5235-3 00 info@phoenixcontact.com