1604793

https://www.phoenixcontact.com/us/products/1604793

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON box mounting base B16, with double locking latch, height 84 mm, with support 1xM32

Commercial data

Item number	1604793
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	BF55
Product key	BF7AAC
Catalog page	Page 516 (C-4-2013)
GTIN	4017918882716
Weight per piece (including packing)	439 g
Weight per piece (excluding packing)	439 g
Customs tariff number	85389099
Country of origin	DE

PHŒNIX

1604793

https://www.phoenixcontact.com/us/products/1604793



Technical data

Notes

General	For contact inserts HC-B16, BB32, BBB40, D40, DD72, HS6, M, K
Product properties	
Product type	Housing with locking latch
Housing type	Box mounting bases
Application	Standard
Туре	B16
No. of cable outlets	1
Type of the screw connection	1x M32
Shielded	no
Cable outlet	lateral
Pg screw connection	none

Dimensions

Dimensional drawing

Width	57 mm
Height	84 mm
Length	117 mm

Material specifications

Seal material	NBR
Housing material	die-cast aluminum
Housing surface material	Powder-coated, gray
Locking latch material	Stainless steel, handle: PA

Mechanical properties

Mechanical data	
Type of the screw connection	1x M32
Locking type	Latch

Mounting

Environmental and real-life conditions

Ambient conditions

1604793

https://www.phoenixcontact.com/us/products/1604793

Degree of protection	IP65
Ambient temperature (operation)	-40 °C 125 °C

PHŒNIX CONTACT


þ


1604793

https://www.phoenixcontact.com/us/products/1604793

Drawings

Dimensional drawing





Dimensional drawing

X

PHŒN

1604793

https://www.phoenixcontact.com/us/products/1604793



Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-13.0	27440202

UNSPSC

UNSPSC 21.0	31261501
01051 56 21:0	51201301

1604793

https://www.phoenixcontact.com/us/products/1604793



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

1604793

https://www.phoenixcontact.com/us/products/1604793



Accessories

G-INS-M32-M68N-PNES-GY - Cable gland

1411127 https://www.phoenixcontact.com/us/products/1411127



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 15 mm ... 21 mm, shielding: no, connecting thread: M32 x 1.5, color: silver-grey RAL 7001

G-INS-M32-M68N-PNES-BK - Cable gland

1411136

https://www.phoenixcontact.com/us/products/1411136



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 15 mm ... 21 mm, shielding: no, connecting thread: M32 x 1.5, color: jet black RAL 9005

1604793

https://www.phoenixcontact.com/us/products/1604793



G-INS-M32-M68N-NNES-S - Cable gland

1411166

https://www.phoenixcontact.com/us/products/1411166



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 15 mm ... 21 mm, shielding: no, connecting thread: M32 x 1.5, color: silver, with O-ring

HC-M-KV-M32(19-27) - Cable gland

1646010 https://www.phoenixcontact.com/us/products/1646010



Metal screw connection up to 5 bar, thread length: 8 mm, cable diameter: 19 - 27 mm, WAF 43, screw connection: M32 $\,$

1604793

https://www.phoenixcontact.com/us/products/1604793



G-INSEC-M32-M68N-NCRS-S - Cable gland

1411191

https://www.phoenixcontact.com/us/products/1411191



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 14 mm ... 21 mm, shielding: yes, connecting thread: M32 x 1.5, color: silver, with O-ring

HC-M-KV-Z-M32 - Cable gland

1646162 https://www.phoenixcontact.com/us/products/1646162



Metal screw connection with strain relief clamp, thread length: 8 mm, cable sealing area: 18 - 27 mm, clamping area: 19 - 30 mm, SW 40, screw connection: M32

1604793

https://www.phoenixcontact.com/us/products/1604793



HC-M-KV-T-M32 - Cable gland

1646201

https://www.phoenixcontact.com/us/products/1646201

Metal screw connection with cable bend protection and strain relief, thread length: 8 mm, cable sealing area: 18 - 27 mm, clamping area: 20 - 30 mm, SW 40, screw connection: M32



REDUC-M-KV-M32/M25 - Reducing adapter

1647637 https://www.phoenixcontact.com/us/products/1647637

Reducing adapter, connecting thread: M32 x 1.5, color: silver, with O-ring



1604793

https://www.phoenixcontact.com/us/products/1604793



ENLAR-M-KV-M32/M40 - Extension adapter

1647682

https://www.phoenixcontact.com/us/products/1647682

Extension adapter, connecting thread: M32 x 1.5, color: silver, with O-ring



HC-M-BS-M32 - Screw plug

1645862 https://www.phoenixcontact.com/us/products/1645862



Screw plug, material for screw connection: Brass, nickel-plated, connecting thread: M32 x 1.5, color: silver

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com