

SM-7ES1N8A8L04 - Cable connector



1605861

<https://www.phoenixcontact.com/pc/products/1605861>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable connector, straight long, SPEEDCON, M40, number of positions: 4+3+PE, contact connection type: Socket, shielded: yes, degree of protection: IP67, cable diameter range: 20.5 mm ... 26.5 mm, number of positions: 8, connection method: Crimp connection, series: SM

Your advantages

- Consistent EMC protection for reliable connection solutions in the industrial environment
- Crimping connection: vibration- and temperature-resistant assembly
- Flexible use: reliably connect various cable diameters

Commercial data

Item number	1605861
Packing unit	12 pc
Minimum order quantity	1 pc
Product key	ABRBGA
GTIN	4046356255356
Weight per piece (including packing)	461.8 g
Weight per piece (excluding packing)	445.05 g
Customs tariff number	85366990
Country of origin	DE

SM-7ES1N8A8L04 - Cable connector



1605861

<https://www.phoenixcontact.com/pc/products/1605861>

Technical data

Notes

General	Order crimp contacts 4 x Ø 2 mm, 4 x Ø 3.6 mm separately
Safety note	
Safety note	WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property. • WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible. • WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product. • The products are suitable for applications in plant, controller, and electrical device engineering. • When operating the connectors in outdoor applications, they must be separately protected against environmental influences. • Assembled products may not be manipulated or improperly opened. • Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products). • When using the product in direct connection with third-party manufacturers, the user is responsible. • For operating voltages > 50 V AC, conductive connector housings must be grounded • Ensure that the protective or functional ground has been properly connected. • VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector • Only use tools recommended by Phoenix Contact • The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product. • Operate the connector only when it is fully plugged in and interlocked. • Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards. • Observe the minimum bending radius of the cable. Lay the cable without twisting it. • The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting

SM-7ES1N8A8L04 - Cable connector



1605861

<https://www.phoenixcontact.com/pc/products/1605861>

warnings (e.g. DIN EN ISO 13732-1:2008-12).

Product properties

Product type	Circular connector (cable-side)
Series	SM
Application	Power
Number of positions	8
Connection profile	4+3+PE
Shielded	yes
Thread type	M40

Material specifications

Seal material	FPM
Housing material	Metal

Connection data

Conductor connection

Connection method	Crimp connection
-------------------	------------------

Electrical properties

Contact

Contact diameter	3.6 mm
Max. current	70 A
Nominal voltage U_N	630 V
Overvoltage category	III
Degree of pollution	3
Rated surge voltage	6 kV

Contact

Contact diameter	2 mm
Max. current	30 A
Nominal voltage U_N	250 V
Overvoltage category	III
Degree of pollution	3
Rated surge voltage	4 kV

Connector

Type	straight long
------	---------------

Cable/line

External cable diameter	20.5 mm ... 26.5 mm
-------------------------	---------------------

Environmental and real-life conditions

Ambient conditions

SM-7ES1N8A8L04 - Cable connector



1605861

<https://www.phoenixcontact.com/pc/products/1605861>

Degree of protection	IP67
Ambient temperature (operation)	-40 °C ... 125 °C
Altitude	3000 m


SM-7ES1N8A8L04 - Cable connector

1605861

<https://www.phoenixcontact.com/pc/products/1605861>

Drawings

Schematic diagram




Connector pin assignment

SM-7ES1N8A8L04 - Cable connector




1605861

<https://www.phoenixcontact.com/pc/products/1605861>



I = current strength, T = ambient temperature



Dimensional drawing

SM-7ES1N8A8L04 - Cable connector



1605861

<https://www.phoenixcontact.com/pc/products/1605861>

Classifications

ECLASS

ECLASS-11.0	27440102
-------------	----------

ETIM

ETIM 8.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

SM-7ES1N8A8L04 - Cable connector



1605861

<https://www.phoenixcontact.com/pc/products/1605861>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
-------------------------------------	----------------------

SM-7ES1N8A8L04 - Cable connector



1605861

<https://www.phoenixcontact.com/pc/products/1605861>

Accessories

SM-36KS001 - Crimp contact

1605756

<https://www.phoenixcontact.com/pc/products/1605756>



Crimp contact, Socket, turned, Single contact, contact diameter: 3.6 mm, crimp range: 1 mm² ... 2.5 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241977

SM-36KS002 - Crimp contact

1605758

<https://www.phoenixcontact.com/pc/products/1605758>



Crimp contact, Socket, turned, Single contact, contact diameter: 3.6 mm, crimp range: 2.5 mm² ... 4 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241979

SM-7ES1N8A8L04 - Cable connector

1605861

<https://www.phoenixcontact.com/pc/products/1605861>



SM-36KS003 - Crimp contact

1605760

<https://www.phoenixcontact.com/pc/products/1605760>



Crimp contact, Socket, turned, Single contact, contact diameter: 3.6 mm, crimp range: 4 mm² ... 6 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241979

SM-36KS004 - Crimp contact

1605762

<https://www.phoenixcontact.com/pc/products/1605762>



Crimp contact, Socket, turned, Single contact, contact diameter: 3.6 mm, crimp range: 6 mm² ... 10 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241980

SM-7ES1N8A8L04 - Cable connector

1605861

<https://www.phoenixcontact.com/pc/products/1605861>



SF-7PS2000 - Crimp contact

1605636

<https://www.phoenixcontact.com/pc/products/1605636>



Crimp contact, Socket, turned, Single contact, contact diameter: 2 mm, crimp range: 0.25 mm² ... 1 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241952

SF-7NS2000 - Crimp contact

1605631

<https://www.phoenixcontact.com/pc/products/1605631>



Crimp contact, Socket, turned, Single contact, contact diameter: 2 mm, crimp range: 0.75 mm² ... 1.5 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1237431

SM-7ES1N8A8L04 - Cable connector



1605861

<https://www.phoenixcontact.com/pc/products/1605861>

SF-7QS2000 - Crimp contact

1605643

<https://www.phoenixcontact.com/pc/products/1605643>



Crimp contact, Socket, turned, Single contact, contact diameter: 2 mm, crimp range: 1 mm² ... 2.5 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1237431

SF-7MS2000 - Crimp contact

1605628

<https://www.phoenixcontact.com/pc/products/1605628>



Crimp contact, Socket, turned, Single contact, contact diameter: 2 mm, crimp range: 4 mm² ... 4 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241949

SM-7ES1N8A8L04 - Cable connector



1605861


<https://www.phoenixcontact.com/pc/products/1605861>

SM-Z0025 - Color coding

1620558

<https://www.phoenixcontact.com/pc/products/1620558>

Color coding, color: green



SM-Z0026 - Color coding

1620559

<https://www.phoenixcontact.com/pc/products/1620559>

Color coding, color: orange



SM-7ES1N8A8L04 - Cable connector

1605861

<https://www.phoenixcontact.com/pc/products/1605861>



SM-Z0027 - Color coding

1620560

<https://www.phoenixcontact.com/pc/products/1620560>

Color coding, color: black



SM-Z0077 - Metal protective cap

1627218

<https://www.phoenixcontact.com/pc/products/1627218>

Metal protective cap, degree of protection: IP67, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1245442



SM-7ES1N8A8L04 - Cable connector

1605861

<https://www.phoenixcontact.com/pc/products/1605861>



SM-Z0003 - Square mounting flange with O-ring

1607935

<https://www.phoenixcontact.com/pc/products/1607935>

Square mounting flange with O-ring, Axial O-ring, 4x Ø4,2, series: SM



SM-Z0004 - Square mounting flange

1607937

<https://www.phoenixcontact.com/pc/products/1607937>

Square mounting flange, 4x Ø4,2, series: SM



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com