

1606113

https://www.phoenixcontact.com/pc/products/1606113

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Cable connector, series: UC, straight, shielded: yes, Screw locking mechanism, No. of pos.: 6, Direction of rotation: Standard, contact connection type: Socket, Solder cup, coding: N

Commercial data

| Item number | 1606113 |
|--------------------------------------|--------------------------------|
| Packing unit | 20 pc |
| Minimum order quantity | 1 pc |
| Note | Made to order (non-returnable) |
| Product key | ABRAIA |
| GTIN | 4046356257435 |
| Weight per piece (including packing) | 95.575 g |
| Weight per piece (excluding packing) | 95.575 g |
| Customs tariff number | 85366990 |
| Country of origin | DE |



1606113

https://www.phoenixcontact.com/pc/products/1606113

Technical data

Product properties

| | Product type | Circular connector (cable-side) |
|----|-------------------------|---------------------------------|
| Ma | laterial specifications | |
| | Housing material | Metal |

Connector

Insulating body

| Coding | N |
|---|------------|
| Insertion/withdrawal cycles | 50 |
| Connection method | Solder cup |
| Contact switching type | Socket |
| Application | Signal |
| Number of positions | 6 |
| Direction of rotation | Standard |
| Connection profile | 6 |
| Contact diameter Power contacts | 2 mm |
| Litz wire cross-section Power contacts min. | 0.08 mm² |
| Litz wire cross-section Power contacts max. | 2.5 mm² |
| Rated current Power contacts | 20 A |
| Rated voltage | 48 V AC |
| | 74 V DC |
| Rated surge voltage | 1.5 kV |
| Overvoltage category | III |
| Degree of pollution | 3 |

Housing

| Housing material | Metal |
|-----------------------------------|-------------------------|
| Type of locking | Screw locking mechanism |
| Pg screw connection | none |
| Degree of protection (plugged in) | IP67 |
| Thread type | M23 |




https://www.phoenixcontact.com/pc/products/1606113



Drawings

Schematic diagram



Connector pin assignment



1606113

https://www.phoenixcontact.com/pc/products/1606113

Classifications

| | ECLASS-11.0 | 27440102 | |
|------|-------------|----------|--|
| ETIM | | | |
| | ETIM 8.0 | EC002635 | |
| UI | NSPSC | | |
| | UNSPSC 21.0 | 39121400 | |



1606113

https://www.phoenixcontact.com/pc/products/1606113

Environmental product compliance

EU RoHS

| Fulfills EU RoHS substance requirements | Yes |
|---|---|
| Exemption | 6(c) |
| China RoHS | |
| Environment friendly use period (EFUP) | EFUP-50 |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |
| EU REACH SVHC | |
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1) |
| | |

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstraße 8 D-32825 Blomberg +49 (0) 5235-3 00 info@phoenixcontact.com