

UC-12P1N1280DU - Cable connector



1606282

<https://www.phoenixcontact.com/pc/products/1606282>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Cable connector, series: UC, straight, shielded: yes, Screw locking mechanism, No. of pos. : 12, Direction of rotation: Standard, contact connection type: Pin, Solder cup, cable diameter range: 2 mm ... 14.5 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1242101

Commercial data

Item number	1606282
Packing unit	20 pc
Minimum order quantity	1 pc
Product key	ABRAIA
GTIN	4046356258593
Weight per piece (including packing)	99.24 g
Weight per piece (excluding packing)	90.22 g
Customs tariff number	85389099
Country of origin	DE

UC-12P1N1280DU - Cable connector



1606282

<https://www.phoenixcontact.com/pc/products/1606282>

Technical data

Product properties

Product type	Circular connector (cable-side)
--------------	---------------------------------

Connector

Insulating body

Coding	N
Insertion/withdrawal cycles	100
Connection method	Solder cup
Contact switching type	Pin
Application	Signal
Number of positions	12
Direction of rotation	Standard
Connection profile	12
Contact diameter	1 mm
Litz wire cross-section	0.08 mm ²
Litz wire cross-section	1 mm ²
Rated current	8 A
Rated voltage	48 V AC 74 V DC
Rated surge voltage	1.5 kV
Overvoltage category	III
Degree of pollution	3

Housing

Housing material	Metal
Type of locking	Screw locking mechanism
Pg screw connection	none
Degree of protection (plugged in)	IP67
Thread type	M23

Seal

External cable diameter	2 mm ... 14.5 mm
-------------------------	------------------

UC-12P1N1280DU - Cable connector


1606282

<https://www.phoenixcontact.com/pc/products/1606282>



Drawings

Schematic diagram



Connector pin assignment

UC-12P1N1280DU - Cable connector



1606282

<https://www.phoenixcontact.com/pc/products/1606282>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 8.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

UC-12P1N1280DU - Cable connector



1606282

<https://www.phoenixcontact.com/pc/products/1606282>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	12d79d38-3fe1-4e0e-982e-9b6546eb1025

UC-12P1N1280DU - Cable connector

1606282

<https://www.phoenixcontact.com/pc/products/1606282>



Accessories

PROT-M23-SG-IT-IP20 - Plastic protective cap

1577206

<https://www.phoenixcontact.com/pc/products/1577206>



Plastic protective cap, M23, degree of protection: IP20, series: CA, RC, RF, UC, RM

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com