

RF-12P1N8A8002 - Cable connector



1607225

<https://www.phoenixcontact.com/pc/products/1607225>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable connector, straight, Screw locking mechanism, M23, number of positions: 12, contact connection type: Pin, shielded: yes, degree of protection: IP67, cable diameter range: 6 mm ... 10 mm, number of positions: 12, connection method: Crimp connection, series: RF, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1242241

Commercial data

Item number	1607225
Packing unit	20 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	ABRAGA
GTIN	4046356267892
Weight per piece (including packing)	98.9 g
Weight per piece (excluding packing)	98.9 g
Customs tariff number	85366990
Country of origin	DE

RF-12P1N8A8002 - Cable connector



1607225

<https://www.phoenixcontact.com/pc/products/1607225>

Technical data

Notes

General	Order crimp contacts Ø 1 mm separately
---------	--

Product properties

Product type	Circular connector (cable-side)
Series	RF
Application	Feedback, signal
	Signal
Number of positions	12
Connection profile	12
Shielded	yes
Coding	N
Thread type	M23

Material specifications

Seal material	FPM
Housing material	Metal
Housing material	Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Insulator material	PA 6.6
Gasket and O-ring material	FPM

Connection data

Conductor connection

Connection method	Crimp connection
-------------------	------------------

Electrical properties

Contact

Contact diameter	1 mm
Max. current	8 A
Nominal voltage U_N	48 V AC 74 V DC
Overvoltage category	III
Degree of pollution	3
Rated surge voltage	1.5 kV

Connector

Type	straight
Direction of rotation	Standard

Insulating body

Note	Order information: Order crimp contacts separately
Connection method	Crimp connection

RF-12P1N8A8002 - Cable connector



1607225

<https://www.phoenixcontact.com/pc/products/1607225>

Contact switching type	Pin
Application	Signal
Number of positions	12
Rated voltage	48 V AC
	74 V DC

Cable/line

External cable diameter	6 mm ... 10 mm
-------------------------	----------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-40 °C ... 125 °C
Altitude	2000 m

RF-12P1N8A8002 - Cable connector


1607225

<https://www.phoenixcontact.com/pc/products/1607225>




Drawings

Schematic diagram



Connector pin assignment

Dimensional drawing



Dimensional drawing

RF-12P1N8A8002 - Cable connector



1607225

<https://www.phoenixcontact.com/pc/products/1607225>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1607225>

 cUL Recognized Approval ID: E153698-20090723				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	48 V	5 A	- 20	-

 UL Recognized Approval ID: E153698-20090723				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	48 V	5 A	- 20	-

cULus Recognized				
-------------------------	--	--	--	--

RF-12P1N8A8002 - Cable connector



1607225

<https://www.phoenixcontact.com/pc/products/1607225>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 8.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

RF-12P1N8A8002 - Cable connector



1607225

<https://www.phoenixcontact.com/pc/products/1607225>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	2f50667c-0240-4f99-95df-781244744548

RF-12P1N8A8002 - Cable connector



1607225

<https://www.phoenixcontact.com/pc/products/1607225>

Accessories

SF-6CP2000 - Crimp contact

1605559

<https://www.phoenixcontact.com/pc/products/1605559>



Crimp contact, Pin, turned, Single contact, contact diameter: 1 mm, crimp range: 0.06 mm² ... 0.25 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241921

SF-10KP004 - Crimp contact

1607355

<https://www.phoenixcontact.com/pc/products/1607355>



Crimp contact, Pin, turned, Single contact, contact diameter: 1 mm, crimp range: 0.14 mm² ... 0.5 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241921

RF-12P1N8A8002 - Cable connector

1607225

<https://www.phoenixcontact.com/pc/products/1607225>



SF-6AP2000 - Crimp contact

1605554

<https://www.phoenixcontact.com/pc/products/1605554>



Crimp contact, Pin, turned, Single contact, contact diameter: 1 mm, crimp range: 0.25 mm² ... 1 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241921

SF-Z0028 - Torque screwdriver

1607456

<https://www.phoenixcontact.com/pc/products/1607456>



Torque screwdriver, series: RC, UC, SH, SF

RF-12P1N8A8002 - Cable connector

1607225

<https://www.phoenixcontact.com/pc/products/1607225>



SF-Z0027 - Hook wrench

1607455

<https://www.phoenixcontact.com/pc/products/1607455>



Hook wrench, series: RC, UC, RF, SF

RF-Z0003 - Square mounting flange

1607905

<https://www.phoenixcontact.com/pc/products/1607905>



Square mounting flange, Axial seal, 4xM3, flange dimensions: 35 mm x 35 mm, series: RF, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1242369

RF-12P1N8A8002 - Cable connector

1607225

<https://www.phoenixcontact.com/pc/products/1607225>



PROT-M23-SG-IT-IP20 - Plastic protective cap

1577206

<https://www.phoenixcontact.com/pc/products/1577206>



Plastic protective cap, M23, degree of protection: IP20, series: CA, RC, RF, UC, RM

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

info@phoenixcontact.com