

RF-12S1S8A8003 - Cable connector



1607285

<https://www.phoenixcontact.com/il/products/1607285>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable connector, straight, Screw locking mechanism, M23, number of positions: 12, contact connection type: Socket, shielded: yes, degree of protection: IP67, cable diameter range: 9 mm .
.. 13.2 mm, number of positions: 12, connection method: Crimp connection, series: RF

Commercial data

Item number	1607285
Packing unit	20 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	ABRAGA
GTIN	4046356268561
Weight per piece (including packing)	96.3 g
Weight per piece (excluding packing)	96.3 g
Customs tariff number	85366990
Country of origin	DE

RF-12S1S8A8003 - Cable connector



1607285

<https://www.phoenixcontact.com/il/products/1607285>

Technical data

Notes

Order information:	Order crimp contacts Ø 1 mm separately
--------------------	--

Product properties

Product type	Circular connector (cable-side)
Series	RF
Application	Feedback, signal
	Signal
Number of positions	12
Connection profile	12
Shielded	yes
Coding	S
Thread type	M23

Material specifications

Seal material	FPM
Housing material	Metal
Housing material	Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Insulator material	PA 6.6
Gasket and O-ring material	FPM

Connection data

Conductor connection	
Connection method	Crimp connection

Electrical properties

Contact	
Contact diameter	1 mm
Max. current	8 A
Nominal voltage U_N	150 V
Overvoltage category	III
Degree of pollution	3
Rated surge voltage	2.5 kV
Contact	
Overvoltage category	III
Degree of pollution	3

Connector

Type	straight
Direction of rotation	Standard

RF-12S1S8A8003 - Cable connector



1607285

<https://www.phoenixcontact.com/il/products/1607285>

Cable/line

External cable diameter	9 mm ... 13.2 mm
-------------------------	------------------

Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP67
Ambient temperature (operation)	-20 °C ... 125 °C
Altitude	2000 m

RF-12S1S8A8003 - Cable connector


1607285

<https://www.phoenixcontact.com/il/products/1607285>




Drawings

Dimensional drawing



Schematic diagram



RF-12S1S8A8003 - Cable connector



1607285

<https://www.phoenixcontact.com/il/products/1607285>

Accessories

SF-6CS2000 - Crimp contact

1605562

<https://www.phoenixcontact.com/il/products/1605562>



Crimp contact, Socket, turned, Single contact, contact diameter: 1 mm, crimp range: 0.06 mm² ... 0.25 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241922

SF-10KS004 - Crimp contact

1607356

<https://www.phoenixcontact.com/il/products/1607356>



Crimp contact, Socket, turned, Single contact, contact diameter: 1 mm, crimp range: 0.14 mm² ... 0.5 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241922

RF-12S1S8A8003 - Cable connector

1607285

<https://www.phoenixcontact.com/il/products/1607285>



SF-6AS2000 - Crimp contact

1605557

<https://www.phoenixcontact.com/il/products/1605557>



Crimp contact, Socket, turned, Single contact, contact diameter: 1 mm, crimp range: 0.25 mm² ... 1 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241922

SF-10KS010 - Crimp contact

1605481

<https://www.phoenixcontact.com/il/products/1605481>



Crimp contact, Socket, turned, Single contact, contact diameter: 1 mm, crimp range: 0.14 mm² ... 1 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241922

RF-12S1S8A8003 - Cable connector

1607285

<https://www.phoenixcontact.com/il/products/1607285>



SF-Z0028 - Torque screwdriver

1607456

<https://www.phoenixcontact.com/il/products/1607456>

Torque screwdriver, series: RC, UC, SH, SF



SF-Z0027 - Hook wrench

1607455

<https://www.phoenixcontact.com/il/products/1607455>

Hook wrench, series: RC, UC, RF, SF



RF-12S1S8A8003 - Cable connector

1607285

<https://www.phoenixcontact.com/il/products/1607285>



RF-Z0003 - Square mounting flange

1607905

<https://www.phoenixcontact.com/il/products/1607905>



Square mounting flange, Axial seal, 4xM3, flange dimensions: 35 mm x 35 mm, series: RF, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1242369

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Israel Ltd.
P.O.B. 1799 Industrial Park Hasharon
Quadima 60920
+972-9-8915700
info@phoenixcontact.co.il