

RF-17P2N8A8003 - Cable connector



1607330
<https://www.phoenixcontact.com/pc/products/1607330>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable connector, straight, Screw locking mechanism, M23, number of positions: 17, contact connection type: Pin, shielded: yes, degree of protection: IP67, cable diameter range: 9 mm ... 13.2 mm, number of positions: 17, connection method: Crimp connection, series: RF

Commercial data

Item number	1607330
Packing unit	20 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	ABRAGA
GTIN	4046356269117
Weight per piece (including packing)	96.195 g
Weight per piece (excluding packing)	96.195 g
Customs tariff number	85366990
Country of origin	DE

RF-17P2N8A8003 - Cable connector



1607330

<https://www.phoenixcontact.com/pc/products/1607330>

Technical data

Notes

General	Order crimp contacts Ø 1 mm separately
---------	--

Product properties

Product type	Circular connector (cable-side)
Series	RF
Application	Feedback, signal
	Signal
Number of positions	17
Connection profile	17
Shielded	yes
Coding	N
Thread type	M23

Material specifications

Seal material	FPM
Housing material	Metal
Housing material	Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Insulator material	PA 6.6
Gasket and O-ring material	FPM

Connection data

Conductor connection	
Connection method	Crimp connection

Electrical properties

Contact	
Contact diameter	1 mm
Max. current	8 A
Nominal voltage U_N	100 V
Overvoltage category	III
Degree of pollution	3
Rated surge voltage	1.5 kV

Contact	
Overvoltage category	III
Degree of pollution	3

Connector

Type	straight
Direction of rotation	Counter direction

RF-17P2N8A8003 - Cable connector



1607330

<https://www.phoenixcontact.com/pc/products/1607330>

Cable/line

External cable diameter	9 mm ... 13.2 mm
-------------------------	------------------

Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP67
Ambient temperature (operation)	-40 °C ... 125 °C
Altitude	2000 m

RF-17P2N8A8003 - Cable connector


1607330

<https://www.phoenixcontact.com/pc/products/1607330>




Drawings

Schematic diagram



Dimensional drawing



RF-17P2N8A8003 - Cable connector



1607330

<https://www.phoenixcontact.com/pc/products/1607330>

Classifications

UNSPSC

UNSPSC 21.0	39121413
-------------	----------

RF-17P2N8A8003 - Cable connector



1607330

<https://www.phoenixcontact.com/pc/products/1607330>

Accessories

SF-6CP2000 - Crimp contact

1605559

<https://www.phoenixcontact.com/pc/products/1605559>



Crimp contact, Pin, turned, Single contact, contact diameter: 1 mm, crimp range: 0.06 mm² ... 0.25 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241921

SF-10KP004 - Crimp contact

1607355

<https://www.phoenixcontact.com/pc/products/1607355>



Crimp contact, Pin, turned, Single contact, contact diameter: 1 mm, crimp range: 0.14 mm² ... 0.5 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241921

RF-17P2N8A8003 - Cable connector

1607330

<https://www.phoenixcontact.com/pc/products/1607330>



SF-6AP2000 - Crimp contact

1605554

<https://www.phoenixcontact.com/pc/products/1605554>



Crimp contact, Pin, turned, Single contact, contact diameter: 1 mm, crimp range: 0.25 mm² ... 1 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241921

SF-Z0028 - Torque screwdriver

1607456

<https://www.phoenixcontact.com/pc/products/1607456>



Torque screwdriver, series: RC, UC, SH, SF

RF-17P2N8A8003 - Cable connector

1607330

<https://www.phoenixcontact.com/pc/products/1607330>



SF-Z0027 - Hook wrench

1607455

<https://www.phoenixcontact.com/pc/products/1607455>



Hook wrench, series: RC, UC, RF, SF

RF-Z0003 - Square mounting flange

1607905

<https://www.phoenixcontact.com/pc/products/1607905>



Square mounting flange, Axial seal, 4xM3, flange dimensions: 35 mm x 35 mm, series: RF, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1242369

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com