Sleeve housing - VC-K-T2-Z-FK-6X20,5 - 1607703

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid
(http://phoenixcontact.com/download)

The figure shows version VC-K-T3-Z

Sleeve housing, plastic, type: VC2, with 6 x 20.5 mm flat cable outlet, locking screws with positive/negative head,

RoHS

Key Commercial Data

Packing unit	10 pc
GTIN	4 017918 952914
GTIN	4017918952914

Technical data

Dimensions

Height	65 mm

Ambient conditions

Degree of protection	IP54
Ambient temperature (operation)	-40 °C ... 80 °C

General

Type	VC2
Degree of protection	IP54
Flammability rating according to UL 94	V0
Locking type	Screw locking, cylinder head
Fixing screws	M4
Tightening torque, mounting screw	1.5 Nm ±0.3 Nm
Type of the screw connection	6 x 20.5 mm
Cable outlet	straight
Housing material	PA
Seal material	EPDM

Sleeve housing - VC-K-T2-Z-FK-6X20,5 - 1607703

Technical data

General

Ambient temperature (operation)	-40 °C ... 80 °C

Standards and Regulations

Flammability rating according to UL 94	V0

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC	EAC	B.01742

Phoenix Contact 2018 © - all rights reserved
http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
http://www.phoenixcontact.com