

https://www.phoenixcontact.com/in/products/1607729



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Metal screw connection up to 5 bar, thread length: 8 mm, cable diameter: 27 ... 34 mm, WAF 50, screw connection: M40

Commercial data

Item number	1607729
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BF7
Product key	BF7DAX
Catalog page	Page 690 (C-4-2015)
GTIN	4017918938819
Weight per piece (including packing)	184.2 g
Weight per piece (excluding packing)	168.65 g
Customs tariff number	74198090
Country of origin	DE



https://www.phoenixcontact.com/in/products/1607729



Technical data

Product properties

Product type	Full screw connection
No. of conductors	1
Type of the screw connection	M40
Manufacturer	Jacob
Manufacturer Designation	101036M40
Shielded	no

Dimensions

Dimensional drawing	95 g
Length	35 mm
Length of the connecting thread	8 mm
Hole diameter	40.1 mm 40.3 mm
Wrench size, union nut	50 mm
Wrench size, support	50 mm
Hexagon angular dimension	58 mm
Thread type connection side	M40 x 1.5
Thread pitch	1.5 mm

Connection data

Tightening torque	20 Nm (Union nut)
	20 Nm (Support sleeve)

Material specifications

Material Compression ring	PA
Seal material O-ring	NBR
Seal material Cable seal	Neoprene
Material for screw connection	Brass, nickel-plated

Cable/line

External cable diameter (Cable 1)	27 mm 34 mm
Halogen-free	no

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP68 (up to 5 bar)
Ambient temperature (operation)	-30 °C 100 °C


1607729

https://www.phoenixcontact.com/in/products/1607729



Drawings

Dimensional drawing



Dimensional drawing



https://www.phoenixcontact.com/in/products/1607729



Approvals

🎨 To download certificates, visit the product detail page: https://www.phoenixcontact.com/in/products/1607729



EAC-RoHS

Approval ID: RU D-DE.HB35.B.00387



1607729

https://www.phoenixcontact.com/in/products/1607729

Classifications

UNSPSC 21.0

ECLASS

	ECLASS-11.0	27144432
	ECLASS-12.0	27140801
	ECLASS-13.0	27140801
ETIM		
	ETIM 9.0	EC000441
UN	SPSC	

39121300



https://www.phoenixcontact.com/in/products/1607729



Environmental product compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in