

RF-17P1N8AWA00 - Device connector front mounting



1607860

<https://www.phoenixcontact.com/pc/products/1607860>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector front mounting, straight, Screw locking mechanism, M23, number of positions: 17, contact connection type: Pin, Axial O-ring, 4x Ø 3.2, shielded: yes, degree of protection: IP67, number of positions: 17, connection method: Crimp connection, series: RF

Your advantages

- Safe use in the field, thanks to high degree of protection
- Connector for flexible on-site assembly
- Consistent EMC protection for reliable connection solutions in the industrial environment
- Crimping connection: vibration- and temperature-resistant assembly
- Crimping connection: vibration- and temperature-resistant assembly

Commercial data

Item number	1607860
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	ABRAFL
Catalog page	Page 112 (C-2-2019)
GTIN	4046356174947
Weight per piece (including packing)	35.5 g
Weight per piece (excluding packing)	31.1 g
Customs tariff number	85366990
Country of origin	DE

RF-17P1N8AWA00 - Device connector front mounting



1607860

<https://www.phoenixcontact.com/pc/products/1607860>

Technical data

Notes

Order information:	Order crimp contacts Ø 1 mm separately
--------------------	--

Mounting

Mounting type	Front mounting
Mounting	4x Ø 3.2

Product properties

Product type	Circular connectors (device side)
Series	RF
Application	Signal
	Signal
Number of positions	17
Connection profile	17
Shielded	yes
Coding	N
Thread type	M23

Material specifications

Seal material	FPM
Housing material	Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Insulator material	PA 6.6
Gasket and O-ring material	FPM

Electrical properties

Contact

Contact diameter	1 mm
Max. current	8 A
Nominal voltage U_N	48 V AC 74 V DC
Overvoltage category	III
Degree of pollution	3
Rated surge voltage	1.5 kV

Connection data

Conductor connection

Connection method	Crimp connection
Contact connection type	Pin

Connector

Type	straight
------	----------

RF-17P1N8AWA00 - Device connector front mounting



1607860

<https://www.phoenixcontact.com/pc/products/1607860>


Direction of rotation	Standard
-----------------------	----------

Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP67
Ambient temperature (operation)	-40 °C ... 125 °C
Altitude	2000 m


Drawings

Dimensional drawing



Installation dimensions

Dimensional drawing




Dimensional drawing

1607860

<https://www.phoenixcontact.com/pc/products/1607860>

Schematic diagram



Contact chamber numbering (view of plug-in side), standard pin

RF-17P1N8AWA00 - Device connector front mounting



1607860

<https://www.phoenixcontact.com/pc/products/1607860>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1607860>

 cUL Recognized Approval ID: E153698-20090723				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	48 V	1 A	26 - 26	-

 UL Recognized Approval ID: E153698-20090723				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	48 V	1 A	26 - 26	-

cULus Recognized				
-------------------------	--	--	--	--

RF-17P1N8AWA00 - Device connector front mounting



1607860

<https://www.phoenixcontact.com/pc/products/1607860>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 9.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------