

ST-08P1N8AWQ00S - Device connector front mounting



1613286

<https://www.phoenixcontact.com/us/products/1613286>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector front mounting, straight, for standard and SPEEDCON interlock, M17, number of positions: 8, contact connection type: Pin, Axial O-ring, 4x Ø2,7, shielded: yes, flange dimensions: 21.6 mm x 21.6 mm, degree of protection: IP67, number of positions: 8, connection method: Crimp connection, series: ST

Your advantages

- Consistent EMC protection for reliable connection solutions in the industrial environment
- Crimping connection: vibration- and temperature-resistant assembly
- Flexible mounting, thanks to snap-in contact inserts

Commercial data

Item number	1613286
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB31
Product key	ABRADL
Catalog page	Page 65 (C-2-2019)
GTIN	4046356708487
Weight per piece (including packing)	30.9 g
Weight per piece (excluding packing)	27 g
Customs tariff number	85366990
Country of origin	DE

ST-08P1N8AWQ00S - Device connector front mounting



1613286

<https://www.phoenixcontact.com/us/products/1613286>

Technical data

Notes

General	Order crimp contacts Ø 1 mm separately
<p>Safety note</p>	
Safety note	<p>WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.</p> <ul style="list-style-type: none">• WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.• WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.• The products are suitable for applications in plant, controller, and electrical device engineering.• When operating the connectors in outdoor applications, they must be separately protected against environmental influences.• Assembled products may not be manipulated or improperly opened.• Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).• When using the product in direct connection with third-party manufacturers, the user is responsible.• For operating voltages > 50 V AC, conductive connector housings must be grounded• Ensure that the protective or functional ground has been properly connected.• VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector• Only use tools recommended by Phoenix Contact• The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product.• Operate the connector only when it is fully plugged in and interlocked.• Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.• Observe the minimum bending radius of the cable. Lay the cable without twisting it.• The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting

ST-08P1N8AWQ00S - Device connector front mounting



1613286

<https://www.phoenixcontact.com/us/products/1613286>

warnings (e.g. DIN EN ISO 13732-1:2008-12).

Mounting

Mounting	4x Ø2,7
----------	---------

Product properties

Product type	Circular connectors (device side)
Number of positions	8
Connection profile	8
Application	Signal
Series	ST
Shielded	yes
Coding	N
Thread type	M17

Dimensions

Housing	
Flange dimensions	21.6 mm x 21.6 mm

Material specifications

Seal material	FPM
Housing material	Metal

Electrical properties

Contact	
Contact diameter	1 mm
Max. current	8 A
Nominal voltage U _N	48 V AC 74 V DC
Overshoot category	III
Degree of pollution	3
Rated surge voltage	1.5 kV

Connection data

Conductor connection	
Connection method	Crimp connection
Contact connection type	Pin

Connector

Type	straight
Direction of rotation	Standard

Environmental and real-life conditions

Ambient conditions	
--------------------	--

ST-08P1N8AWQ00S - Device connector front mounting



1613286

<https://www.phoenixcontact.com/us/products/1613286>

Degree of protection	IP67
Ambient temperature (operation)	-40 °C ... 125 °C

ST-08P1N8AWQ00S - Device connector front mounting




1613286

<https://www.phoenixcontact.com/us/products/1613286>


Drawings

Dimensional drawing



Installation dimensions

Diagram



I = current strength, ϑ = ambient temperature, 8x 8 A


ST-08P1N8AWQ00S - Device connector front mounting



1613286


<https://www.phoenixcontact.com/us/products/1613286>

Schematic diagram



Connector pin assignment

Dimensional drawing



Dimensional drawing

ST-08P1N8AWQ00S - Device connector front mounting



1613286

<https://www.phoenixcontact.com/us/products/1613286>

Approvals

ⓘ To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1613286>

cUL Recognized			
Approval ID: FILE E 335019			
Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
48 V	5 A	-	-

UL Recognized			
Approval ID: FILE E 335019			
Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
48 V	5 A	-	-

UL Recognized			
Approval ID: E153698-20140124			
Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
48 V	5 A	-	-

cUL Recognized			
Approval ID: E153698-20140124			
Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
48 V	5 A	-	-

ST-08P1N8AWQ00S - Device connector front mounting



1613286

<https://www.phoenixcontact.com/us/products/1613286>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 9.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

ST-08P1N8AWQ00S - Device connector front mounting



1613286

<https://www.phoenixcontact.com/us/products/1613286>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com