

# RF-16P2N8A80DU - Cable connector



1613722

<https://www.phoenixcontact.com/il/products/1613722>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable connector, straight, Screw locking mechanism, M23, number of positions: 16, contact connection type: Pin, shielded: yes, degree of protection: IP67, cable diameter range: 5 mm ... 13.2 mm, number of positions: 16, connection method: Crimp connection, series: RF

## Commercial data

Item number	1613722
Packing unit	20 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	ABRAGA
GTIN	4046356401838
Weight per piece (including packing)	94.35 g
Weight per piece (excluding packing)	94.35 g
Customs tariff number	85366990
Country of origin	DE

# RF-16P2N8A80DU - Cable connector



1613722

<https://www.phoenixcontact.com/il/products/1613722>

## Technical data

### Notes

Order information:	Order crimp contacts Ø 1 mm separately
--------------------	--

### Product properties

Product type	Circular connector (cable-side)
Series	RF
Application	Feedback, signal
	Signal
Number of positions	16
Connection profile	16
Shielded	yes
Coding	N
Thread type	M23

### Material specifications

Seal material	FPM
Housing material	Metal
Housing material	Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Insulator material	PA 6.6
Gasket and O-ring material	FPM

### Connection data

Conductor connection	
Connection method	Crimp connection

### Electrical properties

Contact	
Contact diameter	1 mm
Max. current	8 A
Nominal voltage $U_N$	100 V
Overvoltage category	III
Degree of pollution	3
Rated surge voltage	1.5 kV

Contact	
Overvoltage category	III
Degree of pollution	3

### Connector

Type	straight
Direction of rotation	Counter direction

# RF-16P2N8A80DU - Cable connector



1613722

<https://www.phoenixcontact.com/il/products/1613722>

## Cable/line

External cable diameter	5 mm ... 13.2 mm
-------------------------	------------------

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-40 °C ... 125 °C
Altitude	2000 m


# RF-16P2N8A80DU - Cable connector

1613722


<https://www.phoenixcontact.com/il/products/1613722>

## Drawings

Dimensional drawing



Schematic diagram



Environmental product compliance

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

# RF-16P2N8A80DU - Cable connector



1613722

<https://www.phoenixcontact.com/il/products/1613722>

## Accessories

### SF-6CP2000 - Crimp contact

1605559

<https://www.phoenixcontact.com/il/products/1605559>



Crimp contact, Pin, turned, Single contact, contact diameter: 1 mm, crimp range: 0.06 mm<sup>2</sup> ... 0.25 mm<sup>2</sup>, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241921

---

### SF-10KP004 - Crimp contact

1607355

<https://www.phoenixcontact.com/il/products/1607355>



Crimp contact, Pin, turned, Single contact, contact diameter: 1 mm, crimp range: 0.14 mm<sup>2</sup> ... 0.5 mm<sup>2</sup>, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241921

## RF-16P2N8A80DU - Cable connector

1613722

<https://www.phoenixcontact.com/il/products/1613722>



## SF-6AP2000 - Crimp contact

1605554

<https://www.phoenixcontact.com/il/products/1605554>



Crimp contact, Pin, turned, Single contact, contact diameter: 1 mm, crimp range: 0.25 mm<sup>2</sup> ... 1 mm<sup>2</sup>, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241921

---

## SF-Z0028 - Torque screwdriver

1607456

<https://www.phoenixcontact.com/il/products/1607456>



Torque screwdriver, series: RC, UC, SH, SF

## RF-16P2N8A80DU - Cable connector

1613722

<https://www.phoenixcontact.com/il/products/1613722>



## SF-Z0027 - Hook wrench

1607455

<https://www.phoenixcontact.com/il/products/1607455>



Hook wrench, series: RC, UC, RF, SF

## RF-Z0003 - Square mounting flange

1607905

<https://www.phoenixcontact.com/il/products/1607905>



Square mounting flange, Axial seal, 4xM3, flange dimensions: 35 mm x 35 mm, series: RF, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1242369

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT Israel Ltd.  
P.O.B. 1799 Industrial Park Hasharon  
Quadima 60920  
+972-9-8915700  
[info@phoenixcontact.co.il](mailto:info@phoenixcontact.co.il)