

ST-3EP1N8A9K03S - Coupler connector



1618406

<https://www.phoenixcontact.com/pc/products/1618406>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Coupler connector, straight, for standard and SPEEDCON interlock, M17, number of positions: 3+PE, contact connection type: Pin, shielded: yes, degree of protection: IP67, cable diameter range: 5 mm ... 9.2 mm, number of positions: 4, connection method: Crimp connection, series: ST, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1243209

Your advantages

- Reduced size: ideal for compact devices
- Consistent EMC protection for reliable connection solutions in the industrial environment
- Crimping connection: vibration- and temperature-resistant assembly
- Flexible use: reliably connect various cable diameters

Commercial data

Item number	1618406
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	ABRSEF
Catalog page	Page 134 (C-2-2019)
GTIN	4046356816694
Weight per piece (including packing)	45.8 g
Weight per piece (excluding packing)	31.1 g
Customs tariff number	85366990
Country of origin	DE

ST-3EP1N8A9K03S - Coupler connector



1618406

<https://www.phoenixcontact.com/pc/products/1618406>

Technical data

Notes

Order information:	Order crimp contacts Ø 2 mm separately
Safety note	
Safety note	WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property. • WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible. • WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product. • The products are suitable for applications in plant, controller, and electrical device engineering. • When operating the connectors in outdoor applications, they must be separately protected against environmental influences. • Assembled products may not be manipulated or improperly opened. • Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products). • When using the product in direct connection with third-party manufacturers, the user is responsible. • For operating voltages > 50 V AC, conductive connector housings must be grounded • Ensure that the protective or functional ground has been properly connected. • VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector • Only use tools recommended by Phoenix Contact • The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product. • Operate the connector only when it is fully plugged in and interlocked. • Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards. • Observe the minimum bending radius of the cable. Lay the cable without twisting it. • The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting

ST-3EP1N8A9K03S - Coupler connector



1618406

<https://www.phoenixcontact.com/pc/products/1618406>

warnings (e.g. DIN EN ISO 13732-1:2008-12).

Product properties

Product type	Circular connector (cable-side)
Series	ST
Application	Power
Number of positions	4
Connection profile	3+PE
Shielded	yes
Coding	N
Thread type	M17

Data management status

Article revision	11
------------------	----

Material specifications

Seal material	FPM
Housing material	Metal

Connection data

Conductor connection

Connection method	Crimp connection
-------------------	------------------

Electrical properties

Contact

Contact diameter	2 mm
Max. current	25 A
Nominal voltage U_N	630 V
Overvoltage category	III
Degree of pollution	3
Rated surge voltage	6 kV

Contact

Contact diameter	2 mm
------------------	------

Connector

Type	straight
Direction of rotation	Standard

Connection 1

Head design	Pin
-------------	-----

Cable/line

External cable diameter	5 mm ... 9.2 mm
-------------------------	-----------------

ST-3EP1N8A9K03S - Coupler connector



1618406

<https://www.phoenixcontact.com/pc/products/1618406>

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-40 °C ... 125 °C
Altitude	3000 m

ST-3EP1N8A9K03S - Coupler connector




1618406

<https://www.phoenixcontact.com/pc/products/1618406>


Drawings

Diagram



I = current strength, ϑ = ambient temperature, 3x 25 A

Dimensional drawing




Technical drawings can be found under Downloads

ST-3EP1N8A9K03S - Coupler connector

1618406

<https://www.phoenixcontact.com/pc/products/1618406>

Schematic diagram



Connector pin assignment

ST-3EP1N8A9K03S - Coupler connector



1618406

<https://www.phoenixcontact.com/pc/products/1618406>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1618406>



cUL Recognized
Approval ID: E335019-20111129



UL Recognized
Approval ID: E335019-20111129



UL Recognized
Approval ID: E153698-20140124



cUL Recognized
Approval ID: E153698-20140124

ST-3EP1N8A9K03S - Coupler connector



1618406

<https://www.phoenixcontact.com/pc/products/1618406>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 9.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

ST-3EP1N8A9K03S - Coupler connector



1618406

<https://www.phoenixcontact.com/pc/products/1618406>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	7ae212a3-be56-48f2-8bf7-1e966b473210

ST-3EP1N8A9K03S - Coupler connector



1618406

<https://www.phoenixcontact.com/pc/products/1618406>

Accessories

ST-20KP010 - Crimp contact

1607655

<https://www.phoenixcontact.com/pc/products/1607655>



Crimp contact, Pin, turned, contact diameter: 2 mm, crimp range: 0.25 mm² ... 1 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1242329

ST-20KP020 - Crimp contact

1607656

<https://www.phoenixcontact.com/pc/products/1607656>



Crimp contact, Pin, turned, Single contact, contact diameter: 2 mm, crimp range: 1 mm² ... 2.5 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1242329

ST-3EP1N8A9K03S - Coupler connector



1618406


<https://www.phoenixcontact.com/pc/products/1618406>

ST-Z0016 - Color coding

1617993

<https://www.phoenixcontact.com/pc/products/1617993>

Color coding, color: green



ST-Z0017 - Color coding

1618049

<https://www.phoenixcontact.com/pc/products/1618049>

Color coding, color: orange



ST-3EP1N8A9K03S - Coupler connector

1618406

<https://www.phoenixcontact.com/pc/products/1618406>



ST-Z0018 - Color coding

1618050

<https://www.phoenixcontact.com/pc/products/1618050>

Color coding, color: black



PROT-M17PRO-OT-IP20 - Plastic protective cap

1055708

<https://www.phoenixcontact.com/pc/products/1055708>

Plastic protective cap, M17, degree of protection: IP20, series: M17 PRO



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com