

ST-08P1N8A6100S - Device connector front mounting



1618584

<https://www.phoenixcontact.com/us/products/1618584>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector front mounting, straight, for standard and SPEEDCON interlock, M17, number of positions: 8, contact connection type: Pin, Axial O-ring, Central fixing, shielded: yes, degree of protection: IP67, number of positions: 8, connection method: Crimp connection, series: ST, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1243233

Your advantages

- Application-specific wall mounting optionally with thread or anti-rotation protection and lock nut
- Consistent EMC protection for reliable connection solutions in the industrial environment
- Crimping connection: vibration- and temperature-resistant assembly

Commercial data

Item number	1618584
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB31
Product key	ABRACL
Catalog page	Page 69 (C-2-2019)
GTIN	4046356816717
Weight per piece (including packing)	23.4 g
Weight per piece (excluding packing)	20.5 g
Customs tariff number	85366990
Country of origin	DE

Technical data

Notes

General	Order crimp contacts Ø 1 mm separately
Safety note	
Safety note	WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property. • WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible. • WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product. • The products are suitable for applications in plant, controller, and electrical device engineering. • When operating the connectors in outdoor applications, they must be separately protected against environmental influences. • Assembled products may not be manipulated or improperly opened. • Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products). • When using the product in direct connection with third-party manufacturers, the user is responsible. • For operating voltages > 50 V AC, conductive connector housings must be grounded • Ensure that the protective or functional ground has been properly connected. • VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector • Only use tools recommended by Phoenix Contact • The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product. • Operate the connector only when it is fully plugged in and interlocked. • Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards. • Observe the minimum bending radius of the cable. Lay the cable without twisting it. • The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting

ST-08P1N8A6100S - Device connector front mounting



1618584

<https://www.phoenixcontact.com/us/products/1618584>

warnings (e.g. DIN EN ISO 13732-1:2008-12).

Mounting

Mounting

Central fixing

Product properties

Product type	Circular connectors (device side)
Number of positions	8
Connection profile	8
Application	Signal
Series	ST
Shielded	yes
Coding	N
Thread type	M17

Material specifications

Flammability rating according to UL 94	V0
Seal material	FPM
Housing material	Metal

Electrical properties

Contact

Contact diameter	1 mm
Max. current	8 A
Nominal voltage U_N	48 V AC 74 V DC
Overvoltage category	III
Degree of pollution	3
Rated surge voltage	1.5 kV

Connection data

Conductor connection

Connection method	Crimp connection
Contact connection type	Pin

Connector

Type	straight
Direction of rotation	Standard

Connection 1

Head design	Pin
-------------	-----

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
----------------------	------

ST-08P1N8A6100S - Device connector front mounting



1618584

<https://www.phoenixcontact.com/us/products/1618584>


Ambient temperature (operation)	-40 °C ... 125 °C
Ambient temperature (storage/transport)	15 °C ... 25 °C
Altitude	3000 m
Permissible humidity (storage/transport)	50 % ... 65 %

1618584

<https://www.phoenixcontact.com/us/products/1618584>


Drawings

Dimensional drawing



Installation dimensions: mounting with anti-rotation protection and locking nut

Diagram


 I = current strength, ϑ = ambient temperature, $8 \times 8 \text{ A}$

ST-08P1N8A6100S - Device connector front mounting

1618584


<https://www.phoenixcontact.com/us/products/1618584>

Schematic diagram



Connector pin assignment

Dimensional drawing



Installation dimensions: mounting with thread


ST-08P1N8A6100S - Device connector front mounting

1618584

<https://www.phoenixcontact.com/us/products/1618584>



Dimensional drawing



Dimensional drawing

ST-08P1N8A6100S - Device connector front mounting



1618584

<https://www.phoenixcontact.com/us/products/1618584>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1618584>

cUL Recognized Approval ID: FILE E 335019				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	48 V	5 A	-	-

UL Recognized Approval ID: FILE E 335019				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	48 V	5 A	-	-

UL Recognized Approval ID: E153698-20140124				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	48 V	5 A	-	-

cUL Recognized Approval ID: E153698-20140124				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	48 V	5 A	-	-

ST-08P1N8A6100S - Device connector front mounting



1618584

<https://www.phoenixcontact.com/us/products/1618584>

Classifications

ECLASS

ECLASS-11.0	27440109
ECLASS-12.0	27440109
ECLASS-13.0	27440109

ETIM

ETIM 8.0	EC003569
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

ST-08P1N8A6100S - Device connector front mounting



1618584

<https://www.phoenixcontact.com/us/products/1618584>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com