

1619214

https://www.phoenixcontact.com/us/products/1619214

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector front mounting, straight, for standard and SPEEDCON interlock, M17, number of positions: 5+PE, contact connection type: Socket, Axial O-ring, $4x \varnothing 3.2$, shielded: yes, flange dimensions: 25.75 mm x 25.75 mm, degree of protection: IP67, number of positions: 6, connection method: Crimp connection, series: ST

Your advantages

- Consistent EMC protection for reliable connection solutions in the industrial environment
- · Crimping connection: vibration- and temperature-resistant assembly
- · Flexible mounting, thanks to snap-in contact inserts

Commercial data

| Item number | 1619214 |
|--------------------------------------|--------------------------------|
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Note | Made to order (non-returnable) |
| Sales key | AB32 |
| Product key | ABRBEL |
| Catalog page | Page 137 (C-2-2019) |
| GTIN | 4046356827454 |
| Weight per piece (including packing) | 43.6 g |
| Weight per piece (excluding packing) | 33 g |
| Customs tariff number | 85366990 |
| Country of origin | DE |



1619214

https://www.phoenixcontact.com/us/products/1619214

Technical data

Notes

| General | Order crimp contacts Ø 1 mm separately |
|-------------|--|
| Safety note | |
| Safety note | WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property. |
| | WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible. |
| | WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product. |
| | The products are suitable for applications in plant, controller, and electrical device engineering. |
| | When operating the connectors in outdoor applications, they must be separately protected against environmental influences. |
| | Assembled products may not be manipulated or improperly opened. |
| | Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products). |
| | When using the product in direct connection with third-party manufacturers, the user is responsible. |
| | For operating voltages > 50 V AC, conductive connector housings must be grounded |
| | Ensure that the protective or functional ground has been properly connected. |
| | VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector |
| | Only use tools recommended by Phoenix Contact |
| | The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product. |
| | Operate the connector only when it is fully plugged in and interlocked. |
| | Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards. |
| | Observe the minimum bending radius of the cable. Lay the cable without twisting it. |
| | The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting |



1619214

https://www.phoenixcontact.com/us/products/1619214

| | Warriago / DIN EN ICO 40700 4 0000 40 |
|--------------------------------|---|
| | warnings (e.g. DIN EN ISO 13732-1:2008-12). |
| Mounting | |
| Mounting | 4x Ø 3.2 |
| Product properties | |
| Product type | Circular connectors (device side) |
| Number of positions | 6 |
| Connection profile | 5+PE |
| Application | Power |
| Series | ST |
| Shielded | yes |
| Coding | N |
| Thread type | M17 |
| Dimensions | |
| Housing | |
| Flange dimensions | 25.75 mm x 25.75 mm |
| Material specifications | |
| Seal material | FPM |
| Housing material | Metal |
| Electrical properties Contact | |
| Contact diameter | 1 mm |
| Max. current | 14 A |
| Nominal voltage U _N | 630 V |
| Overvoltage category | III |
| Degree of pollution | 3 |
| Rated surge voltage | 6 kV |
| Contact | |
| Contact diameter | 1 mm |
| Connection data | |
| | |
| Conductor connection | |
| Connection method | Crimp connection |
| Contact connection type | Socket |
| Connector | |
| Туре | straight |
| Direction of rotation | Standard |



1619214

https://www.phoenixcontact.com/us/products/1619214

| \sim | | |
|--------|---------|---|
| Con | nection | 1 |

| Head design | Socket |
|-------------|--------|
|-------------|--------|

Environmental and real-life conditions

Ambient conditions

| Degree of protection | IP67 |
|--|---------------|
| Ambient temperature (operation) | -40 °C 125 °C |
| Ambient temperature (storage/transport) | 15 °C 25 °C |
| Altitude | 3000 mm |
| Permissible humidity (storage/transport) | 50 % 65 % |




1619214

https://www.phoenixcontact.com/us/products/1619214


Drawings

Schematic diagram



Connector pin assignment

Schematic diagram




Installation dimensions



1619214

https://www.phoenixcontact.com/us/products/1619214



I = current strength, ϑ = ambient temperature, 3x 14 A + 2x 2 A constant



1619214

https://www.phoenixcontact.com/us/products/1619214

Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1619214



cUL Recognized

Approval ID: E335019-20111129



UL Recognized

Approval ID: E335019-20111129

| UL Listed Approval ID: E468743-20210825 | | | | |
|--|-----------------------|--------------------------------|-------------------|-------------------------------|
| | Nominal voltage U_N | Nominal current I _N | Cross section AWG | Cross section mm ² |
| Power | 600 V | 10 A | - | - 18 |
| Signal | 60 V | 2 A | - | - 20 |

| cUL Listed Approval ID: E468743-20210825 | | | | |
|--|--------------------------------|--------------------------------|-------------------|-------------------------------|
| | Nominal voltage U _N | Nominal current I _N | Cross section AWG | Cross section mm ² |
| Power | 600 V | 8 A | - 18 | - |
| Signal | 60 V | 2 A | - 20 | - |

| <i>9</i> 1 | UL Recognized |
|------------|-------------------------------|
| 74 | Approval ID: E153698-20140124 |



cUL Recognized

Approval ID: E153698-20140124

cULus Listed



1619214

https://www.phoenixcontact.com/us/products/1619214

Classifications

UNSPSC 21.0

ECLASS

| | F01 400 44 0 | 07440400 |
|----|--------------|----------|
| | ECLASS-11.0 | 27440102 |
| | ECLASS-12.0 | 27440116 |
| | ECLASS-13.0 | 27440116 |
| ΕT | М | |
| | ETIM 9.0 | EC002635 |
| UN | SPSC | |

39121400



1619214

https://www.phoenixcontact.com/us/products/1619214

Environmental product compliance

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e | |
|------------|---|--|
| | No hazardous substances above threshold values | |

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com