

K-12 - OE/5,0-E00/M23 F8-N2 - Cable plug in molded plastic

1619248
<https://www.phoenixcontact.com/us/products/1619248>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable plug in molded plastic, Straight, plastic molded, number of positions: 12, type of locking: Screw locking mechanism, cable length: 5 m, shielded: yes, color of outer sheath: orange RAL 2003

Your advantages

- Our standard: robust halogen-free PUR cable
- Simple and safe: 100% electrically tested and assembled ready for use
- Designs with preassembled cables on one or both sides
- High flexibility: customer-specific assemblies and cable lengths can be supplied

Commercial data

Item number	1619248
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	AB34
Product key	ABRDFA
Catalog page	Page 216 (C-2-2019)
GTIN	4046356833424
Weight per piece (including packing)	619 g
Weight per piece (excluding packing)	540 g
Customs tariff number	85444290
Country of origin	DE

K-12 - OE/5,0-E00/M23 F8-N2 - Cable plug in molded plastic



1619248

<https://www.phoenixcontact.com/us/products/1619248>

Technical data

Product properties

Product type	Signal and power cable
Data management status	
Article revision	09

Connector

Connector specifications

Type	Straight, plastic molded
Housing material	Zinc die-cast
Type of locking	Screw locking mechanism
Degree of protection	IP67, when in locked state
No. of pos.	12
Direction of rotation	Standard
Contact switching type	Socket
Insertion/withdrawal cycles	50
Contact resistance	< 0.3 mΩ
Max. current	8 A
Voltage	48 V AC 74 V DC
Overvoltage category	III
Degree of pollution	3
Rated surge voltage	1.5 kV
Ambient temperature (operation)	-40 °C ... 105 °C

Cable specifications

Cable type	RSL9YSLC11Y
Shielded	yes
Cable structure	4 x 2 x 0.25 mm ² + 2 x 0.5 mm ²
Cable structure (AWG)	24 AWG/4pr + 20 AWG/2c
External cable diameter	8.00 mm
Outer sheath, material	TPU
Material wire insulation	PP
External sheath, color	orange RAL 2003
Test voltage	1 kV
Rated current	9 A
Smallest bending radius, fixed installation	40 mm
Smallest bending radius, movable installation	60 mm
Ambient temperature (operation) for fixed installation	-40 °C ... 80 °C
Ambient temperature (operation) for flexible installation	-20 °C ... 60 °C

Electrical properties

K-12 - OE/5,0-E00/M23 F8-N2 - Cable plug in molded plastic



1619248

<https://www.phoenixcontact.com/us/products/1619248>

Nominal current I_N	9 A
-----------------------	-----

Cable/line

Cable length	5 m
--------------	-----

K-12 - OE/5,0-E00/M23 F8-N2 - Cable plug in molded plastic




1619248

<https://www.phoenixcontact.com/us/products/1619248>

Drawings

Dimensional drawing




Dimensional drawing

K-12 - OE/5,0-E00/M23 F8-N2 - Cable plug in molded plastic

1619248

<https://www.phoenixcontact.com/us/products/1619248>

Schematic diagram



Connector pin assignment


K-12 - OE/5,0-E00/M23 F8-N2 - Cable plug in molded plastic



1619248

<https://www.phoenixcontact.com/us/products/1619248>

Circuit diagram



1619248
<https://www.phoenixcontact.com/us/products/1619248>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1619248>



EAC
Approval ID: 19060508

	UL Listed Approval ID: E335019-20140707			
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
Power	48 V	5 A	-	-
Signal	48 V	2 A	-	-

	cUL Listed Approval ID: E335019-20140707			
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
Power	48 V	5 A	-	-
Signal	48 V	2 A	-	-

cULus Listed

K-12 - OE/5,0-E00/M23 F8-N2 - Cable plug in molded plastic



1619248

<https://www.phoenixcontact.com/us/products/1619248>

Classifications

ECLASS

ECLASS-11.0	27060106
ECLASS-12.0	27060106
ECLASS-13.0	27060106

ETIM

ETIM 9.0	EC003250
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

1619248
<https://www.phoenixcontact.com/us/products/1619248>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(b), 6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	9578f33d-670e-4d0a-9982-0dfb944cb675

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com