

CA-12S1N12T0DN - Cable connector



1619331

<https://www.phoenixcontact.com/be/products/1619331>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Cable connector, series: CA, angled, shielded: yes, Screw locking mechanism, No. of pos.: 12, Direction of rotation: Standard, contact connection type: Socket, Solder connection, cable diameter range: 3 mm ... 14.5 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1243452

Your advantages

- Angled cable outlet for confined spaces
- Can be adapted to various applications, thanks to adjustable cable outlet direction
- Safe use in the field, thanks to high degree of protection
- Connector for flexible on-site assembly
- Consistent EMC protection for reliable transmission of signals
- Solder connection: proven connection technology for various litz wires

Commercial data

Item number	1619331
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	ABRAEC
Product key	ABRAEC
Catalog page	Page 92 (C-2-2019)
GTIN	4046356825139
Weight per piece (including packing)	195,1 g
Weight per piece (excluding packing)	195,1 g
Customs tariff number	85366990
Country of origin	DE

CA-12S1N12T0DN - Cable connector



1619331

<https://www.phoenixcontact.com/be/products/1619331>

Technical data

Product properties

Product type	Circular connector (cable-side)
Data management status	
Article revision	05

Connector

Connection 1

Head design	Socket
-------------	--------

Insulating body

Coding	N
Insulation body material	PBT
Contact material	CuZn
Contact surface material	Ni/Au
Insertion/withdrawal cycles	100
Connection method	Solder connection
Contact switching type	Socket
Application	Signal
Number of positions	12
Direction of rotation	Standard
Connection profile	12
Rated voltage	48 V AC 74 V DC
Rated surge voltage	1.5 kV
Overvoltage category	III
Degree of pollution	3
Contact diameter	1 mm
Litz wire cross-section	1 mm ²
Nominal current per signal contact	8 A

Signal contacts

Signal contacts max.

Housing

Housing material	Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Type of locking	Screw locking mechanism
Pg screw connection	none
Degree of protection (plugged in)	IP67
Thread type	M23

Seal

External cable diameter	3 mm ... 14.5 mm
Seal material	NBR

CA-12S1N12T0DN - Cable connector



1619331

<https://www.phoenixcontact.com/be/products/1619331>

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
Ambient temperature (storage/transport)	15 °C ... 25 °C
Permissible humidity (storage/transport)	50 % ... 65 %

CA-12S1N12T0DN - Cable connector




1619331

<https://www.phoenixcontact.com/be/products/1619331>

Drawings

Schematic diagram



Connector pin assignment

CA-12S1N12T0DN - Cable connector



1619331

<https://www.phoenixcontact.com/be/products/1619331>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/be/products/1619331>

 cUL Recognized Approval ID: E335019-20141210				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	48 V	6 A	18 - 18	-

 UL Recognized Approval ID: E335019-20141210				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	48 V	8 A	18 - 18	-

cULus Recognized				
-------------------------	--	--	--	--

CA-12S1N12T0DN - Cable connector



1619331

<https://www.phoenixcontact.com/be/products/1619331>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 9.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

CA-12S1N12T0DN - Cable connector



1619331
<https://www.phoenixcontact.com/be/products/1619331>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	391a4e91-3925-40a1-9d37-caf8c44345ab

CA-12S1N12T0DN - Cable connector



1619331

<https://www.phoenixcontact.com/be/products/1619331>

Accessories

SF-Z0028 - Torque screwdriver

1607456

<https://www.phoenixcontact.com/be/products/1607456>

Torque screwdriver, series: RC, UC, SH, SF



SF-Z0027 - Hook wrench

1607455

<https://www.phoenixcontact.com/be/products/1607455>

Hook wrench, series: RC, UC, RF, SF



CA-12S1N12T0DN - Cable connector

1619331

<https://www.phoenixcontact.com/be/products/1619331>




RF-Z0014 - Color coding

1620588

<https://www.phoenixcontact.com/be/products/1620588>

Color coding, color: green



RF-Z0015 - Color coding

1620592

<https://www.phoenixcontact.com/be/products/1620592>

Color coding, color: orange



CA-12S1N12T0DN - Cable connector

1619331

<https://www.phoenixcontact.com/be/products/1619331>



RF-Z0016 - Color coding

1620593

<https://www.phoenixcontact.com/be/products/1620593>

Color coding, color: black



PROT-M23-SG-IT-IP20 - Plastic protective cap

1577206

<https://www.phoenixcontact.com/be/products/1577206>

Plastic protective cap, M23, degree of protection: IP20, series: CA, RC, RF, UC, RM



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT nv/sa
Minervastraat 10-12
1930 Zaventem-Keiberg II
+32 (0)2/723 98 11
info@phoenixcontact.be