

CA-06S1N8AT0DN - Cable connector



1619341

<https://www.phoenixcontact.com/be/products/1619341>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Cable connector, series: CA, angled, shielded: yes, Screw locking mechanism, No. of pos.: 6, Direction of rotation: Standard, contact connection type: Socket, Crimp connection, cable diameter range: 3 mm ... 14.5 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1243462

Your advantages

- Angled cable outlet for confined spaces
- Can be adapted to various applications, thanks to adjustable cable outlet direction
- Safe use in the field, thanks to high degree of protection
- Connector for flexible on-site assembly
- Consistent EMC protection for reliable transmission of signals
- Crimping connection: vibration- and temperature-resistant assembly

Commercial data

Item number	1619341
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	ABRAEC
Product key	ABRAEC
Catalog page	Page 92 (C-2-2019)
GTIN	4046356825030
Weight per piece (including packing)	188,4 g
Weight per piece (excluding packing)	188,4 g
Customs tariff number	85366990
Country of origin	DE

CA-06S1N8AT0DN - Cable connector



1619341

<https://www.phoenixcontact.com/be/products/1619341>

Technical data

Notes

Order information:	Order crimp contacts 6 x Ø 2 mm separately
--------------------	--

Product properties

Product type	Circular connector (cable-side)
--------------	---------------------------------

Data management status

Article revision	04
------------------	----

Connector

Connection 1

Head design	Socket
-------------	--------

Insulating body

Note	Order information: Order crimp contacts Ø 2 mm separately
Coding	N
Insulation body material	PA 6.6
Connection method	Crimp connection
Contact switching type	Socket
Application	Signal
Number of positions	6
Direction of rotation	Standard
Connection profile	6
Contact diameter	2 mm
Signal contacts	
Litz wire cross-section Signal contacts min.	1 mm ²
Litz wire cross-section Signal contacts max.	2.5 mm ²
Nominal current per signal contact	20 A
Rated voltage Signal contact	48 V AC
Rated surge voltage	1.5 kV
Overvoltage category	III
Degree of pollution	3

Housing

Housing material	Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Type of locking	Screw locking mechanism
Pg screw connection	none
Degree of protection (plugged in)	IP67
Thread type	M23

Seal

External cable diameter	3 mm ... 14.5 mm
-------------------------	------------------

CA-06S1N8AT0DN - Cable connector



1619341

<https://www.phoenixcontact.com/be/products/1619341>

Seal material	NBR
---------------	-----

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
Ambient temperature (storage/transport)	15 °C ... 25 °C
Permissible humidity (storage/transport)	50 % ... 65 %

CA-06S1N8AT0DN - Cable connector


1619341

<https://www.phoenixcontact.com/be/products/1619341>



Drawings

Schematic diagram



Connector pin assignment

CA-06S1N8AT0DN - Cable connector



1619341

<https://www.phoenixcontact.com/be/products/1619341>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/be/products/1619341>

	cUL Recognized			
	Approval ID: E335019-20141210			
		Nominal voltage U_N	Nominal current I_N	Cross section AWG
		48 V	10 A	14 - 14
				Cross section mm^2
				-

	UL Recognized			
	Approval ID: E335019-20141210			
		Nominal voltage U_N	Nominal current I_N	Cross section AWG
		48 V	17 A	14 - 14
				Cross section mm^2
				-

cULus Recognized				
-------------------------	--	--	--	--

CA-06S1N8AT0DN - Cable connector



1619341

<https://www.phoenixcontact.com/be/products/1619341>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 9.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

CA-06S1N8AT0DN - Cable connector



1619341

<https://www.phoenixcontact.com/be/products/1619341>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	67b4b566-1cc0-4d20-be51-001fce3c2d1d

CA-06S1N8AT0DN - Cable connector

1619341

<https://www.phoenixcontact.com/be/products/1619341>



Accessories

SF-Z0028 - Torque screwdriver

1607456

<https://www.phoenixcontact.com/be/products/1607456>

Torque screwdriver, series: RC, UC, SH, SF



SF-Z0027 - Hook wrench

1607455

<https://www.phoenixcontact.com/be/products/1607455>

Hook wrench, series: RC, UC, RF, SF



CA-06S1N8AT0DN - Cable connector



1619341


<https://www.phoenixcontact.com/be/products/1619341>

RF-Z0014 - Color coding

1620588

<https://www.phoenixcontact.com/be/products/1620588>

Color coding, color: green



RF-Z0015 - Color coding

1620592

<https://www.phoenixcontact.com/be/products/1620592>

Color coding, color: orange



CA-06S1N8AT0DN - Cable connector

1619341

<https://www.phoenixcontact.com/be/products/1619341>



RF-Z0016 - Color coding

1620593

<https://www.phoenixcontact.com/be/products/1620593>

Color coding, color: black



RC-5CS2000 - Crimp contact

1603517

<https://www.phoenixcontact.com/be/products/1603517>



Crimp contact, Socket, turned, contact diameter: 2 mm, crimp range: 1 mm² ... 1.5 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241635

CA-06S1N8AT0DN - Cable connector

1619341

<https://www.phoenixcontact.com/be/products/1619341>



RC-5AS2000 - Crimp contact

1603509

<https://www.phoenixcontact.com/be/products/1603509>



Crimp contact, Socket, turned, contact diameter: 2 mm, crimp range: 1.5 mm² ... 2.5 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241635

RC-5SS2000 - Crimp contact

1603530

<https://www.phoenixcontact.com/be/products/1603530>



Crimp contact, Socket, turned, contact diameter: 2 mm, crimp range: 0.5 mm² ... 0.75 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241633

CA-06S1N8AT0DN - Cable connector

1619341

<https://www.phoenixcontact.com/be/products/1619341>



RC-59S2000 - Crimp contact

1603501

<https://www.phoenixcontact.com/be/products/1603501>



Crimp contact, Socket, turned, Single contact, contact diameter: 2 mm, crimp range: 0.75 mm² ... 1 mm², Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241633

PROT-M23-SG-IT-IP20 - Plastic protective cap

1577206

<https://www.phoenixcontact.com/be/products/1577206>



Plastic protective cap, M23, degree of protection: IP20, series: CA, RC, RF, UC, RM

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT nv/sa
Minervastraat 10-12
1930 Zaventem-Keiberg II
+32 (0)2/723 98 11
info@phoenixcontact.be