

# CA-09P1N8AT007S - Cable connector



1619387  
<https://www.phoenixcontact.com/pc/products/1619387>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

M23, Cable connector, series: CA, angled, shielded: yes, SPEEDCON, No. of pos.: 8+1, Direction of rotation: Standard, contact connection type: Pin, Crimp connection, cable diameter range: 6 mm ... 10 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1243505



## Your advantages

- Angled cable outlet for confined spaces
- Can be adapted to various applications, thanks to adjustable cable outlet direction
- Safe use in the field, thanks to high degree of protection
- Connector for flexible on-site assembly
- Consistent EMC protection for reliable transmission of signals
- Reduced connection time with SPEEDCON fast locking system
- Crimping connection: vibration- and temperature-resistant assembly

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 1619387                        |
| Packing unit                         | 1 pc                           |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Product key                          | ABRAED                         |
| Catalog page                         | Page 90 (C-2-2019)             |
| GTIN                                 | 4046356824606                  |
| Weight per piece (including packing) | 187.9 g                        |
| Weight per piece (excluding packing) | 187.9 g                        |
| Customs tariff number                | 85366990                       |
| Country of origin                    | DE                             |

# CA-09P1N8AT007S - Cable connector



1619387

<https://www.phoenixcontact.com/pc/products/1619387>

## Technical data

### Notes

|         |                                                        |
|---------|--------------------------------------------------------|
| General | Order crimp contacts 8 x Ø 1 mm, 1 x Ø 2 mm separately |
|---------|--------------------------------------------------------|

### Product properties

|              |                                 |
|--------------|---------------------------------|
| Product type | Circular connector (cable-side) |
|--------------|---------------------------------|

### Connector

#### Insulating body

|                                                     |                                                                           |
|-----------------------------------------------------|---------------------------------------------------------------------------|
| Note                                                | Order information: Order crimp contacts 8 x Ø 1 mm, 1 x Ø 2 mm separately |
| Coding                                              | N                                                                         |
| Insulation body material                            | PA 6.6                                                                    |
| Connection method                                   | Crimp connection                                                          |
| Contact switching type                              | Pin                                                                       |
| Application                                         | Signal                                                                    |
| Number of positions                                 | 9                                                                         |
| Direction of rotation                               | Standard                                                                  |
| Connection profile                                  | 8+1                                                                       |
| Contact diameter <b>Power contacts</b>              | 2 mm                                                                      |
| Litz wire cross-section <b>Power contacts</b> min.  | 1 mm <sup>2</sup>                                                         |
| Litz wire cross-section <b>Power contacts</b> max.  | 2.5 mm <sup>2</sup>                                                       |
| Rated current <b>Power contacts</b>                 | 20 A                                                                      |
| Rated voltage                                       | 48 V AC<br>74 V DC                                                        |
| Rated surge voltage                                 | 1.5 kV                                                                    |
| Overvoltage category                                | III                                                                       |
| Degree of pollution                                 | 3                                                                         |
| Contact diameter <b>Signal contacts</b>             | 1 mm                                                                      |
| Litz wire cross-section <b>Signal contacts</b> min. | 0.08 mm <sup>2</sup>                                                      |
| Litz wire cross-section <b>Signal contacts</b> max. | 1 mm <sup>2</sup>                                                         |
| Nominal current per signal contact                  | 8 A                                                                       |

#### Housing

|                                   |          |
|-----------------------------------|----------|
| Housing material                  | Metal    |
| Type of locking                   | SPEEDCON |
| Pg screw connection               | none     |
| Degree of protection (plugged in) | IP67     |
| Thread type                       | M23      |

#### Seal

# CA-09P1N8AT007S - Cable connector



1619387

<https://www.phoenixcontact.com/pc/products/1619387>

|                         |                |
|-------------------------|----------------|
| External cable diameter | 6 mm ... 10 mm |
| Seal material           | NBR            |

## Environmental and real-life conditions

### Ambient conditions

|                                          |                   |
|------------------------------------------|-------------------|
| Ambient temperature (operation)          | -40 °C ... 125 °C |
| Ambient temperature (storage/transport)  | 15 °C ... 25 °C   |
| Permissible humidity (storage/transport) | 50 % ... 65 %     |

# CA-09P1N8AT007S - Cable connector


1619387

<https://www.phoenixcontact.com/pc/products/1619387>



## Drawings

Dimensional drawing



Dimensional drawing


# CA-09P1N8AT007S - Cable connector

1619387

<https://www.phoenixcontact.com/pc/products/1619387>



Schematic diagram



Connector pin assignment

# CA-09P1N8AT007S - Cable connector



1619387

<https://www.phoenixcontact.com/pc/products/1619387>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1619387>

|  <b>cUL Recognized</b><br>Approval ID: E335019-20141210 |                       |                       |                   |                             |
|------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                                                                                                          | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Power                                                                                                                                    | 48 V                  | 12 A                  | - 14              | -                           |
| Signal                                                                                                                                   | 48 V                  | 4 A                   | - 20              | -                           |

|  <b>UL Recognized</b><br>Approval ID: E335019-20141210 |                       |                       |                   |                             |
|-----------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                                                                                                         | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Power                                                                                                                                   | 48 V                  | 20 A                  | - 14              | -                           |
| Signal                                                                                                                                  | 48 V                  | 6 A                   | - 20              | -                           |

| <b>cULus Recognized</b> |  |  |  |  |
|-------------------------|--|--|--|--|
|-------------------------|--|--|--|--|

# CA-09P1N8AT007S - Cable connector



1619387

<https://www.phoenixcontact.com/pc/products/1619387>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27440102 |
| ECLASS-12.0 | 27440116 |
| ECLASS-13.0 | 27440116 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002635 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

Environmental product compliance

|                                         |                                                                                                                                                                                                                                   |
|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS                                 |                                                                                                                                                                                                                                   |
| Fulfills EU RoHS substance requirements | Yes                                                                                                                                                                                                                               |
| Exemption                               | 6(c)                                                                                                                                                                                                                              |
| China RoHS                              |                                                                                                                                                                                                                                   |
| Environment friendly use period (EFUP)  | EFUP-50                                                                                                                                                                                                                           |
|                                         | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |
| EU REACH SVHC                           |                                                                                                                                                                                                                                   |
| REACH candidate substance (CAS No.)     | Lead(CAS: 7439-92-1)                                                                                                                                                                                                              |
| SCIP                                    | 870ea7f2-ad15-4a8a-8fee-8394f1d92a51                                                                                                                                                                                              |

# CA-09P1N8AT007S - Cable connector



1619387

<https://www.phoenixcontact.com/pc/products/1619387>

## Accessories

### RC-5CP2000 - Crimp contact

1603513

<https://www.phoenixcontact.com/pc/products/1603513>



Crimp contact, Pin, turned, contact diameter: 2 mm, crimp range: 1 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241634

---

### RC-5AP2000 - Crimp contact

1603505

<https://www.phoenixcontact.com/pc/products/1603505>



Crimp contact, Pin, turned, contact diameter: 2 mm, crimp range: 1.5 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241634

## CA-09P1N8AT007S - Cable connector

1619387

<https://www.phoenixcontact.com/pc/products/1619387>



## RC-5SP2000 - Crimp contact

1603529

<https://www.phoenixcontact.com/pc/products/1603529>



Crimp contact, Pin, turned, contact diameter: 2 mm, crimp range: 0.5 mm<sup>2</sup> ... 0.75 mm<sup>2</sup>, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241632

---

## SF-Z0028 - Torque screwdriver

1607456

<https://www.phoenixcontact.com/pc/products/1607456>



Torque screwdriver, series: RC, UC, SH, SF

## CA-09P1N8AT007S - Cable connector

1619387

<https://www.phoenixcontact.com/pc/products/1619387>



## SF-Z0027 - Hook wrench

1607455

<https://www.phoenixcontact.com/pc/products/1607455>



Hook wrench, series: RC, UC, RF, SF

---

## RF-Z0014 - Color coding

1620588

<https://www.phoenixcontact.com/pc/products/1620588>



Color coding, color: green

# CA-09P1N8AT007S - Cable connector

1619387

<https://www.phoenixcontact.com/pc/products/1619387>



## RF-Z0015 - Color coding

1620592

<https://www.phoenixcontact.com/pc/products/1620592>

Color coding, color: orange



---

## RF-Z0016 - Color coding

1620593

<https://www.phoenixcontact.com/pc/products/1620593>

Color coding, color: black



## CA-09P1N8AT007S - Cable connector

1619387

<https://www.phoenixcontact.com/pc/products/1619387>



## PROT-M23-SG-IT-IP20 - Plastic protective cap

1577206

<https://www.phoenixcontact.com/pc/products/1577206>



Plastic protective cap, M23, degree of protection: IP20, series: CA, RC, RF, UC, RM

---

## RC-11P2000 - Crimp contact

1596770

<https://www.phoenixcontact.com/pc/products/1596770>



Crimp contact, Pin, turned, Single contact, contact diameter: 1 mm, crimp range: 0.08 mm<sup>2</sup> ... 0.22 mm<sup>2</sup>, Contact release tool not necessary for the 12- and 17-pos. crimp versions of the M23-PRO series, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1240882

# CA-09P1N8AT007S - Cable connector



1619387

<https://www.phoenixcontact.com/pc/products/1619387>

## RC-12P2000 - Crimp contact

1597862

<https://www.phoenixcontact.com/pc/products/1597862>



Crimp contact, Pin, turned, Single contact, contact diameter: 1 mm, crimp range: 0.14 mm<sup>2</sup> ... 0.56 mm<sup>2</sup>, Contact release tool not necessary for the 12- and 17-pos. crimp versions of the M23-PRO series, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1240882

---

## RC-1KP2000 - Crimp contact

1602996

<https://www.phoenixcontact.com/pc/products/1602996>



Crimp contact, Pin, turned, Single contact, contact diameter: 1 mm, crimp range: 0.5 mm<sup>2</sup> ... 1 mm<sup>2</sup>, Contact release tool not necessary for the 12- and 17-pos. crimp versions of the M23-PRO series, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241571

## CA-09P1N8AT007S - Cable connector

1619387

<https://www.phoenixcontact.com/pc/products/1619387>



### RC-22P2000 - Crimp contact

1603321

<https://www.phoenixcontact.com/pc/products/1603321>



Crimp contact, Pin, rolled, Single contact, contact diameter: 1 mm, crimp range: 0.22 mm<sup>2</sup> ... 0.56 mm<sup>2</sup>, Single contact, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb < 0.1 %)

---

### RC-22P2300 - Crimp contact

1603324

<https://www.phoenixcontact.com/pc/products/1603324>



Crimp contact, Pin, rolled, Taped product, number of pieces per reel: 500, contact diameter: 1 mm, crimp range: 0.22 mm<sup>2</sup> ... 0.56 mm<sup>2</sup>, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb < 0.1 %)

## CA-09P1N8AT007S - Cable connector

1619387

<https://www.phoenixcontact.com/pc/products/1619387>



## RC-22P2400 - Crimp contact

1603325

<https://www.phoenixcontact.com/pc/products/1603325>



Crimp contact, Pin, rolled, Taped product, number of pieces per reel: 10000, contact diameter: 1 mm, crimp range: 0.22 mm<sup>2</sup> ... 0.56 mm<sup>2</sup>, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb < 0.1 %)

## RC-21P2000 - Crimp contact

1603310

<https://www.phoenixcontact.com/pc/products/1603310>



Crimp contact, Pin, rolled, Single contact, contact diameter: 1 mm, crimp range: 0.08 mm<sup>2</sup> ... 0.22 mm<sup>2</sup>, Single contact

# CA-09P1N8AT007S - Cable connector

1619387

<https://www.phoenixcontact.com/pc/products/1619387>



## RC-21P2300 - Crimp contact

1603313

<https://www.phoenixcontact.com/pc/products/1603313>



Crimp contact, Pin, rolled, Taped product, number of pieces per reel: 500, contact diameter: 1 mm, crimp range: 0.08 mm<sup>2</sup> ... 0.22 mm<sup>2</sup>

---

## RC-21P2400 - Crimp contact

1611637

<https://www.phoenixcontact.com/pc/products/1611637>



Crimp contact, Pin, rolled, Taped product, number of pieces per reel: 10000, contact diameter: 1 mm, crimp range: 0.08 mm<sup>2</sup> ... 0.22 mm<sup>2</sup>

---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)