

# CA-09P1N128007S - Cable connector



1619525

<https://www.phoenixcontact.com/us/products/1619525>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Cable connector, series: CA, straight, shielded: yes, SPEEDCON, No. of pos.: 8+1, Direction of rotation: Standard, contact connection type: Pin, Solder connection, cable diameter range: 6 mm ... 10 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1243635

## Your advantages

- Safe use in the field, thanks to high degree of protection
- Connector for flexible on-site assembly
- Consistent EMC protection for reliable transmission of signals
- Reduced connection time with SPEEDCON fast locking system
- Solder connection: proven connection technology for various litz wires

## Commercial data

|                                      |                    |
|--------------------------------------|--------------------|
| Item number                          | 1619525            |
| Packing unit                         | 1 pc               |
| Minimum order quantity               | 1 pc               |
| Sales key                            | AB31               |
| Product key                          | ABRAEB             |
| Catalog page                         | Page 84 (C-2-2019) |
| GTIN                                 | 4046356823302      |
| Weight per piece (including packing) | 94 g               |
| Weight per piece (excluding packing) | 94 g               |
| Customs tariff number                | 85366990           |
| Country of origin                    | DE                 |

# CA-09P1N128007S - Cable connector



1619525

<https://www.phoenixcontact.com/us/products/1619525>

## Technical data

### Product properties

|              |                                 |
|--------------|---------------------------------|
| Product type | Circular connector (cable-side) |
|--------------|---------------------------------|

### Connector

#### Insulating body

|                                                     |                     |
|-----------------------------------------------------|---------------------|
| Coding                                              | N                   |
| Insulation body material                            | PBT                 |
| Contact material                                    | CuZn                |
| Contact surface material                            | Ni/Au               |
| Insertion/withdrawal cycles                         | 100                 |
| Connection method                                   | Solder connection   |
| Contact switching type                              | Pin                 |
| Application                                         | Signal              |
| Number of positions                                 | 9                   |
| Direction of rotation                               | Standard            |
| Connection profile                                  | 8+1                 |
| Contact diameter <b>Power contacts</b>              | 2 mm                |
| Litz wire cross-section <b>Power contacts max.</b>  | 2.5 mm <sup>2</sup> |
| Rated current <b>Power contacts</b>                 | 20 A                |
| Rated voltage                                       | 48 V AC             |
|                                                     | 74 V DC             |
| Rated surge voltage                                 | 1.5 kV              |
| Overvoltage category                                | III                 |
| Degree of pollution                                 | 3                   |
| Contact diameter <b>Signal contacts</b>             | 1 mm                |
| Litz wire cross-section <b>Signal contacts max.</b> | 1 mm <sup>2</sup>   |
| Nominal current per signal contact                  | 8 A                 |

#### Housing

|                                   |             |
|-----------------------------------|-------------|
| Housing material                  | CuZn, GD-Zn |
| Type of locking                   | SPEEDCON    |
| Pg screw connection               | none        |
| Degree of protection (plugged in) | IP67        |
| Thread type                       | M23         |

#### Seal

|                         |                |
|-------------------------|----------------|
| External cable diameter | 6 mm ... 10 mm |
| Seal material           | NBR            |

### Environmental and real-life conditions

# CA-09P1N128007S - Cable connector



1619525

<https://www.phoenixcontact.com/us/products/1619525>

Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 125 °C |
|---------------------------------|-------------------|

# CA-09P1N128007S - Cable connector


1619525

<https://www.phoenixcontact.com/us/products/1619525>



## Drawings

Schematic diagram



Connector pin assignment


# CA-09P1N128007S - Cable connector

1619525

<https://www.phoenixcontact.com/us/products/1619525>



Dimensional drawing



Technical drawings can be found under Downloads

# CA-09P1N128007S - Cable connector



1619525

<https://www.phoenixcontact.com/us/products/1619525>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1619525>

|  <b>cUL Recognized</b><br>Approval ID: E335019-20141210 |                       |                       |                   |                             |
|------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                                                                                                          | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Power                                                                                                                                    | 48 V                  | 12 A                  | - 14              | -                           |
| Signal                                                                                                                                   | 48 V                  | 6 A                   | - 18              | -                           |

|  <b>UL Recognized</b><br>Approval ID: E335019-20141210 |                       |                       |                   |                             |
|-----------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                                                                                                         | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Power                                                                                                                                   | 48 V                  | 20 A                  | - 14              | -                           |
| Signal                                                                                                                                  | 48 V                  | 8 A                   | - 18              | -                           |

|                         |  |  |  |  |
|-------------------------|--|--|--|--|
| <b>cULus Recognized</b> |  |  |  |  |
|-------------------------|--|--|--|--|

# CA-09P1N128007S - Cable connector



1619525

<https://www.phoenixcontact.com/us/products/1619525>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27440102 |
| ECLASS-12.0 | 27440116 |
| ECLASS-13.0 | 27440116 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002635 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# CA-09P1N128007S - Cable connector



1619525

<https://www.phoenixcontact.com/us/products/1619525>

## Environmental product compliance

|            |                                                                                                              |
|------------|--------------------------------------------------------------------------------------------------------------|
| REACH SVHC | Lead 7439-92-1                                                                                               |
| China RoHS | Environmentally Friendly Use Period = 50 years                                                               |
|            | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)