

# CA-06S1N8A8007S - Cable connector



1619532

<https://www.phoenixcontact.com/us/products/1619532>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Cable connector, series: CA, straight, shielded: yes, SPEEDCON, No. of pos.: 6, Direction of rotation: Standard, contact connection type: Socket, Crimp connection, cable diameter range: 6 mm ... 10 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1243642

## Your advantages

- Safe use in the field, thanks to high degree of protection
- Connector for flexible on-site assembly
- Consistent EMC protection for reliable transmission of signals
- Reduced connection time with SPEEDCON fast locking system
- Crimping connection: vibration- and temperature-resistant assembly

## Commercial data

|                                      |                    |
|--------------------------------------|--------------------|
| Item number                          | 1619532            |
| Packing unit                         | 1 pc               |
| Minimum order quantity               | 1 pc               |
| Sales key                            | AB31               |
| Product key                          | ABRAEB             |
| Catalog page                         | Page 84 (C-2-2019) |
| GTIN                                 | 4046356823234      |
| Weight per piece (including packing) | 90 g               |
| Weight per piece (excluding packing) | 90 g               |
| Customs tariff number                | 85366990           |
| Country of origin                    | DE                 |

# CA-06S1N8A8007S - Cable connector



1619532

<https://www.phoenixcontact.com/us/products/1619532>

## Technical data

### Notes

|                    |  |
|--------------------|--|
| Order information: | Order crimp contacts 6 x Ø 2 mm separately |
|--------------------|--|

### Product properties

|              |                                 |
|--------------|---------------------------------|
| Product type | Circular connector (cable-side) |
|--------------|---------------------------------|

### Data management status

|                  |    |
|------------------|----|
| Article revision | 07 |
|------------------|----|

### Connector

#### Connection 1

|             |        |
|-------------|--------|
| Head design | Socket |
|-------------|--------|

#### Insulating body

|   |   |
|---|---|
| Note  | Order information: Order crimp contacts Ø 2 mm separately |
| Coding  | N   |
| Insulation body material                            | PA 6.6  |
| Connection method                                   | Crimp connection  |
| Contact switching type                              | Socket  |
| Application   | Signal  |
| Number of positions                                 | 6   |
| Direction of rotation                               | Standard  |
| Connection profile                                  | 6   |
| Contact diameter <b>Signal contacts</b>             | 2 mm  |
| Litz wire cross-section <b>Signal contacts</b> min. | 1 mm <sup>2</sup>   |
| Litz wire cross-section <b>Signal contacts</b> max. | 2.5 mm <sup>2</sup>                                       |
| Nominal current per signal contact                  | 20 A  |
| Rated voltage <b>Signal contact</b>                 | 48 V AC   |
| Rated surge voltage                                 | 1.5 kV  |
| Overvoltage category                                | III   |
| Degree of pollution                                 | 3   |

#### Housing

|                                   |             |
|-----------------------------------|-------------|
| Housing material                  | CuZn, GD-Zn |
| Type of locking                   | SPEEDCON    |
| Pg screw connection               | none        |
| Degree of protection (plugged in) | IP67        |
| Thread type                       | M23         |

#### Seal

|                         |                |
|-------------------------|----------------|
| External cable diameter | 6 mm ... 10 mm |
| Seal material           | NBR            |

# CA-06S1N8A8007S - Cable connector



1619532

<https://www.phoenixcontact.com/us/products/1619532>

## Environmental and real-life conditions

### Ambient conditions

|  |                   |
|--|-------------------|
| Ambient temperature (operation)          | -40 °C ... 125 °C |
| Ambient temperature (storage/transport)  | 15 °C ... 25 °C   |
| Permissible humidity (storage/transport) | 50 % ... 65 %     |

# CA-06S1N8A8007S - Cable connector



1619532

<https://www.phoenixcontact.com/us/products/1619532>

## Drawings

Schematic diagram



Connector pin assignment

# CA-06S1N8A8007S - Cable connector





1619532

<https://www.phoenixcontact.com/us/products/1619532>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1619532>

|  <b>cUL Recognized</b><br>Approval ID: E335019-20141210 |                       |                       |                   |                      |
|--|-----------------------|-----------------------|-------------------|----------------------|
|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $mm^2$ |
|  | 48 V                  | 10 A                  | 14 - 14           | -                    |

|  <b>UL Recognized</b><br>Approval ID: E335019-20141210 |                       |                       |                   |                      |
|---|-----------------------|-----------------------|-------------------|----------------------|
|   | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $mm^2$ |
|   | 48 V                  | 17 A                  | 14 - 14           | -                    |

| <b>cULus Recognized</b> |  |  |  |  |
|-------------------------|--|--|--|--|
|-------------------------|--|--|--|--|

# CA-06S1N8A8007S - Cable connector



1619532

<https://www.phoenixcontact.com/us/products/1619532>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27440102 |
| ECLASS-12.0 | 27440116 |
| ECLASS-13.0 | 27440116 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002635 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# CA-06S1N8A8007S - Cable connector



1619532

<https://www.phoenixcontact.com/us/products/1619532>

## Environmental product compliance

### EU RoHS

|   |      |
|---|------|
| Fulfills EU RoHS substance requirements | Yes  |
| Exemption                               | 6(c) |

### China RoHS

|  |   |
|--|---|
| Environment friendly use period (EFUP) | EFUP-50   |
|  | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

### EU REACH SVHC

|                                     |                                      |
|-------------------------------------|--------------------------------------|
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1)                 |
| SCIP                                | 76710b3c-4556-4b1d-a2e3-546c2b2ab6c3 |

# CA-06S1N8A8007S - Cable connector

1619532

<https://www.phoenixcontact.com/us/products/1619532>

## Accessories

### SF-Z0028 - Torque screwdriver

1607456

<https://www.phoenixcontact.com/us/products/1607456>

Torque screwdriver, series: RC, UC, SH, SF



---

### SF-Z0027 - Hook wrench

1607455

<https://www.phoenixcontact.com/us/products/1607455>

Hook wrench, series: RC, UC, RF, SF



# CA-06S1N8A8007S - Cable connector

1619532


<https://www.phoenixcontact.com/us/products/1619532>

## RF-Z0014 - Color coding

1620588

<https://www.phoenixcontact.com/us/products/1620588>

Color coding, color: green



---

## RF-Z0015 - Color coding

1620592

<https://www.phoenixcontact.com/us/products/1620592>

Color coding, color: orange



## CA-06S1N8A8007S - Cable connector

1619532

<https://www.phoenixcontact.com/us/products/1619532>



### RF-Z0016 - Color coding

1620593

<https://www.phoenixcontact.com/us/products/1620593>

Color coding, color: black



---

### RC-5CS2000 - Crimp contact

1603517

<https://www.phoenixcontact.com/us/products/1603517>



Crimp contact, Socket, turned, contact diameter: 2 mm, crimp range: 1 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241635

## CA-06S1N8A8007S - Cable connector

1619532

<https://www.phoenixcontact.com/us/products/1619532>



## RC-5AS2000 - Crimp contact

1603509

<https://www.phoenixcontact.com/us/products/1603509>



Crimp contact, Socket, turned, contact diameter: 2 mm, crimp range: 1.5 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241635

---

## RF-Z0003 - Square mounting flange

1607905

<https://www.phoenixcontact.com/us/products/1607905>



Square mounting flange, Axial seal, 4xM3, flange dimensions: 35 mm x 35 mm, series: RF, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1242369

## CA-06S1N8A8007S - Cable connector

1619532

<https://www.phoenixcontact.com/us/products/1619532>



### RC-59S2000 - Crimp contact

1603501

<https://www.phoenixcontact.com/us/products/1603501>



Crimp contact, Socket, turned, Single contact, contact diameter: 2 mm, crimp range: 0.75 mm<sup>2</sup> ... 1 mm<sup>2</sup>, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241633

---

### RC-5SS2000 - Crimp contact

1603530

<https://www.phoenixcontact.com/us/products/1603530>



Crimp contact, Socket, turned, contact diameter: 2 mm, crimp range: 0.5 mm<sup>2</sup> ... 0.75 mm<sup>2</sup>, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241633

## CA-06S1N8A8007S - Cable connector

1619532

<https://www.phoenixcontact.com/us/products/1619532>



## CA-Z0077 - Metal protective cap

1627224

<https://www.phoenixcontact.com/us/products/1627224>



Metal protective cap, degree of protection: IP67, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1245447

---

## PROT-M23-SG-IT-IP20 - Plastic protective cap

1577206

<https://www.phoenixcontact.com/us/products/1577206>



Plastic protective cap, M23, degree of protection: IP20, series: CA, RC, RF, UC, RM

---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)