

CA-07P1N8A8008 - Cable connector



1619652

<https://www.phoenixcontact.com/us/products/1619652>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Cable connector, series: CA, straight, shielded: yes, Screw locking mechanism, No. of pos. : 7, Direction of rotation: Standard, contact connection type: Pin, Crimp connection, cable diameter range: 10 mm ... 14.5 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1243741

Your advantages

- Safe use in the field, thanks to high degree of protection
- Connector for flexible on-site assembly
- Consistent EMC protection for reliable transmission of signals
- Crimping connection: vibration- and temperature-resistant assembly

Commercial data

Item number	1619652
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	AB31
Product key	ABRAEA
Catalog page	Page 86 (C-2-2019)
GTIN	4046356822268
Weight per piece (including packing)	91.31 g
Weight per piece (excluding packing)	91.3 g
Customs tariff number	85366990
Country of origin	DE

CA-07P1N8A8008 - Cable connector



1619652

<https://www.phoenixcontact.com/us/products/1619652>

Technical data

Notes

General	Order crimp contacts 6 x Ø 2 mm separately
---------	--

Product properties

Product type	Circular connector (cable-side)
--------------	---------------------------------

Connector

Insulating body

Note	Order information: Order 7 x Ø 2 mm crimp contacts separately
Coding	N
Insulation body material	PA 6.6
Connection method	Crimp connection
Contact switching type	Pin
Application	Signal
Number of positions	7
Direction of rotation	Standard
Connection profile	7
Contact diameter	2 mm
Litz wire cross-section	Signal contacts min. 1 mm ²
Litz wire cross-section	Signal contacts max. 2.5 mm ²
Nominal current per signal contact	20 A
Rated voltage	Signal contact 48 V AC
Rated surge voltage	1.5 kV
Overvoltage category	III
Degree of pollution	3

Housing

Housing material	Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Type of locking	Screw locking mechanism
Pg screw connection	none
Degree of protection (plugged in)	IP67
Thread type	M23

Seal

External cable diameter	10 mm ... 14.5 mm
Seal material	NBR

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

CA-07P1N8A8008 - Cable connector



1619652

<https://www.phoenixcontact.com/us/products/1619652>

Ambient temperature (storage/transport)	15 °C ... 25 °C
Permissible humidity (storage/transport)	50 % ... 65 %

CA-07P1N8A8008 - Cable connector


1619652

<https://www.phoenixcontact.com/us/products/1619652>



Drawings

Dimensional drawing



Technical drawings can be found under Downloads


CA-07P1N8A8008 - Cable connector

1619652

<https://www.phoenixcontact.com/us/products/1619652>



Schematic diagram



Connector pin assignment

CA-07P1N8A8008 - Cable connector



1619652

<https://www.phoenixcontact.com/us/products/1619652>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1619652>

 cUL Recognized Approval ID: E335019-20141210				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	48 V	10 A	- 14	-

 UL Recognized Approval ID: E335019-20141210				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	48 V	17 A	- 14	-

cULus Recognized				
-------------------------	--	--	--	--

CA-07P1N8A8008 - Cable connector



1619652

<https://www.phoenixcontact.com/us/products/1619652>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 9.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

CA-07P1N8A8008 - Cable connector



1619652

<https://www.phoenixcontact.com/us/products/1619652>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com