

# CA-06S1N8A8008 - Cable connector



1619657  
<https://www.phoenixcontact.com/us/products/1619657>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Cable connector, series: CA, straight, shielded: yes, Screw locking mechanism, No. of pos. : 6, Direction of rotation: Standard, contact connection type: Socket, Crimp connection, cable diameter range: 10 mm ... 14.5 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1243746

## Your advantages

- Safe use in the field, thanks to high degree of protection
- Connector for flexible on-site assembly
- Consistent EMC protection for reliable transmission of signals
- Crimping connection: vibration- and temperature-resistant assembly

## Commercial data

|                                      |                    |
|--------------------------------------|--------------------|
| Item number                          | 1619657            |
| Packing unit                         | 1 pc               |
| Minimum order quantity               | 1 pc               |
| Sales key                            | AB31               |
| Product key                          | ABRAEA             |
| Catalog page                         | Page 86 (C-2-2019) |
| GTIN                                 | 4046356822213      |
| Weight per piece (including packing) | 88.8 g             |
| Weight per piece (excluding packing) | 88.8 g             |
| Customs tariff number                | 85366990           |
| Country of origin                    | DE                 |

# CA-06S1N8A8008 - Cable connector



1619657

<https://www.phoenixcontact.com/us/products/1619657>

## Technical data

### Notes

|         |                                            |
|---------|--------------------------------------------|
| General | Order crimp contacts 6 x Ø 2 mm separately |
|---------|--------------------------------------------|

### Product properties

|              |                                 |
|--------------|---------------------------------|
| Product type | Circular connector (cable-side) |
|--------------|---------------------------------|

### Connector

#### Connection 1

|             |        |
|-------------|--------|
| Head design | Socket |
|-------------|--------|

#### Insulating body

|                                    |                                                           |
|------------------------------------|-----------------------------------------------------------|
| Note                               | Order information: Order crimp contacts Ø 2 mm separately |
| Coding                             | N                                                         |
| Insulation body material           | PA 6.6                                                    |
| Connection method                  | Crimp connection                                          |
| Contact switching type             | Socket                                                    |
| Application                        | Signal                                                    |
| Number of positions                | 6                                                         |
| Direction of rotation              | Standard                                                  |
| Connection profile                 | 6                                                         |
| Contact diameter                   | 2 mm                                                      |
| Litz wire cross-section            | 1 mm <sup>2</sup>                                         |
| Litz wire cross-section            | 2.5 mm <sup>2</sup>                                       |
| Nominal current per signal contact | 20 A                                                      |
| Rated voltage Signal contact       | 48 V AC                                                   |
| Rated surge voltage                | 1.5 kV                                                    |
| Overvoltage category               | III                                                       |
| Degree of pollution                | 3                                                         |

#### Housing

|                                   |                                                                      |
|-----------------------------------|----------------------------------------------------------------------|
| Housing material                  | Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn) |
| Type of locking                   | Screw locking mechanism                                              |
| Pg screw connection               | none                                                                 |
| Degree of protection (plugged in) | IP67                                                                 |
| Thread type                       | M23                                                                  |

#### Seal

|                         |                   |
|-------------------------|-------------------|
| External cable diameter | 10 mm ... 14.5 mm |
| Seal material           | NBR               |

## Environmental and real-life conditions

# CA-06S1N8A8008 - Cable connector



1619657

<https://www.phoenixcontact.com/us/products/1619657>

## Ambient conditions

|                                          |                   |
|------------------------------------------|-------------------|
| Ambient temperature (operation)          | -40 °C ... 125 °C |
| Ambient temperature (storage/transport)  | 15 °C ... 25 °C   |
| Permissible humidity (storage/transport) | 50 % ... 65 %     |

# CA-06S1N8A8008 - Cable connector

1619657

<https://www.phoenixcontact.com/us/products/1619657>



## Drawings

Schematic diagram



Connector pin assignment


# CA-06S1N8A8008 - Cable connector

1619657

<https://www.phoenixcontact.com/us/products/1619657>



Dimensional drawing



Technical drawings can be found under Downloads

# CA-06S1N8A8008 - Cable connector



1619657  
<https://www.phoenixcontact.com/us/products/1619657>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1619657>

|                                                                                                                                          |                       |                       |                   |                             |
|------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|  <b>cUL Recognized</b><br>Approval ID: E335019-20141210 |                       |                       |                   |                             |
|                                                                                                                                          | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                                                                                                                          | 48 V                  | 10 A                  | - 14              | -                           |

|                                                                                                                                         |                       |                       |                   |                             |
|-----------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|  <b>UL Recognized</b><br>Approval ID: E335019-20141210 |                       |                       |                   |                             |
|                                                                                                                                         | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                                                                                                                         | 48 V                  | 17 A                  | - 14              | -                           |

|                         |  |  |  |  |
|-------------------------|--|--|--|--|
| <b>cULus Recognized</b> |  |  |  |  |
|-------------------------|--|--|--|--|

# CA-06S1N8A8008 - Cable connector



1619657

<https://www.phoenixcontact.com/us/products/1619657>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27440102 |
| ECLASS-12.0 | 27440116 |
| ECLASS-13.0 | 27440116 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002635 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# CA-06S1N8A8008 - Cable connector



1619657  
<https://www.phoenixcontact.com/us/products/1619657>

## Environmental product compliance

|            |                                                                                                              |
|------------|--------------------------------------------------------------------------------------------------------------|
| REACH SVHC | Lead 7439-92-1                                                                                               |
| China RoHS | Environmentally Friendly Use Period = 50 years                                                               |
|            | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)