

# CA-12P1N8A8006 - Cable connector



1619735

<https://www.phoenixcontact.com/us/products/1619735>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Cable connector, series: CA, straight, shielded: yes, Screw locking mechanism, No. of pos. : 12, Direction of rotation: Standard, contact connection type: Pin, Crimp connection, cable diameter range: 4 mm ... 6 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1243787

## Your advantages

- Safe use in the field, thanks to high degree of protection
- Connector for flexible on-site assembly
- Consistent EMC protection for reliable transmission of signals
- Crimping connection: vibration- and temperature-resistant assembly

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 1619735                        |
| Packing unit                         | 1 pc                           |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | AB31                           |
| Product key                          | ABRAEA                         |
| Catalog page                         | Page 86 (C-2-2019)             |
| GTIN                                 | 4046356821827                  |
| Weight per piece (including packing) | 95 g                           |
| Weight per piece (excluding packing) | 94 g                           |
| Customs tariff number                | 85366990                       |
| Country of origin                    | DE                             |

# CA-12P1N8A8006 - Cable connector



1619735

<https://www.phoenixcontact.com/us/products/1619735>

## Technical data

### Notes

|                    |   |
|--------------------|---|
| Order information: | Order 12 x 1 mm crimp contacts separately |
|--------------------|---|

### Product properties

|              |                                 |
|--------------|---------------------------------|
| Product type | Circular connector (cable-side) |
|--------------|---------------------------------|

### Data management status

|                  |    |
|------------------|----|
| Article revision | 05 |
|------------------|----|

### Connector

#### Insulating body

|                                    |   |
|------------------------------------|---|
| Note                               | Order information: Order crimp contacts Ø 1 mm separately |
| Coding                             | N   |
| Insulation body material           | PA 6.6  |
| Connection method                  | Crimp connection  |
| Contact switching type             | Pin   |
| Application                        | Signal  |
| Number of positions                | 12  |
| Direction of rotation              | Standard  |
| Connection profile                 | 12  |
| Contact diameter                   | Signal contacts 1 mm                                      |
| Litz wire cross-section            | Signal contacts min. 0.08 mm <sup>2</sup>                 |
| Litz wire cross-section            | Signal contacts max. 1 mm <sup>2</sup>                    |
| Nominal current per signal contact | 8 A   |
| Rated voltage                      | Signal contact 48 V AC                                    |
| Rated surge voltage                | 1.5 kV  |
| Overvoltage category               | III   |
| Degree of pollution                | 3   |

#### Housing

|                                   |  |
|-----------------------------------|--|
| Housing material                  | Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn) |
| Type of locking                   | Screw locking mechanism  |
| Pg screw connection               | none   |
| Degree of protection (plugged in) | IP67   |
| Thread type                       | M23  |

#### Seal

|                         |               |
|-------------------------|---------------|
| External cable diameter | 4 mm ... 6 mm |
| Seal material           | NBR           |

## Environmental and real-life conditions

# CA-12P1N8A8006 - Cable connector



1619735

<https://www.phoenixcontact.com/us/products/1619735>

## Ambient conditions

|  |                   |
|--|-------------------|
| Ambient temperature (operation)          | -40 °C ... 125 °C |
| Ambient temperature (storage/transport)  | 15 °C ... 25 °C   |
| Permissible humidity (storage/transport) | 50 % ... 65 %     |

# CA-12P1N8A8006 - Cable connector


1619735

<https://www.phoenixcontact.com/us/products/1619735>



## Drawings

Schematic diagram



Connector pin assignment

# CA-12P1N8A8006 - Cable connector





1619735

<https://www.phoenixcontact.com/us/products/1619735>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1619735>

|  |                       |                       |                   |                             |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  <b>cUL Recognized</b><br>Approval ID: E335019-20141210 |                       |                       |                   |                             |
|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|  | 48 V                  | 4 A                   | 20 - 20           | -                           |

|   |                       |                       |                   |                             |
|---|-----------------------|-----------------------|-------------------|-----------------------------|
|  <b>UL Recognized</b><br>Approval ID: E335019-20141210 |                       |                       |                   |                             |
|   | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|   | 48 V                  | 6 A                   | 20 - 20           | -                           |

|                         |  |  |  |  |
|-------------------------|--|--|--|--|
| <b>cULus Recognized</b> |  |  |  |  |
|-------------------------|--|--|--|--|

# CA-12P1N8A8006 - Cable connector



1619735

<https://www.phoenixcontact.com/us/products/1619735>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27440102 |
| ECLASS-12.0 | 27440116 |
| ECLASS-13.0 | 27440116 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002635 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# CA-12P1N8A8006 - Cable connector



1619735

<https://www.phoenixcontact.com/us/products/1619735>

## Environmental product compliance

|   |      |
|---|------|
| EU RoHS                                 |      |
| Fulfills EU RoHS substance requirements | Yes  |
| Exemption                               | 6(c) |

|  |   |
|--|---|
| China RoHS                             |   |
| Environment friendly use period (EFUP) | EFUP-50   |
|  | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

|                                     |                                      |
|-------------------------------------|--------------------------------------|
| EU REACH SVHC                       |                                      |
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1)                 |
| SCIP                                | eeb7ba5f-0862-4976-bc7c-f7eb303ec787 |

# CA-12P1N8A8006 - Cable connector

1619735

<https://www.phoenixcontact.com/us/products/1619735>



## Accessories

### CA-Z0077 - Metal protective cap

1627224

<https://www.phoenixcontact.com/us/products/1627224>



Metal protective cap, degree of protection: IP67, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1245447

---

### SF-Z0028 - Torque screwdriver

1607456

<https://www.phoenixcontact.com/us/products/1607456>



Torque screwdriver, series: RC, UC, SH, SF



## CA-12P1N8A8006 - Cable connector

1619735

<https://www.phoenixcontact.com/us/products/1619735>



## SF-Z0027 - Hook wrench

1607455

<https://www.phoenixcontact.com/us/products/1607455>



Hook wrench, series: RC, UC, RF, SF

---

## RF-Z0014 - Color coding

1620588

<https://www.phoenixcontact.com/us/products/1620588>



Color coding, color: green

# CA-12P1N8A8006 - Cable connector

1619735

<https://www.phoenixcontact.com/us/products/1619735>




## RF-Z0015 - Color coding

1620592

<https://www.phoenixcontact.com/us/products/1620592>

Color coding, color: orange



---

## RF-Z0016 - Color coding

1620593

<https://www.phoenixcontact.com/us/products/1620593>

Color coding, color: black



## CA-12P1N8A8006 - Cable connector

1619735

<https://www.phoenixcontact.com/us/products/1619735>



## RF-Z0003 - Square mounting flange

1607905

<https://www.phoenixcontact.com/us/products/1607905>



Square mounting flange, Axial seal, 4xM3, flange dimensions: 35 mm x 35 mm, series: RF, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1242369

---

## PROT-M23-SG-IT-IP20 - Plastic protective cap

1577206

<https://www.phoenixcontact.com/us/products/1577206>



Plastic protective cap, M23, degree of protection: IP20, series: CA, RC, RF, UC, RM

# CA-12P1N8A8006 - Cable connector



1619735

<https://www.phoenixcontact.com/us/products/1619735>

## RC-11P2000 - Crimp contact

1596770

<https://www.phoenixcontact.com/us/products/1596770>



Crimp contact, Pin, turned, Single contact, contact diameter: 1 mm, crimp range: 0.08 mm<sup>2</sup> ... 0.22 mm<sup>2</sup>, Contact release tool not necessary for the 12- and 17-pos. crimp versions of the M23-PRO series, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1240882

---

## RC-12P2000 - Crimp contact

1597862

<https://www.phoenixcontact.com/us/products/1597862>



Crimp contact, Pin, turned, Single contact, contact diameter: 1 mm, crimp range: 0.14 mm<sup>2</sup> ... 0.56 mm<sup>2</sup>, Contact release tool not necessary for the 12- and 17-pos. crimp versions of the M23-PRO series, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1240882

## CA-12P1N8A8006 - Cable connector

1619735

<https://www.phoenixcontact.com/us/products/1619735>



### RC-1KP2000 - Crimp contact

1602996

<https://www.phoenixcontact.com/us/products/1602996>



Crimp contact, Pin, turned, Single contact, contact diameter: 1 mm, crimp range: 0.5 mm<sup>2</sup> ... 1 mm<sup>2</sup>, Contact release tool not necessary for the 12- and 17-pos. crimp versions of the M23-PRO series, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241571

---

### RC-22P2000 - Crimp contact

1603321

<https://www.phoenixcontact.com/us/products/1603321>



Crimp contact, Pin, rolled, Single contact, contact diameter: 1 mm, crimp range: 0.22 mm<sup>2</sup> ... 0.56 mm<sup>2</sup>, Single contact, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb < 0.1 %)

# CA-12P1N8A8006 - Cable connector

1619735

<https://www.phoenixcontact.com/us/products/1619735>



## RC-22P2300 - Crimp contact

1603324

<https://www.phoenixcontact.com/us/products/1603324>



Crimp contact, Pin, rolled, Taped product, number of pieces per reel: 500, contact diameter: 1 mm, crimp range: 0.22 mm<sup>2</sup> ... 0.56 mm<sup>2</sup>, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb < 0.1 %)

---

## RC-22P2400 - Crimp contact

1603325

<https://www.phoenixcontact.com/us/products/1603325>



Crimp contact, Pin, rolled, Taped product, number of pieces per reel: 10000, contact diameter: 1 mm, crimp range: 0.22 mm<sup>2</sup> ... 0.56 mm<sup>2</sup>, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb < 0.1 %)

## CA-12P1N8A8006 - Cable connector

1619735

<https://www.phoenixcontact.com/us/products/1619735>



### RC-21P2000 - Crimp contact

1603310

<https://www.phoenixcontact.com/us/products/1603310>



Crimp contact, Pin, rolled, Single contact, contact diameter: 1 mm, crimp range: 0.08 mm<sup>2</sup> ... 0.22 mm<sup>2</sup>, Single contact

---

### RC-21P2300 - Crimp contact

1603313

<https://www.phoenixcontact.com/us/products/1603313>



Crimp contact, Pin, rolled, Taped product, number of pieces per reel: 500, contact diameter: 1 mm, crimp range: 0.08 mm<sup>2</sup> ... 0.22 mm<sup>2</sup>

# CA-12P1N8A8006 - Cable connector

1619735

<https://www.phoenixcontact.com/us/products/1619735>



## RC-21P2400 - Crimp contact

1611637

<https://www.phoenixcontact.com/us/products/1611637>



Crimp contact, Pin, rolled, Taped product, number of pieces per reel: 10000, contact diameter: 1 mm, crimp range: 0.08 mm<sup>2</sup> ... 0.22 mm<sup>2</sup>

---

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)