

CA-09P1N8AHZ00 - Device connector rear mounting



1619791

<https://www.phoenixcontact.com/us/products/1619791>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Device connector rear mounting, series: CA, straight, shielded: yes, for standard and SPEEDCON interlock, No. of pos.: 8+1, Direction of rotation: Standard, contact connection type: Pin, Crimp connection, Axial seal, Central fixing, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1243843

Your advantages

- Safe use in the field, thanks to high degree of protection
- Connector for flexible on-site assembly
- Consistent EMC protection for reliable transmission of signals
- Crimping connection: vibration- and temperature-resistant assembly
- Application-specific wall mounting optionally with thread or anti-rotation protection and lock nut

Commercial data

| | |
|--------------------------------------|--------------------------------|
| Item number | 1619791 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Note | Made to order (non-returnable) |
| Sales key | AB31 |
| Product key | ABRAER |
| Catalog page | Page 102 (C-2-2019) |
| GTIN | 4046356821261 |
| Weight per piece (including packing) | 50.2 g |
| Weight per piece (excluding packing) | 50.2 g |
| Customs tariff number | 85366990 |
| Country of origin | DE |

CA-09P1N8AHZ00 - Device connector rear mounting



1619791

<https://www.phoenixcontact.com/us/products/1619791>

Technical data

Notes

| | |
|---------|--|
| General | Order crimp contacts 8 x Ø 1 mm, 1 x Ø 2 mm separately |
|---------|--|

Product properties

| | |
|--------------|-----------------------------------|
| Product type | Circular connectors (device side) |
|--------------|-----------------------------------|

Connector

Insulating body

| | |
|---|---|
| Note | Order information: Order crimp contacts 8 x Ø 1 mm, 1 x Ø 2 mm separately |
| Coding | N |
| Insulation body material | PA 6.6 |
| Connection method | Crimp connection |
| Contact switching type | Pin |
| Application | Signal |
| Number of positions | 9 |
| Direction of rotation | Standard |
| Connection profile | 8+1 |
| Contact diameter Power contacts | 2 mm |
| Litz wire cross-section Power contacts min. | 1 mm ² |
| Litz wire cross-section Power contacts max. | 2.5 mm ² |
| Rated current Power contacts | 20 A |
| Rated voltage | 48 V AC 74 V DC |
| Rated surge voltage | 1.5 kV |
| Overvoltage category | III |
| Degree of pollution | 3 |
| Contact diameter Signal contacts | 1 mm |
| Litz wire cross-section Signal contacts min. | 0.08 mm ² |
| Litz wire cross-section Signal contacts max. | 1 mm ² |
| Nominal current per signal contact | 8 A |

Housing

| | |
|-----------------------------------|--|
| Housing material | Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn) |
| Type of locking | for standard and SPEEDCON interlock |
| Pg screw connection | none |
| Degree of protection (plugged in) | IP67 |
| Thread type | M23 |

CA-09P1N8AHZ00 - Device connector rear mounting



1619791

<https://www.phoenixcontact.com/us/products/1619791>

Environmental and real-life conditions

Ambient conditions

| | |
|--|-------------------|
| Ambient temperature (operation) | -40 °C ... 125 °C |
| Ambient temperature (storage/transport) | 15 °C ... 25 °C |
| Permissible humidity (storage/transport) | 50 % ... 65 % |

CA-09P1N8AHZ00 - Device connector rear mounting



1619791

<https://www.phoenixcontact.com/us/products/1619791>

Drawings

Schematic diagram



Connector pin assignment

CA-09P1N8AHZ00 - Device connector rear mounting





1619791

<https://www.phoenixcontact.com/us/products/1619791>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1619791>

|  cUL Recognized Approval ID: E335019-20141210 | | | | |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
| | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
| Power | 48 V | 12 A | - 14 | - |
| Signal | 48 V | 4 A | - 20 | - |

|  UL Recognized Approval ID: E335019-20141210 | | | | |
|---|-----------------------|-----------------------|-------------------|-----------------------------|
| | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
| Power | 48 V | 20 A | - 14 | - |
| Signal | 48 V | 6 A | - 20 | - |

| cULus Recognized | | | | |
|-------------------------|--|--|--|--|
|-------------------------|--|--|--|--|

CA-09P1N8AHZ00 - Device connector rear mounting



1619791

<https://www.phoenixcontact.com/us/products/1619791>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27440102 |
| ECLASS-12.0 | 27440116 |
| ECLASS-13.0 | 27440116 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC002635 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

CA-09P1N8AHZ00 - Device connector rear mounting



1619791

<https://www.phoenixcontact.com/us/products/1619791>

Environmental product compliance

| | |
|------------|--|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com