

1619895

<https://www.phoenixcontact.com/us/products/1619895>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Device connector front mounting, series: CA, straight, shielded: yes, for standard and SPEEDCON interlock, No. of pos.: 8+1, Direction of rotation: Standard, contact connection type: Socket, Solder connection, Axial seal, Central fastening Pg13,5, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1243878

Your advantages

- Safe use in the field, thanks to high degree of protection
- Connector for flexible on-site assembly
- Consistent EMC protection for reliable transmission of signals
- Solder connection: proven connection technology for various litz wires

Commercial data

| | |
|--------------------------------------|--------------------------------|
| Item number | 1619895 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Note | Made to order (non-returnable) |
| Sales key | AB31 |
| Product key | ABRAEL |
| Catalog page | Page 94 (C-2-2019) |
| GTIN | 4046356820714 |
| Weight per piece (including packing) | 26 g |
| Weight per piece (excluding packing) | 26 g |
| Customs tariff number | 85366990 |
| Country of origin | DE |

CA-09S1N126Z00 - Device connector front mounting



1619895

<https://www.phoenixcontact.com/us/products/1619895>

Technical data

Product properties

| | |
|------------------------|-----------------------------------|
| Product type | Circular connectors (device side) |
| Data management status | |
| Article revision | 05 |

Connector

| | |
|------------------------------------|---------------------|
| Insulating body | |
| Coding | N |
| Insulation body material | PBT |
| Contact material | CuZn |
| Contact surface material | Ni/Au |
| Insertion/withdrawal cycles | 100 |
| Connection method | Solder connection |
| Contact switching type | Socket |
| Application | Signal |
| Number of positions | 9 |
| Direction of rotation | Standard |
| Connection profile | 8+1 |
| Contact diameter | 2 mm |
| Power contacts | |
| Litz wire cross-section | 2.5 mm ² |
| Rated current | 20 A |
| Rated voltage | 48 V AC |
| | 74 V DC |
| Rated surge voltage | 1.5 kV |
| Overvoltage category | III |
| Degree of pollution | 3 |
| Contact diameter | 1 mm |
| Signal contacts | |
| Litz wire cross-section | 1 mm ² |
| Nominal current per signal contact | 8 A |

Housing

| | |
|-----------------------------------|--|
| Order information: | If necessary, order locking nut separately |
| Housing material | CuZn |
| Type of locking | for standard and SPEEDCON interlock |
| Pg screw connection | none |
| Degree of protection (plugged in) | IP67 |
| Thread type | M23 |

Environmental and real-life conditions

CA-09S1N126Z00 - Device connector front mounting



1619895


<https://www.phoenixcontact.com/us/products/1619895>

Ambient conditions

| | |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 125 °C |
|---------------------------------|-------------------|

Drawings


Schematic diagram




Connector pin assignment

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1619895>

| <div> cUL Recognized Approval ID: E335019-20141210</div> | | | | |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
| | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
| Power | 48 V | 12 A | 14 - 14 | - |
| Signal | 48 V | 6 A | 18 - 18 | - |

| <div> UL Recognized Approval ID: E335019-20141210</div> | | | | |
|---|-----------------------|-----------------------|-------------------|-----------------------------|
| | Nominal voltage U_N | Nominal current I_N | Cross section AWG | Cross section mm^2 |
| Power | 48 V | 20 A | 14 - 14 | - |
| Signal | 48 V | 8 A | 18 - 18 | - |

| | | | | |
|------------------|--|--|--|--|
| cULus Recognized | | | | |
|------------------|--|--|--|--|

CA-09S1N126Z00 - Device connector front mounting



1619895

<https://www.phoenixcontact.com/us/products/1619895>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27440102 |
| ECLASS-12.0 | 27440116 |
| ECLASS-13.0 | 27440116 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC002635 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

Environmental product compliance

| | |
|---|---|
| EU RoHS | |
| Fulfills EU RoHS substance requirements | Yes |
| Exemption | 6(c) |
| China RoHS | |
| Environment friendly use period (EFUP) | EFUP-50 |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |
| EU REACH SVHC | |
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1) |
| SCIP | 5a59539b-3142-4cde-976f-52ce39fa1262 |