

# CA-07S1N8AT007 - Cable connector



1620256  
<https://www.phoenixcontact.com/us/products/1620256>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Cable connector, series: CA, angled, shielded: yes, Screw locking mechanism, No. of pos.: 7, Direction of rotation: Standard, contact connection type: Socket, Crimp connection, cable diameter range: 6 mm ... 10 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1244107

## Your advantages

- Angled cable outlet for confined spaces
- Can be adapted to various applications, thanks to adjustable cable outlet direction
- Safe use in the field, thanks to high degree of protection
- Connector for flexible on-site assembly
- Consistent EMC protection for reliable transmission of signals
- Crimping connection: vibration- and temperature-resistant assembly

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 1620256                        |
| Packing unit                         | 1 pc                           |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | AB31                           |
| Product key                          | ABRAEC                         |
| Catalog page                         | Page 92 (C-2-2019)             |
| GTIN                                 | 4046356818278                  |
| Weight per piece (including packing) | 186.7 g                        |
| Weight per piece (excluding packing) | 186.7 g                        |
| Customs tariff number                | 85366990                       |
| Country of origin                    | DE                             |

# CA-07S1N8AT007 - Cable connector



1620256

<https://www.phoenixcontact.com/us/products/1620256>

## Technical data

### Product properties

|              |                                 |
|--------------|---------------------------------|
| Product type | Circular connector (cable-side) |
|--------------|---------------------------------|

### Connector

#### Connection 1

|             |        |
|-------------|--------|
| Head design | Socket |
|-------------|--------|

#### Insulating body

|                                    |                                                           |
|------------------------------------|-----------------------------------------------------------|
| Note                               | Order information: Order crimp contacts Ø 2 mm separately |
| Coding                             | N                                                         |
| Insulation body material           | PA 6.6                                                    |
| Connection method                  | Crimp connection                                          |
| Contact switching type             | Socket                                                    |
| Application                        | Signal                                                    |
| Number of positions                | 7                                                         |
| Direction of rotation              | Standard                                                  |
| Connection profile                 | 7                                                         |
| Contact diameter                   | 2 mm                                                      |
| Litz wire cross-section            | Signal contacts min. 1 mm <sup>2</sup>                    |
| Litz wire cross-section            | Signal contacts max. 2.5 mm <sup>2</sup>                  |
| Nominal current per signal contact | 20 A                                                      |
| Rated voltage Signal contact       | 48 V AC                                                   |
| Rated surge voltage                | 1.5 kV                                                    |
| Overvoltage category               | III                                                       |
| Degree of pollution                | 3                                                         |

#### Housing

|                                   |                                                                      |
|-----------------------------------|----------------------------------------------------------------------|
| Housing material                  | Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn) |
| Type of locking                   | Screw locking mechanism                                              |
| Pg screw connection               | none                                                                 |
| Degree of protection (plugged in) | IP67                                                                 |
| Thread type                       | M23                                                                  |

#### Seal

|                         |                |
|-------------------------|----------------|
| External cable diameter | 6 mm ... 10 mm |
| Seal material           | NBR            |

### Environmental and real-life conditions

#### Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 125 °C |
|---------------------------------|-------------------|

# CA-07S1N8AT007 - Cable connector



1620256

<https://www.phoenixcontact.com/us/products/1620256>

|                                          |                 |
|------------------------------------------|-----------------|
| Ambient temperature (storage/transport)  | 15 °C ... 25 °C |
| Permissible humidity (storage/transport) | 50 % ... 65 %   |

# CA-07S1N8AT007 - Cable connector

1620256

<https://www.phoenixcontact.com/us/products/1620256>



## Drawings

Schematic diagram



Connector pin assignment


# CA-07S1N8AT007 - Cable connector

1620256

<https://www.phoenixcontact.com/us/products/1620256>



Dimensional drawing



Dimensional drawing

# CA-07S1N8AT007 - Cable connector



1620256

<https://www.phoenixcontact.com/us/products/1620256>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1620256>

|                                                                                                                                          |                                |                                |                   |                               |
|------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|--------------------------------|-------------------|-------------------------------|
|  <b>cUL Recognized</b><br>Approval ID: E335019-20141210 |                                |                                |                   |                               |
|                                                                                                                                          | Nominal voltage U <sub>N</sub> | Nominal current I <sub>N</sub> | Cross section AWG | Cross section mm <sup>2</sup> |
|                                                                                                                                          | 48 V                           | 10 A                           | - 14              | -                             |

|                                                                                                                                         |                                |                                |                   |                               |
|-----------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|--------------------------------|-------------------|-------------------------------|
|  <b>UL Recognized</b><br>Approval ID: E335019-20141210 |                                |                                |                   |                               |
|                                                                                                                                         | Nominal voltage U <sub>N</sub> | Nominal current I <sub>N</sub> | Cross section AWG | Cross section mm <sup>2</sup> |
|                                                                                                                                         | 48 V                           | 17 A                           | - 14              | -                             |

|                         |  |  |  |  |
|-------------------------|--|--|--|--|
| <b>cULus Recognized</b> |  |  |  |  |
|-------------------------|--|--|--|--|

# CA-07S1N8AT007 - Cable connector



1620256

<https://www.phoenixcontact.com/us/products/1620256>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27440102 |
| ECLASS-12.0 | 27440116 |
| ECLASS-13.0 | 27440116 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002635 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# CA-07S1N8AT007 - Cable connector



1620256

<https://www.phoenixcontact.com/us/products/1620256>

## Environmental product compliance

|            |                                                                                                              |
|------------|--------------------------------------------------------------------------------------------------------------|
| REACH SVHC | Lead 7439-92-1                                                                                               |
| China RoHS | Environmentally Friendly Use Period = 50 years                                                               |
|            | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

# CA-07S1N8AT007 - Cable connector

1620256

<https://www.phoenixcontact.com/us/products/1620256>



## Accessories

### CA-Z0077 - Metal protective cap

1627224

<https://www.phoenixcontact.com/us/products/1627224>



Metal protective cap, degree of protection: IP67, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1245447

---

### SF-Z0028 - Torque screwdriver

1607456

<https://www.phoenixcontact.com/us/products/1607456>



Torque screwdriver, series: RC, UC, SH, SF

## CA-07S1N8AT007 - Cable connector

1620256

<https://www.phoenixcontact.com/us/products/1620256>



## SF-Z0027 - Hook wrench

1607455

<https://www.phoenixcontact.com/us/products/1607455>



Hook wrench, series: RC, UC, RF, SF

---

## RF-Z0014 - Color coding

1620588

<https://www.phoenixcontact.com/us/products/1620588>



Color coding, color: green

# CA-07S1N8AT007 - Cable connector

1620256

<https://www.phoenixcontact.com/us/products/1620256>




## RF-Z0015 - Color coding

1620592

<https://www.phoenixcontact.com/us/products/1620592>

Color coding, color: orange



---

## RF-Z0016 - Color coding

1620593

<https://www.phoenixcontact.com/us/products/1620593>

Color coding, color: black



## CA-07S1N8AT007 - Cable connector

1620256

<https://www.phoenixcontact.com/us/products/1620256>



### RC-5CS2000 - Crimp contact

1603517

<https://www.phoenixcontact.com/us/products/1603517>



Crimp contact, Socket, turned, contact diameter: 2 mm, crimp range: 1 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241635

---

### RC-5AS2000 - Crimp contact

1603509

<https://www.phoenixcontact.com/us/products/1603509>



Crimp contact, Socket, turned, contact diameter: 2 mm, crimp range: 1.5 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241635

## CA-07S1N8AT007 - Cable connector

1620256

<https://www.phoenixcontact.com/us/products/1620256>



### RC-5SS2000 - Crimp contact

1603530

<https://www.phoenixcontact.com/us/products/1603530>



Crimp contact, Socket, turned, contact diameter: 2 mm, crimp range: 0.5 mm<sup>2</sup> ... 0.75 mm<sup>2</sup>, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241633

---

### RC-59S2000 - Crimp contact

1603501

<https://www.phoenixcontact.com/us/products/1603501>



Crimp contact, Socket, turned, Single contact, contact diameter: 2 mm, crimp range: 0.75 mm<sup>2</sup> ... 1 mm<sup>2</sup>, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241633

# CA-07S1N8AT007 - Cable connector

1620256

<https://www.phoenixcontact.com/us/products/1620256>



## PROT-M23-SG-IT-IP20 - Plastic protective cap

1577206

<https://www.phoenixcontact.com/us/products/1577206>



Plastic protective cap, M23, degree of protection: IP20, series: CA, RC, RF, UC, RM

---

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)