

1620382

https://www.phoenixcontact.com/sg/products/1620382

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Connector in molded plastic on both sides, series: KSM, M40-Socket, Straight, plastic molded, number of positions: 4+3+PE, type of locking: Screw locking mechanism, on M40-Pin, Straight, plastic molded, number of positions: 4+3+PE, cable length: 2 m, shielded: yes, color of outer sheath: orange RAL 2003

Your advantages

- Our standard: robust halogen-free PUR cable
- · Simple and safe: 100% electrically tested and assembled ready for use
- · Designs with preassembled cables on one or both sides
- · High flexibility: customer-specific assemblies and cable lengths can be supplied

Commercial data

Item number	1620382
Packing unit	1 pc
Minimum order quantity	2 pc
Note	Made to order (non-returnable)
Sales key	****
Product key	ABRDIG
Catalog page	Page 225 (C-2-2019)
GTIN	4046356833776
Weight per piece (including packing)	1,531 g
Weight per piece (excluding packing)	1,417.831 g
Customs tariff number	85444290
Country of origin	DE



1620382

https://www.phoenixcontact.com/sg/products/1620382

Technical data

Notes

Notes on operation	Observe derating curve.
ety note	
Safety note	WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.
	WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.
	• WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.
	 The products are suitable for applications in plant, controller, and electrical device engineering.
	 When operating the connectors in outdoor applications, they must be separately protected against environmental influences.
	 Assembled products may not be manipulated or improperly opened.
	 Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).
	 When using the product in direct connection with third-party manufacturers, the user is responsible.
	 For operating voltages > 50 V AC, conductive connector housings must be grounded
	 Ensure that the protective or functional ground has been properly connected.
	 VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector
	Only use tools recommended by Phoenix Contact
	 The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product.
	 Operate the connector only when it is fully plugged in and interlocked.
	 Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.
	Observe the minimum bending radius of the cable. Lay the cable without twisting it.
	The connector warms up in normal operation. Depending on the connector warms up in normal operation.



1620382

https://www.phoenixcontact.com/sg/products/1620382

	ambient conditions, the surface of the connector can continue t warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).
duct properties	
Product type	Signal and power cable
ata management status	
Article revision	08
nnector	
Connector specifications	
Type	Straight, plastic molded
Thread type	M40
Type of locking	Screw locking mechanism
Degree of protection	IP67, when in locked state
No. of pos.	4+3+PE
Direction of rotation	Standard
Contact switching type	Socket
Insertion/withdrawal cycles	50
Contact resistance	< 0.3 mΩ
Max. current	70 A
Voltage	630 V
Overvoltage category	
Degree of pollution	3
Rated surge voltage	6 kV
Ambient temperature (operation)	-40 °C 105 °C
Cable specifications Cable type	PSLC11Y-J
Shielded	yes
Cable structure	4 x 2.5 mm ² + 2 x 2 x 1.0 mm ² StC
External cable diameter	13.50 mm ±0.4 mm
Outer sheath, material	PUR
Material wire insulation	ТРМ
External sheath, color	orange RAL 2003
Nominal voltage, cable	1000 V
Test voltage	4 kV (2 kV signal)
Smallest bending radius, movable installation	135 mm
Max. bending cycles	1000000
Bending radius	135 mm
Traversing path	6 m
Acceleration	5 m/s ²
Ambient temperature (operation) for fixed installation	-40 °C 80 °C



1620382

https://www.phoenixcontact.com/sg/products/1620382

Ambient temperature (operation) for flexible installation	-20 °C 60 °C
Special properties	Flexible cable conduit capable
Flame resistance	IEC 332-1
Halogen-free	DIN VDE 0472
Connector specifications (second page)	
Туре	Straight, plastic molded
Housing material	Zinc die-cast
Thread type	M40
Degree of protection	IP67, when in locked state
No. of pos.	4+3+PE
Direction of rotation	Standard
Contact switching type	Pin
Insertion/withdrawal cycles	50
Contact resistance	< 0.3 mΩ
Max. current	70 A
Voltage	630 V
Overvoltage category	III
Degree of pollution	3
Rated surge voltage	6 kV
Ambient temperature (operation)	-40 °C 105 °C

Cable/line

Cable length

2 m



1620382

https://www.phoenixcontact.com/sg/products/1620382

Drawings

Schematic diagram



Socket pin assignment



1620382

https://www.phoenixcontact.com/sg/products/1620382

Schematic diagram



Pin assignment of pin



1620382

https://www.phoenixcontact.com/sg/products/1620382



I = current strength, T = ambient temperature



1620382

https://www.phoenixcontact.com/sg/products/1620382

Dimensional drawing



Dimensional drawing

Dimensional drawing



Dimensional drawing



1620382

https://www.phoenixcontact.com/sg/products/1620382

Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/sg/products/1620382

EHC	EAC Approval ID: B.00286/19
	UL Listed Approval ID: E335019-20131029
•	cUL Listed Approval ID: E335019-20131029

PP · · · · · · ·				
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
Power	600 V	14 A	-	-
Control	250 V	5 A	-	-



UL Listed Approval ID: E335019-20131029



1620382

https://www.phoenixcontact.com/sg/products/1620382

Classifications

ECLASS

	ECLASS-11.0	27060106
	ECLASS-12.0	27060106
	ECLASS-13.0	27060106
ET	IM	
	ETIM 9.0	EC003250
UN	ISPSC	
	UNSPSC 21.0	26121600



1620382

https://www.phoenixcontact.com/sg/products/1620382

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(b), 6(b)-II, 6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacture declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	4dc12b7a-49f0-407e-9818-dab56bfd4845

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT SEA Pte. Ltd. 105 Eunos Avenue 3, #04-00 Singapore 409836 +65 6228 4900 marketing@phoenixcontact.com.sg