

1622233

https://www.phoenixcontact.com/pc/products/1622233

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable plug in molded plastic, series: KSH, M23-Pin, angled, rotatable, -120 $^{\circ}$ left/120 $^{\circ}$ right, number of positions: 4+4+4+PE, type of locking: SPEEDCON, cable length: 2 m, shielded: yes, color of outer sheath: orange RAL 2003, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1244559

Your advantages

- · Transmission of signals, data, and power in just a single connector
- · CAT5 data interface for up to 100 Mbps
- · Customer-specific assemblies and cable lengths can be supplied
- Simple and safe: 100% electrically tested and assembled ready for use
- · Designs with preassembled cables on one or both sides
- Easy connection: angled design with configurable cable outlet direction

Commercial data

Item number	1622233
Packing unit	1 pc
Minimum order quantity	2 pc
Note	Made to order (non-returnable)
Product key	ABRDGC
Catalog page	Page 227 (C-2-2019)
GTIN	4055626069975
Weight per piece (including packing)	924.042 g
Weight per piece (excluding packing)	924.042 g
Customs tariff number	85444290
Country of origin	DE



1622233

https://www.phoenixcontact.com/pc/products/1622233

Technical data

Notes

Notes on operation	Observe derating curve.		
Safety note			
Safety note	WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.		
	 WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible. 		
	WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.		
	 The products are suitable for applications in plant, controller, and electrical device engineering. 		
	When operating the connectors in outdoor applications, they must be separately protected against environmental influences.		
	 Assembled products may not be manipulated or improperly opened. 		
	 Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products). 		
	 When using the product in direct connection with third-party manufacturers, the user is responsible. 		
	 For operating voltages > 50 V AC, conductive connector housings must be grounded 		
	 Ensure that the protective or functional ground has been properly connected. 		
	VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector		
	Only use tools recommended by Phoenix Contact		
	 The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product. 		
	 Operate the connector only when it is fully plugged in and interlocked. 		
	 Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards. 		
	Observe the minimum bending radius of the cable. Lay the cable without twisting it.		
	 The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting 		



1622233

https://www.phoenixcontact.com/pc/products/1622233

	warnings (e.g. DIN EN ISO 13732-1:2008-12).
oduct properties	
Product type	Signal and power cable
Pata management status	
Article revision	13
Allicie revision	13
nnector	
Connector specifications	
Type	angled, rotatable, -120° left/120° right
Housing material	PUR
Thread type	M23
Type of locking	SPEEDCON
Degree of protection	
Degree of protection	IP67, when in locked state IP68, when in locked state
No of noo	4+4+4+PE
No. of pos. Direction of rotation	Standard
Contact switching type	Pin
Insertion/withdrawal cycles	100
Max. current	30 A
Voltage	630 V AC
Overvoltage category	III
Degree of pollution	3
Rated surge voltage	6 kV
cable specifications	
Cable type	HDSLC11Y-J
Transmission speed	CAT5
Transmission speed	100 Mbps (Data interface)
Shielded	yes
Cable structure	(5x 2.5 + 2x (2x 0.5) + (4x 0.34)C) C
External cable diameter	15.50 mm ±0.5 mm
Outer sheath, material	PUR
Material wire insulation	TPE
External sheath, color	orange RAL 2003
Single wire, color	black 1, black 2, black 3, black 4, green/yellow Power wires + Pl
	brown, violet, black 5, green Signal wires
	blue, yellow, white, orange Data wires
Nominal voltage, cable	1000 V (300 V signal)
Test voltage	4 kV (1.5 kV signal)
Rated current	26 A (Power, in accordance with DIN VDE 0298-4 Tab. 11/5, at 15°C)
	8 A (Signal, according to DIN VDE 0298-4 tab. 11/5)
	3.6 A (Data, according to DIN VDE 0298-4 tab. 11/5)



1622233

https://www.phoenixcontact.com/pc/products/1622233

	Smallest bending radius, fixed installation	73 mm
	Smallest bending radius, movable installation	148 mm
	Max. bending cycles	1000000
	Traversing path	6 m
	Acceleration	30 m/s²
	Ambient temperature (operation) for fixed installation	-40 °C 80 °C (fixed installation)
	Ambient temperature (operation) for flexible installation	-20 °C 80 °C (flexible installation)
	UL AWM style	20234 / 10492 (80°C/1000 V)
	Special properties	Flexible cable conduit capable
	Flame resistance	IEC 60332-1-2
	Halogen-free	in accordance with EN 50267-2-1
	Resistance to oil	EN 60811-2-1
Ele	ctrical properties	
	Nominal current I _N	26 A
Ca	ble/line	
	Cable length	2 m




1622233

https://www.phoenixcontact.com/pc/products/1622233

Drawings






Cable outlet direction



1622233

https://www.phoenixcontact.com/pc/products/1622233






1622233

https://www.phoenixcontact.com/pc/products/1622233

Schematic diagram




Connector pin assignment




1622233

https://www.phoenixcontact.com/pc/products/1622233

Dimensional drawing



Pin version: dimension A = \sim 0.3 mm, socket version: dimension A = 0 mm



3 x 26 A + 4 x 2 A + 4 x 1 A



1622233

https://www.phoenixcontact.com/pc/products/1622233

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/pc/products/1622233



EAC

Approval ID: B.00286/19

UL Listed Approval ID: E468743-20150929				
	Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
Power	600 V	16 A	-	-
Signal	50 V	4 A	-	-
Data	30 V	1 A	-	-

CUL Listed Approval ID: E468743-20150929				
	Nominal voltage U_N	Nominal current I _N	Cross section AWG	Cross section mm ²
Power	600 V	16 A	-	-
Signal	50 V	4 A	-	-
Data	30 V	1 A	-	-

cULus Listed



1622233

https://www.phoenixcontact.com/pc/products/1622233

Classifications

UNSPSC 21.0

ECLASS

	ECLASS-11.0	27060311	
	ECLASS-12.0	27060311	
	ECLASS-13.0	27060311	
ETIN	M		
	ETIM 9.0	EC001855	
UNS	SPSC		

26121600



1622233

https://www.phoenixcontact.com/pc/products/1622233

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(b), 6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	2ed4418d-feff-4ef1-b96f-850d06eadd2d

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstraße 8 D-32825 Blomberg +49 (0) 5235-3 00 info@phoenixcontact.com