

# K-3E-M23 M9/2,0-A00/M23 F8 - Connector in molded plastic on both sides



1624773

<https://www.phoenixcontact.com/pc/products/1624773>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Connector in molded plastic on both sides, series: KSF, M23-Socket, Straight, plastic molded, number of positions: 3+PE, type of locking: Screw locking mechanism, on M23-Pin, Straight, plastic molded, number of positions: 3+PE, cable length: 2 m, shielded: yes, color of outer sheath: gray RAL 7001

## Your advantages

- Our standard: robust halogen-free PUR cable
- Simple and safe: 100% electrically tested and assembled ready for use
- Designs with preassembled cables on one or both sides
- High flexibility: customer-specific assemblies and cable lengths can be supplied

## Commercial data

Item number	1624773
Packing unit	1 pc
Minimum order quantity	2 pc
Note	Made to order (non-returnable)
Product key	ABRDEG
Catalog page	Page 220 (C-2-2019)
GTIN	4046356639170
Weight per piece (including packing)	805.35 g
Weight per piece (excluding packing)	805.35 g
Customs tariff number	85444290
Country of origin	DE

# K-3E-M23 M9/2,0-A00/M23 F8 - Connector in molded plastic on both sides



1624773

<https://www.phoenixcontact.com/pc/products/1624773>

## Technical data

### Notes

Notes on operation	Observe derating curve.
Safety note	<p><b>Safety note</b></p> <p>WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.</p> <ul style="list-style-type: none"><li>• WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.</li><li>• WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.</li><li>• The products are suitable for applications in plant, controller, and electrical device engineering.</li><li>• When operating the connectors in outdoor applications, they must be separately protected against environmental influences.</li><li>• Assembled products may not be manipulated or improperly opened.</li><li>• Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at <a href="https://www.phoenixcontact.com/products">phoenixcontact.com/products</a>).</li><li>• When using the product in direct connection with third-party manufacturers, the user is responsible.</li><li>• For operating voltages &gt; 50 V AC, conductive connector housings must be grounded</li><li>• Ensure that the protective or functional ground has been properly connected.</li><li>• VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector</li><li>• Only use tools recommended by Phoenix Contact</li><li>• The installation notes/Design In documents online on the download page at <a href="https://www.phoenixcontact.com/products">phoenixcontact.com/products</a> must be observed for this product.</li><li>• Operate the connector only when it is fully plugged in and interlocked.</li><li>• Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.</li><li>• Observe the minimum bending radius of the cable. Lay the cable without twisting it.</li><li>• The connector warms up in normal operation. Depending on the</li></ul>

# K-3E-M23 M9/2,0-A00/M23 F8 - Connector in molded plastic on both sides



1624773

<https://www.phoenixcontact.com/pc/products/1624773>

ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).

## Product properties

Product type	Signal and power cable
Data management status	
Article revision	11

## Connector

### Connector specifications

Type	Straight, plastic molded
Thread type	M23
Type of locking	Screw locking mechanism
Degree of protection	IP67, when in locked state
No. of pos.	3+PE
Direction of rotation	Standard
Contact switching type	Socket
Insertion/withdrawal cycles	50
Contact resistance	< 0.3 mΩ
Max. current	30 A
Voltage	630 V
Ovvoltage category	III
Degree of pollution	3
Rated surge voltage	6 kV
Ambient temperature (operation)	-40 °C ... 105 °C

### Cable specifications

Cable type	Ölflex Control TM
Shielded	yes
Cable structure	4G4
Cable structure (AWG)	Ölflex Control TM CY 4G4
External cable diameter	12.30 mm
Outer sheath, material	PVC
Material wire insulation	PVC
External sheath, color	gray RAL 7001
Nominal voltage, cable	600 V
Test voltage	2 kV
Rated current	34 A
Smallest bending radius, fixed installation	73.8 mm
Ambient temperature (operation) for fixed installation	-40 °C ... 90 °C
Resistance to oil	UL OIL RES I&II

# K-3E-M23 M9/2,0-A00/M23 F8 - Connector in molded plastic on both sides



1624773

<https://www.phoenixcontact.com/pc/products/1624773>

## Connector specifications (second page)

Type	Straight, plastic molded
Housing material	Zinc die-cast
Thread type	M23
Degree of protection	IP67, when in locked state
No. of pos.	3+PE
Direction of rotation	Standard
Contact switching type	Pin
Insertion/withdrawal cycles	50
Contact resistance	< 0.3 mΩ
Max. current	30 A
Voltage	630 V
Overshoot category	III
Degree of pollution	3
Rated surge voltage	6 kV
Ambient temperature (operation)	-40 °C ... 105 °C

## Cable/line

Cable length	2 m
--------------	-----

# K-3E-M23 M9/2,0-A00/M23 F8 - Connector in molded plastic on both sides




1624773

<https://www.phoenixcontact.com/pc/products/1624773>


## Drawings

Schematic diagram



Do not use pin 1 and 6

Dimensional drawing



Pin side


# K-3E-M23 M9/2,0-A00/M23 F8 - Connector in molded plastic on both sides




1624773

<https://www.phoenixcontact.com/pc/products/1624773>

Circuit diagram



Diagram



I = current strength, T = ambient temperature


# K-3E-M23 M9/2,0-A00/M23 F8 - Connector in molded plastic on both sides



1624773


<https://www.phoenixcontact.com/pc/products/1624773>

Schematic diagram



Do not use pin 1 and 6

Dimensional drawing



On the female side

# K-3E-M23 M9/2,0-A00/M23 F8 - Connector in molded plastic on both sides



1624773

<https://www.phoenixcontact.com/pc/products/1624773>

## Approvals

>To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1624773>



**EAC**

Approval ID: B.00286/19



**UL Listed**

Approval ID: E335019-20120906

	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $mm^2$
Power	600 V	25 A	-	-



**cUL Listed**

Approval ID: E335019-20120906

	Nominal voltage $U_N$	Nominal current $I_N$	Cross section AWG	Cross section $mm^2$
Power	600 V	25 A	-	-

**cULus Listed**

# K-3E-M23 M9/2,0-A00/M23 F8 - Connector in molded plastic on both sides



1624773

<https://www.phoenixcontact.com/pc/products/1624773>

## Classifications

### ECLASS

ECLASS-11.0	27060106
ECLASS-12.0	27060106
ECLASS-13.0	27060106

### ETIM

ETIM 8.0	EC003250
----------	----------

### UNSPSC

UNSPSC 21.0	26121600
-------------	----------

# K-3E-M23 M9/2,0-A00/M23 F8 - Connector in molded plastic on both sides



1624773

<https://www.phoenixcontact.com/pc/products/1624773>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(b), 6(c)

### China RoHS

Environment friendly use period (EFUP)	EFUP-50  An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
--	--

### EU REACH SVHC

REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	fae4abda-d9eb-4ed3-b91b-f1cf9c34a7e9

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachmarkstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)