

HC-B 24-AMQ-EMV - EMC housing

1642962

<https://www.phoenixcontact.com/za/products/1642962>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON panel mounting base B24, with double locking latch, EMC version. Not suitable for D series terminal adapters

Commercial data

Item number	1642962
Packing unit	10 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	020
Product key	BF7AAD
Catalog page	Page 587 (PC-2011)
GTIN	4046356028608
Weight per piece (including packing)	194,3 g
Weight per piece (excluding packing)	192,2 g
Customs tariff number	85389099
Country of origin	CZ

HC-B 24-AMQ-EMV - EMC housing



1642962

<https://www.phoenixcontact.com/za/products/1642962>

Technical data


Notes

General	For contact inserts HC-B24, BB46, BBB64, D64, DD108, M
---------	--

Product properties

Type	B24
Product type	Housing with locking latch
Application	EMC
Housing type	Panel mounting base
Shielded	yes
Pg screw connection	none

Dimensions

Dimensional drawing	
Width	48 mm
Height	30.5 mm
Length	140 mm

Installation dimensions

Width of the assembly cutout	35 mm
Length of the assembly cutout	108 mm

Material specifications

Seal material	NBR
Housing surface material	EMC coating, silver
Locking latch material	Steel, galvanized
Housing material	die-cast aluminum

Mechanical properties

Mechanical data

Locking type	Latch
--------------	-------

Mounting

Assembly instructions	Cannot be used for HC-D... series terminal adapters. If insulating powder coating is present on the control cabinet panel, it should be removed from the profile gasket area in order to ensure optimum shielding.
-----------------------	---

Environmental and real-life conditions

HC-B 24-AMQ-EMV - EMC housing

1642962

<https://www.phoenixcontact.com/za/products/1642962>



Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 100 °C


HC-B 24-AMQ-EMV - EMC housing



1642962
<https://www.phoenixcontact.com/za/products/1642962>


Drawings

Diagram



Shield attenuation

Dimensional drawing



Dimensional drawing


HC-B 24-AMQ-EMV - EMC housing

1642962

<https://www.phoenixcontact.com/za/products/1642962>



Dimensional drawing



Mounting cutout

HC-B 24-AMQ-EMV - EMC housing

1642962

<https://www.phoenixcontact.com/za/products/1642962>



Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-13.0	27440202

HC-B 24-AMQ-EMV - EMC housing



1642962

<https://www.phoenixcontact.com/za/products/1642962>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (Pty) Ltd.
36 Lyn Road P.O. Box 916 ZA-Ferndale 2160

+27/11/801-8200
info@phoenixcontact.co.za