

https://www.phoenixcontact.com/us/products/1644164



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Filler plug to close the unused openings of the HC-KD/SG-... conduit

Commercial data

Item number	1644164
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	BF66
Product key	BF7AZA
Catalog page	Page 678 (C-4-2015)
GTIN	4017918895860
Weight per piece (including packing)	3.82 g
Weight per piece (excluding packing)	3.82 g
Customs tariff number	39269097
Country of origin	DE



https://www.phoenixcontact.com/us/products/1644164



Technical data

Material specifications

Material	thermoplastic rubber
Flammability rating according to UL 94	НВ

Characteristics

Conductor sealing range	without	

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP54
Ambient temperature (operation)	-40 °C 125 °C



https://www.phoenixcontact.com/us/products/1644164



Classifications

UNSPSC

UNSPSC 21.0 39121311



https://www.phoenixcontact.com/us/products/1644164



Environmental product compliance

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com