

1647640

https://www.phoenixcontact.com/be/products/1647640

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Reducing adapter, connecting thread: M40 x 1.5, color: silver, with O-ring





Product description

Reduced M40 to M32

Commercial data

| Item number | 1647640 |
|--------------------------------------|---------------------|
| Packing unit | 10 pc |
| Minimum order quantity | 1 pc |
| Sales key | BF7DZX |
| Product key | BF7DZX |
| Catalog page | Page 700 (C-2-2019) |
| GTIN | 4017918941543 |
| Weight per piece (including packing) | 45,63 g |
| Weight per piece (excluding packing) | 45,63 g |
| Customs tariff number | 74153300 |
| Country of origin | DE |



1647640

https://www.phoenixcontact.com/be/products/1647640

Technical data

Product properties

| Product type | Reducing adapter |
|--------------|------------------|
| Seal present | yes |

Connection data

| Tightening torque | 11 12 Nm |
|-------------------|----------|

Dimensions

| Dimensional drawing | 31.5 |
|----------------------------------|-----------|
| Width | 43.00 mm |
| Length | 11.5 mm |
| Length of the connecting thread | 8 mm |
| Length without connecting thread | 3.5 mm |
| Diameter | 40 mm |
| Connecting thread diameter | 40 mm |
| Hexagon angular dimension | 43 mm |
| Thread type connection side | M40 x 1.5 |
| Thread pitch | 1.5 mm |
| Thread type on seal side | M32 |

Material specifications

| Color | Brass |
|--------------------------|----------------------|
| Material | Brass, nickel-plated |
| Seal material | NBR |
| Housing surface material | Nickel |

Cable/line

| Halogen-free no |
|-----------------|
|-----------------|

Environmental and real-life conditions

Ambient conditions

| Degree of protection | IP65 (Depends on the screw connection used) |
|---------------------------------|---|
| Ambient temperature (operation) | -20 °C 80 °C |

Mounting

| Assembly instructions | With corresponding screw connection: IP68 |
|-----------------------|---|




https://www.phoenixcontact.com/be/products/1647640



Drawings

Dimensional drawing



Dimensional drawing



1647640

https://www.phoenixcontact.com/be/products/1647640

Classifications

ECLASS

| | ECLASS-11.0 | 27144492 |
|--------|-------------|----------|
| | ECLASS-12.0 | 27144492 |
| | ECLASS-13.0 | 27140806 |
| ETIM | | |
| | ETIM 9.0 | EC000938 |
| UNSPSC | | |
| | UNSPSC 21.0 | 31261500 |



1647640

https://www.phoenixcontact.com/be/products/1647640

Environmental product compliance

| REACh SVHC | Lead 7439-92-1 |
|------------|--|
| | |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT nv/sa Minervastraat 10-12 1930 Zaventem-Keiberg II +32 (0)2/723 98 11 info@phoenixcontact.be