

HC-B 16-A-DT-PEL-M - Terminal adapter



1648445

<https://www.phoenixcontact.com/no/products/1648445>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

HEAVYCON terminal adapter, pin insert, B16 series, 16-pos., for the left side of the control cabinet, push-in connection



Your advantages

- Easy installation without tools, even when mounted, with push-in connection technology
- Shortest installation time compared to other connection technologies
- Quick and effortless wiring, in particular when space is tight
- Automatic cabling with robots possible
- Safe wiring and operation with color-coded actuators
- Shock and vibration-resistant in accordance with DIN EN 61373

Commercial data

Item number	1648445
Packing unit	5 pc
Minimum order quantity	1 pc
Sales key	31BBF
Product key	BF7ADC
Catalog page	Page 549 (C-2-2019)
GTIN	4046356092166
Weight per piece (including packing)	133.2 g
Weight per piece (excluding packing)	133 g
Customs tariff number	85366990
Country of origin	CN

HC-B 16-A-DT-PEL-M - Terminal adapter



1648445

<https://www.phoenixcontact.com/no/products/1648445>

Technical data

Notes

General	For HEAVYCON-ADVANCE mounting flange and HEAVYCON panel mounting base of B16 type
General	Connectors may be operated only when there is no load/voltage.

Product properties

Type	B16
Product type	Terminal adapter
Product family	HC-B
Number of positions	16
Connection profile	16+PE
Contact numbering	1 - 16
Type	for the left side of the control cabinet
Series	HC-B

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated voltage (III/3)	500 V
Rated surge voltage	6 kV
Rated current	16 A
SCCR	5 kA (UL 2237)

Connection data

Connection technology

Connection technology	Push-in connection
-----------------------	--------------------

Conductor connection

Conductor cross section	0.5 mm ² ... 2.5 mm ²
Connection cross section AWG	22 ... 12
Stripping length of the individual wire	10 mm (13 mm with ferrule)


Dimensions

HC-B 16-A-DT-PEL-M - Terminal adapter



1648445

<https://www.phoenixcontact.com/no/products/1648445>

Dimensional drawing	
Width	34 mm
Height	70.5 mm
Length	84 mm
Drill hole distance, horizontal	77.5 mm
Drill hole distance, vertical	27 mm

Material specifications

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ag
Contact carrier material	PA
Standards/regulations	PA: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)

Cable/line

Stripping length of the individual wire	10 mm (13 mm with ferrule)
---	----------------------------

Mechanical properties

Mechanical data	
Insertion/withdrawal cycles	≥ 500

Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 125 °C

Standards and regulations

Constructional and testing regulations	DIN EN 61984
	DIN EN 60664
	IEC 60352
Tests	DIN EN 61984
	DIN EN 60664
	IEC 60352

Testing	
---------	--

HC-B 16-A-DT-PEL-M - Terminal adapter



1648445

<https://www.phoenixcontact.com/no/products/1648445>

Standards/regulations	PA: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)
-----------------------	---

Mounting

Assembly instructions	To ensure correct use, installation in housing with IP54 protection or better is required
	Connectors may be plugged in only when there is no load/voltage.


HC-B 16-A-DT-PEL-M - Terminal adapter

1648445

<https://www.phoenixcontact.com/no/products/1648445>

Drawings

Application drawing



Mounting position PE connection left/right (PEL/PER)


HC-B 16-A-DT-PEL-M - Terminal adapter



1648445

<https://www.phoenixcontact.com/no/products/1648445>

Dimensional drawing



Dimensional drawing, side view


HC-B 16-A-DT-PEL-M - Terminal adapter

1648445

<https://www.phoenixcontact.com/no/products/1648445>



Dimensional drawing




Dimensional drawing

HC-B 16-A-DT-PEL-M - Terminal adapter



1648445

<https://www.phoenixcontact.com/no/products/1648445>



Derating diagram

HC-B 16-A-DT-PEL-M - Terminal adapter



1648445

<https://www.phoenixcontact.com/no/products/1648445>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/no/products/1648445>



CSA
Approval ID: 013631_6233_01



cUL Recognized
Approval ID: FILE E 118976



UL Recognized
Approval ID: FILE E 118976



EAC
Approval ID: RU C-DE.BL08.B.00511

	cULus Recognized Approval ID: E468743			
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	600 V	13 A	- 14	-



UL Recognized
Approval ID: FILE E 118976



CSA
Approval ID: 013631_6233_01



cUL Recognized
Approval ID: FILE E 118976

HC-B 16-A-DT-PEL-M - Terminal adapter



1648445

<https://www.phoenixcontact.com/no/products/1648445>

Classifications

ECLASS

ECLASS-11.0	27440222
ECLASS-12.0	27440222
ECLASS-13.0	27440222

ETIM

ETIM 9.0	EC000438
----------	----------

UNSPSC

UNSPSC 21.0	39121500
-------------	----------

HC-B 16-A-DT-PEL-M - Terminal adapter



1648445

<https://www.phoenixcontact.com/no/products/1648445>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT AS
Strømsveien 344
N-1081 Oslo
+47 22 07 68 00
norge@phoenixcontact.com