

VS-08-ST-H11-RJ45 - RJ45 male insert



1652716

<https://www.phoenixcontact.com/us/products/1652716>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



RJ45 pin insert, CAT5, 8-pos., shielded, IDC connection technology, for 27 ... 26 AWG litz wires, with strain relief

Your advantages

- Reliable 360° shield contact due to the proven crimp connection
- Easy installation with a crimping tool
- Pin insert for V.06 sleeve housing VS-08-T-H-RJ45/IP67

Commercial data

Item number	1652716
Packing unit	5 pc
Minimum order quantity	5 pc
Sales key	AB10
Product key	ABNAAG
Catalog page	Page 350 (C-2-2019)
GTIN	4017918952860
Weight per piece (including packing)	5.7 g
Weight per piece (excluding packing)	4.378 g
Customs tariff number	85366990
Country of origin	TW

VS-08-ST-H11-RJ45 - RJ45 male insert



1652716
<https://www.phoenixcontact.com/us/products/1652716>

Technical data

Product properties

Product type	Male insert
Type	RJ45
Sensor type	Ethernet
Number of positions	8
Connection profile	RJ45
No. of cable outlets	1
Type	RJ45
Shielded	yes
Cable outlet	straight
Positions/contacts	8P8C

Data management status

Article revision	05
------------------	----

Insulation characteristics

Overvoltage category	I
Degree of pollution	2

Electrical properties

Rated voltage (III/3)	72 V (DC)
Rated surge voltage	330 kV
Rated current	0.5 A
Contact resistance	< 20 mΩ (Contact) < 100 mΩ (shield)
Frequency range	to 100 MHz
Insulation resistance	> 500 MΩ (100 V DC)
Nominal voltage U_N	48 V
Nominal current I_N	0.5 A
Contact resistance per contact pair	< 20 Ω
Contact resistance	> 10 mΩ (Wire – IDC)
Transmission medium	Copper
Transmission characteristics (category)	CAT3

Connection data

Connection method	Crimp connection
-------------------	------------------

Dimensions

Dimensional drawing	
---------------------	--

VS-08-ST-H11-RJ45 - RJ45 male insert



1652716

<https://www.phoenixcontact.com/us/products/1652716>

Width	11.7 mm
Height	14 mm
Length	30.2 mm

Material specifications

Color	white
Flammability rating according to UL 94	V2
Housing material	Steel, tin-plated
Contact material	Phosphor bronze
Contact surface material	Au/Ni
Contact carrier material	PC
Locking latch material	PC

Cable/line

External cable diameter	5 mm ... 5.6 mm
Wire diameter including insulation	0.9 mm ... 1 mm
Test voltage Core/Core	1000 V
Test voltage Core/Shield	1500.00 V

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 750
Insertion force per signal contact	< 20.00 N
Extraction force per signal contact	< 20 N

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 60 °C

Mounting

Mounting type	Crimp connection
---------------	------------------


VS-08-ST-H11-RJ45 - RJ45 male insert



1652716

<https://www.phoenixcontact.com/us/products/1652716>

Drawings



RJ45 male insert

VS-08-ST-H11-RJ45 - RJ45 male insert



1652716

<https://www.phoenixcontact.com/us/products/1652716>

Classifications

ECLASS

ECLASS-11.0	27440223
ECLASS-12.0	27440223
ECLASS-13.0	27440116

ETIM

ETIM 9.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

VS-08-ST-H11-RJ45 - RJ45 male insert



1652716

<https://www.phoenixcontact.com/us/products/1652716>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com