

VS-04-2X2X26C7/7-67B/SDA/2,0 - Patch cable



1653919

<https://www.phoenixcontact.com/it/products/1653919>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Assembled USB cable, shielded, color: RAL 5021 (water blue), PUR outer sheath, USB type B/IP67 on USB type A/standard, length: 2 m

Commercial data

Item number	1653919
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	ABN
Product key	ABNDBA
Catalog page	Page 452 (C-2-2019)
GTIN	4017918970246
Weight per piece (including packing)	163.2 g
Weight per piece (excluding packing)	156 g
Customs tariff number	85444290
Country of origin	DE

Technical data

Product properties

Product type	Data cable preassembled
Sensor type	USB 2.0
Number of positions	4
Shielded	yes

Insulation characteristics

Degree of pollution	2
---------------------	---

Electrical properties

Rated voltage (III/3)	125 V
Rated current	1 A
Transmission medium	Copper
Transmission characteristics (category)	USB 2.0
Transmission speed	480 Mbps
Wave impedance	100 Ω

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 500
-----------------------------	------------

Material specifications

Seal material	NBR
O-ring material	FPM
Housing material	PA
Outer sheath, material	PUR
Conductor material	Bare Cu litz wires

Connector

Connection 1

Type	Plug straight USB type B
------	--------------------------

Connection 2

Type	Plug straight USB type A
------	--------------------------

Cable/line

Cable length	2.00 m
--------------	--------

FireWire [980]

Shielded	yes
Cable weight	59 kg/km
Cable type	FireWire

VS-04-2X2X26C7/7-67B/SDA/2,0 - Patch cable



1653919

<https://www.phoenixcontact.com/it/products/1653919>

Cable type (abbreviation)	980
Signal type/category	USB CAT7, 480 Mbps
	FireWire CAT7, 400 Mbps
Cable structure	2x2xAWG26/7 + 2xAWG20/19, S/FTP
External cable diameter	6.70 mm
Outer sheath, material	PUR
External sheath, color	water blue RAL 5021
Conductor material	Bare Cu litz wires
Conductor structure signal line	7x 0.15 mm
AWG signal line	26
Conductor structure, voltage supply	19x 0.20 mm
Conductor cross section	2x 2x 0.14 mm ² (Signal line)
AWG power supply	20
Material wire insulation	Cell PE (Signal line)
	PVC (Power supply)
Wire diameter incl. insulation	≤ 1.05 mm (Signal line)
	nom. 1.4 mm (Power supply)
Single wire, color	white-blue, white-orange, white, black
Twisted pairs	2 cores to the pair
Type of pair shielding	Aluminum-lined polyester foil
Overall twist	Two pairs and two power supply wires to the core
Shielding	Tinned copper braided shield
Nominal voltage, cable	≤ 125 V
Test voltage, cable	1000 V
Cable resistance	150 Ω/km
Cable insulation resistance	5 GΩ*km
Coupling resistance	5.00 mΩ/m (at 10 MHz)
Wave impedance	100 Ω ±5 % (at 100 MHz)
Working capacitance	42 pF (per meter)
Signal runtime	4.6 ns/m
Signal speed	0.72 c
Interference suppression	90.00 dB (up to 1000 MHz)
Tensile strength	≤ 30 N
Minimum bending radius, fixed installation	5 x D
Minimum bending radius, flexible installation	5 x D
Shield attenuation	60.00 dB (up to 1000 MHz)
Resistance to oil	in accordance with EN 60811-2-1
Flame resistance	complying with IEC 60332-2-2
Other resistance	Microbe resistance as per DIN VDE 0282
	Hydrolysis resistance as per DIN 53504
Special properties	Free of substances which would hinder coating with paint or varnish
Ambient temperature (operation)	-10 °C ... 50 °C (Cable, flexible installation)
	-40 °C ... 70 °C (cable, fixed installation)

VS-04-2X2X26C7/7-67B/SDA/2,0 - Patch cable



1653919

<https://www.phoenixcontact.com/it/products/1653919>


Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
	IP67
	IP67/IP20
Ambient temperature (operation)	-20 °C ... 60 °C (cable, fixed installation)
	0 °C ... 50 °C (Cable, flexible installation)
	Plug / socket

Drawings

Dimensional drawing



USB connector, type B, IP67


VS-04-2X2X26C7/7-67B/SDA/2,0 - Patch cable

1653919

<https://www.phoenixcontact.com/it/products/1653919>




Dimensional drawing




USB connector, type A, Standard

Circuit diagram




Schematic diagram



Pin assignment plug USB, type A

Schematic diagram



Plug pin assignment plug USB, type B

VS-04-2X2X26C7/7-67B/SDA/2,0 - Patch cable



1653919

<https://www.phoenixcontact.com/lt/products/1653919>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/lt/products/1653919>



EAC

Approval ID: 19060508

VS-04-2X2X26C7/7-67B/SDA/2,0 - Patch cable



1653919

<https://www.phoenixcontact.com/it/products/1653919>

Classifications

ECLASS

ECLASS-11.0	27060390
ECLASS-12.0	27060307
ECLASS-13.0	27060307

ETIM

ETIM 9.0	EC002599
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

VS-04-2X2X26C7/7-67B/SDA/2,0 - Patch cable



1653919
<https://www.phoenixcontact.com/lt/products/1653919>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact UAB
Svitrigailos str. 11B
03228 Vilnius
+370 5 2106321
balticinfo@phoenixcontact.com