

1654785

<https://www.phoenixcontact.com/us/products/1654785>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



D-SUB contact insert, shell size 1, with nine signal contacts, type of contact pin, for PCB assembly, angled, fixing with a 2.5 mm hole and solder metal plate, for panel mounting frame VS-09-...

Your advantages

- D-SUB 9 connection
- Easy assembly
- Direct PCB connection
- Compatible with IP67 panel-mount frame

Commercial data

Item number	1654785
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	AB19
Product key	ABNCAA
Catalog page	Page 211 (C-2-2013)
GTIN	4017918989170
Weight per piece (including packing)	12.15 g
Weight per piece (excluding packing)	9.39 g
Customs tariff number	85366990
Country of origin	DE

# VS-09-ST-DSUB-LH-B - D-SUB contact insert



1654785

<https://www.phoenixcontact.com/us/products/1654785>

## Technical data

### Product properties

Product type	Male insert
Type	D-SUB
Number of positions	9
Connection profile	D-SUB
Type	Male
Shielded	no

### Insulation characteristics

Overvoltage category	III
Degree of pollution	2


### Electrical properties

Rated voltage in acc. with IEC 61076-2-101	400 V
Rated voltage (III/3)	125 V
Rated surge voltage	1 kV
Rated current	5 A (at 20 °C)
Test voltage	1200 V
Transmission medium	Copper

### Connection data

Connection method	PCB connection
-------------------	----------------

### Dimensions

Dimensional drawing	
Width	20 mm
Height	13 mm
Length	31.19 mm

### Material specifications

Flammability rating according to UL 94	V0
Housing material	Steel, tin-plated
Contact material	Copper alloy
Contact surface material	Gold over nickel
Contact carrier material	PBT-GF

### Mechanical properties

#### Mechanical data

# VS-09-ST-DSUB-LH-B - D-SUB contact insert



1654785

<https://www.phoenixcontact.com/us/products/1654785>

Insertion/withdrawal cycles	$\geq 200$
Insertion force per signal contact	$\leq 3.40 \text{ N}$

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-55 °C ... 125 °C

## Mounting

Mounting type	Hole and solder metal plate
---------------	-----------------------------

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)