

VS-15-ST-DSUB-LH-B - D-SUB contact insert



1654808

<https://www.phoenixcontact.com/pc/products/1654808>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

D-SUB contact insert, shell size 2, with 15 signal contacts, type of contact pin, for PCB assembly, angled, fixing with a 2.5 mm hole and solder metal plate, for panel mounting frame VS-15-...



Your advantages

- D-SUB 15 connection
- Easy assembly
- Direct PCB connection
- Compatible with IP67 panel-mount frame

Commercial data

Item number	1654808
Packing unit	10 pc
Minimum order quantity	10 pc
Product key	ABNCAA
Catalog page	Page 211 (C-2-2013)
GTIN	4017918989194
Weight per piece (including packing)	14.19 g
Weight per piece (excluding packing)	10.46 g
Customs tariff number	85369010
Country of origin	DE

VS-15-ST-DSUB-LH-B - D-SUB contact insert

1654808

<https://www.phoenixcontact.com/pc/products/1654808>



Technical data

Product properties

Product type	Male insert
Type	D-SUB
Number of positions	15
Connection profile	D-SUB
Type	Male
Shielded	no

Data management status

Article revision	01
------------------	----

Insulation characteristics

Overvoltage category	III
Degree of pollution	2


Electrical properties

Rated voltage in acc. with IEC 61076-2-101	400 V
Rated voltage (III/3)	125 V
Rated surge voltage	1 kV
Rated current	5 A (at 20 °C)
Test voltage	1200 V
Transmission medium	Copper

Connection data

Connection method	PCB connection
-------------------	----------------

Dimensions

Dimensional drawing	
Width	19.1 mm
Height	13 mm
Length	39.52 mm

Material specifications

Flammability rating according to UL 94	V0
Housing material	Steel, tin-plated
Contact material	Copper alloy
Contact surface material	Gold over nickel
Contact carrier material	PBT-GF

VS-15-ST-DSUB-LH-B - D-SUB contact insert



1654808

<https://www.phoenixcontact.com/pc/products/1654808>

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 200
Insertion force per signal contact	$\leq 3.40 \text{ N}$

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-55 °C ... 125 °C

Mounting

Mounting type	Hole and solder metal plate
---------------	-----------------------------

VS-15-ST-DSUB-LH-B - D-SUB contact insert


1654808

<https://www.phoenixcontact.com/pc/products/1654808>




Drawings

Dimensional drawing



D-SUB contact insert

Schematic diagram




VS-15-ST-DSUB-LH-B - D-SUB contact insert

1654808

<https://www.phoenixcontact.com/pc/products/1654808>



Drilling plan/solder pad geometry



Drilling diagram

VS-15-ST-DSUB-LH-B - D-SUB contact insert

1654808

<https://www.phoenixcontact.com/pc/products/1654808>



Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1654808>



UL Recognized

Approval ID: E118976

VS-15-ST-DSUB-LH-B - D-SUB contact insert



1654808

<https://www.phoenixcontact.com/pc/products/1654808>

Classifications

ECLASS

ECLASS-11.0	27440223
ECLASS-12.0	27440223
ECLASS-13.0	27440223

ETIM

ETIM 9.0	EC003557
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

VS-15-ST-DSUB-LH-B - D-SUB contact insert



1654808

<https://www.phoenixcontact.com/pc/products/1654808>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)

China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	2de071b9-7a97-4097-ab6e-829066a01ce1

VS-15-ST-DSUB-LH-B - D-SUB contact insert



1654808

<https://www.phoenixcontact.com/pc/products/1654808>

Accessories

CUC-DST-GPME-S/DSSC15 - D-SUB sleeve housings

1419710

<https://www.phoenixcontact.com/pc/products/1419710>



D-SUB sleeve housings, degree of protection: IP20, material: ABS, metal-plated, cable outlet: straight, housing size: 2, color: Bare metallic

CUC-DST-GPME-A/DSSC15 - D-SUB sleeve housings

1419718

<https://www.phoenixcontact.com/pc/products/1419718>



D-SUB sleeve housings, degree of protection: IP20, material: ABS, metal-plated, cable outlet: angled, housing size: 2, color: Bare metallic

VS-15-ST-DSUB-LH-B - D-SUB contact insert

1654808

<https://www.phoenixcontact.com/pc/products/1654808>



CUC-DST-GZNI-S/DSSC15 - D-SUB sleeve housings

1419724

<https://www.phoenixcontact.com/pc/products/1419724>



D-SUB sleeve housings, degree of protection: IP20, material: Zinc die-cast, cable outlet: straight, housing size: 2, color: Bare metallic

CUC-DST-GZNI-A/DSSC15 - D-SUB sleeve housings

1419725

<https://www.phoenixcontact.com/pc/products/1419725>



D-SUB sleeve housings, degree of protection: IP20, material: Zinc die-cast, cable outlet: angled, housing size: 2, color: Bare metallic

VS-15-ST-DSUB-LH-B - D-SUB contact insert

1654808

<https://www.phoenixcontact.com/pc/products/1654808>



VS-15-A - Panel-mount frame

1688036

<https://www.phoenixcontact.com/pc/products/1688036>

D-SUB panel mounting frame, shell size 2, IP67 degree of protection



VS-15-BU-DSUB-LH-B - D-SUB contact insert

1654811

<https://www.phoenixcontact.com/pc/products/1654811>

D-SUB contact insert, shell size 2, with 15 signal contacts, type of contact socket, for PCB assembly, angled, fixing with a 2.5 mm hole and solder metal plate, for panel mounting frame VS-15-...



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com