

VS-09-DSUB-20-LI-2,0 - D-SUB cable

1656246

<https://www.phoenixcontact.com/pc/products/1656246>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Assembled D-SUB cable, shielded, 9-pos., stranded (7-wire), cable color: RAL 7000 (gray), secured using 4-40 UNC thread, IP20 protection, head 1 with socket shell 1 and straight cable outlet, head 2 with pin shell 1 and straight cable outlet, length: 2 m

Commercial data

Item number	1656246
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	ABNCAS
Catalog page	Page 218 (C-2-2013)
GTIN	4046356029728
Weight per piece (including packing)	132.66 g
Weight per piece (excluding packing)	130.66 g
Customs tariff number	85444290
Country of origin	CN

VS-09-DSUB-20-LI-2,0 - D-SUB cable



1656246

<https://www.phoenixcontact.com/pc/products/1656246>

Technical data

Product properties

Type	D-SUB
Product type	Data cable preassembled
Sensor type	Universal
Number of positions	9
Cable outlet	straight

Insulation characteristics

Overvoltage category	III
Degree of pollution	2

Electrical properties

Rated current	1 A
Operating voltage	30 V
Transmission medium	Copper

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 50
-----------------------------	------

Material specifications

Contact material	Copper alloy
Contact surface material	gold-plated
Housing material	PVC
Outer sheath, material	PVC

Connection data

Connection technology

Connection method	D-SUB
-------------------	-------

Conductor connection

Connection method	D-SUB
-------------------	-------

Connector

Connection 1

Type	Socket straight D-SUB 9
------	-------------------------

Connection 2

Type	Plug straight D-SUB 9
------	-----------------------

Cable/line

Outer sheath, material	PVC
------------------------	-----

VS-09-DSUB-20-LI-2,0 - D-SUB cable



1656246

<https://www.phoenixcontact.com/pc/products/1656246>

Cable cross section	0.08 mm²
AWG signal line	28

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
	IP20
Ambient temperature (operation)	0 °C ... 70 °C

VS-09-DSUB-20-LI-2,0 - D-SUB cable


1656246

<https://www.phoenixcontact.com/pc/products/1656246>




Drawings

Dimensional drawing



Schematic diagram




VS-09-DSUB-20-LI-2,0 - D-SUB cable

1656246


<https://www.phoenixcontact.com/pc/products/1656246>



Dimensional drawing



Circuit diagram




VS-09-DSUB-20-LI-2,0 - D-SUB cable

1656246

<https://www.phoenixcontact.com/pc/products/1656246>



Schematic diagram



VS-09-DSUB-20-LI-2,0 - D-SUB cable



1656246

<https://www.phoenixcontact.com/pc/products/1656246>

Classifications

ECLASS

ECLASS-12.0	27060390
ECLASS-11.0	27060390
ECLASS-13.0	27060307

ETIM

ETIM 9.0	EC000748
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

VS-09-DSUB-20-LI-2,0 - D-SUB cable



1656246

<https://www.phoenixcontact.com/pc/products/1656246>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com