

# SAC-3P-M12MR/0,3-PUR/M12FS B - Sensor/actuator cable



1668551

<https://www.phoenixcontact.com/pc/products/1668551>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, Plug angled M12, coding: A, on Socket straight M12, coding: A, PIN 2+4 bridged, cable length: 0.3 m

## Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Efficient integration of bridging functions directly in the connector

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 1668551             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 1 pc                |
| Sales key                            | 02                  |
| Product key                          | BF1CBA              |
| Catalog page                         | Page 188 (C-2-2019) |
| GTIN                                 | 4017918136383       |
| Weight per piece (including packing) | 27.6 g              |
| Weight per piece (excluding packing) | 27.6 g              |
| Customs tariff number                | 85444290            |
| Country of origin                    | PL                  |

# SAC-3P-M12MR/0,3-PUR/M12FS B - Sensor/actuator cable



1668551

<https://www.phoenixcontact.com/pc/products/1668551>

## Technical data

### Product properties

|                      |                       |
|----------------------|-----------------------|
| Product type         | Sensor/actuator cable |
| Application          | Standard              |
| Number of positions  | 3                     |
| No. of cable outlets | 1                     |
| Shielded             | no                    |
| Coding               | A                     |

### Insulation characteristics

|                      |    |
|----------------------|----|
| Overvoltage category | II |
| Degree of pollution  | 3  |

### Material specifications

|                                        |                                             |
|----------------------------------------|---------------------------------------------|
| Flammability rating according to UL 94 | HB                                          |
| Seal material                          | NBR                                         |
| Material of grip body                  | TPU, hardly inflammable, self-extinguishing |
| Contact material                       | CuSn                                        |
| Contact surface material               | Ni/Au                                       |
| Contact carrier material               | TPU GF                                      |
| Material for screw connection          | Zinc die-cast, nickel-plated                |

### Electrical properties

|                       |                            |
|-----------------------|----------------------------|
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Nominal voltage $U_N$ | 250 V AC                   |
|                       | 250 V DC                   |
| Nominal current $I_N$ | 4 A                        |

### Mechanical properties

#### Mechanical data

|                             |            |
|-----------------------------|------------|
| Insertion/withdrawal cycles | $\geq 100$ |
|-----------------------------|------------|

### Signaling

|                        |    |
|------------------------|----|
| Status display         | no |
| Status display present | No |

### Connection data

#### Conductor connection

|                   |                        |
|-------------------|------------------------|
| Tightening torque | 0.4 Nm (M12 connector) |
|-------------------|------------------------|

### Connector

#### Connection 1

# SAC-3P-M12MR/0,3-PUR/M12FS B - Sensor/actuator cable



1668551

<https://www.phoenixcontact.com/pc/products/1668551>

|             |                 |
|-------------|-----------------|
| Type        | Plug angled M12 |
| Coding type | A               |


## Connection 2

|             |                     |
|-------------|---------------------|
| Type        | Socket straight M12 |
| Coding type | A                   |

## Cable/line

|              |       |
|--------------|-------|
| Cable length | 0.3 m |
|--------------|-------|

## PUR halogen-free black [PUR]

|                                               |                                                                                                                       |
|-----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Dimensional drawing                           |                                    |
| Cable weight                                  | 23 kg/km                                                                                                              |
| UL AWM Style                                  | 20549                                                                                                                 |
| Number of positions                           | 3                                                                                                                     |
| Shielded                                      | no                                                                                                                    |
| Cable type                                    | PUR halogen-free black [PUR]                                                                                          |
| Conductor structure signal line               | 42x 0.10 mm                                                                                                           |
| AWG signal line                               | 22                                                                                                                    |
| Conductor cross section                       | 3x 0.34 mm <sup>2</sup> (Signal line)                                                                                 |
| Wire diameter incl. insulation                | 1.27 mm ±0.02 mm (Signal line)                                                                                        |
| External cable diameter                       | 3.85 mm ±0.15 mm                                                                                                      |
| Outer sheath, material                        | PUR                                                                                                                   |
| External sheath, color                        | black-gray RAL 7021                                                                                                   |
| Conductor material                            | Bare Cu litz wires                                                                                                    |
| Material wire insulation                      | PP                                                                                                                    |
| Single wire, color                            | brown, blue, black                                                                                                    |
| Thickness, insulation                         | ≥ 0.21 mm (Core insulation)<br>approx. 0.50 mm (Outer cable sheath)                                                   |
| Overall twist                                 | 3 wires, twisted                                                                                                      |
| Max. conductor resistance                     | max. 58 Ω/km (at 20 °C)                                                                                               |
| Insulation resistance                         | ≥ 100 GΩ*km (at 20 °C)                                                                                                |
| Nominal voltage, cable                        | ≤ 300 V                                                                                                               |
| Test voltage                                  | ≥ 3000 V                                                                                                              |
| Smallest bending radius, fixed installation   | 19 mm                                                                                                                 |
| Smallest bending radius, movable installation | 38 mm                                                                                                                 |
| Dynamic load capacity (bending)               | Max. bending cycles: 10000000, Bending radius: 38 mm, Traversing path: 10 m, Traversing rate: 3 m/s, Acceleration: 10 |

# SAC-3P-M12MR/0,3-PUR/M12FS B - Sensor/actuator cable



1668551

<https://www.phoenixcontact.com/pc/products/1668551>

|                                 |                                                                     |
|---------------------------------|---------------------------------------------------------------------|
|                                 | m/s²                                                                |
| Halogen-free                    | in accordance with DIN VDE 0472 part 815                            |
| Flame resistance                | in accordance with UL 758/1581 FT2                                  |
|                                 | DIN EN 60332-2-2 (20 s)                                             |
| Resistance to oil               | in accordance with DIN EN 60811-2-1                                 |
| Other resistance                | Highly resistant to acids, alkaline solutions and solvents          |
|                                 | hydrolysis and microbe resistant                                    |
|                                 | partly UV-resistant (in accordance with DIN EN ISO 4892-2-A)        |
| Special properties              | Flexible cable conduit capable                                      |
|                                 | Silicone-free                                                       |
|                                 | Free of substances which would hinder coating with paint or varnish |
| Ambient temperature (operation) | -40 °C ... 80 °C (cable, fixed installation)                        |
|                                 | -25 °C ... 80 °C (Cable, flexible installation)                     |

## Environmental and real-life conditions

### Ambient conditions

|                                 |                                                |
|---------------------------------|------------------------------------------------|
| Degree of protection            | IP65                                           |
|                                 | IP67                                           |
|                                 | IP68                                           |
| Ambient temperature (operation) | -25 °C ... 90 °C (Plug / socket)               |
|                                 | -40 °C ... 80 °C (cable, fixed installation)   |
|                                 | -5 °C ... 80 °C (Cable, flexible installation) |

## Standards and regulations

|                          |                 |
|--------------------------|-----------------|
| Standard designation     | M12 connector   |
| Standards/specifications | IEC 61076-2-101 |

# SAC-3P-M12MR/0,3-PUR/M12FS B - Sensor/actuator cable




1668551


<https://www.phoenixcontact.com/pc/products/1668551>

## Drawings

Circuit diagram



Dimensional drawing



M12 x 1 male plug, angled

1668551


<https://www.phoenixcontact.com/pc/products/1668551>

Schematic diagram



Pin assignment M12 plug, 3-pos., A-coded, view male side

Schematic diagram



Pin assignment M12 socket, 3-pos., PIN 2+4 bridged, A-coded, view female side


# SAC-3P-M12MR/0,3-PUR/M12FS B - Sensor/actuator cable



1668551

<https://www.phoenixcontact.com/pc/products/1668551>

Dimensional drawing



M12 x 1 socket, straight

# SAC-3P-M12MR/0,3-PUR/M12FS B - Sensor/actuator cable



1668551  
<https://www.phoenixcontact.com/pc/products/1668551>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1668551>

|  |                                                |                       |                   |                             |
|--|------------------------------------------------|-----------------------|-------------------|-----------------------------|
|  | <b>UL Listed</b><br>Approval ID: FILE E 221474 |                       |                   |                             |
|  | Nominal voltage $U_N$                          | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|  | 300 V                                          | 4 A                   | -                 | -                           |

|  |                                                 |                       |                   |                             |
|--|-------------------------------------------------|-----------------------|-------------------|-----------------------------|
|  | <b>cUL Listed</b><br>Approval ID: FILE E 221474 |                       |                   |                             |
|  | Nominal voltage $U_N$                           | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|  | 300 V                                           | 4 A                   | -                 | -                           |

|  |                                                      |  |  |  |
|--|------------------------------------------------------|--|--|--|
|  | <b>EAC-RoHS</b><br>Approval ID: RU D-DE.HB35.B.00387 |  |  |  |
|  |                                                      |  |  |  |

|                     |  |  |  |  |
|---------------------|--|--|--|--|
| <b>cULus Listed</b> |  |  |  |  |
|---------------------|--|--|--|--|

# SAC-3P-M12MR/0,3-PUR/M12FS B - Sensor/actuator cable



1668551  
<https://www.phoenixcontact.com/pc/products/1668551>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27060311 |
| ECLASS-12.0 | 27060311 |
| ECLASS-13.0 | 27060311 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001855 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

# SAC-3P-M12MR/0,3-PUR/M12FS B - Sensor/actuator cable



1668551  
<https://www.phoenixcontact.com/pc/products/1668551>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)