

1671069

<https://www.phoenixcontact.com/us/products/1671069>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket angled M8, coding: A, with 2 LEDs, cable length: 1.5 m

Your advantages

- Easy and safe: 100 % electrically tested plug-in components
- Convenient: increased machine availability thanks to quick and easy diagnostics

Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 1671069             |
| Packing unit                         | 1 pc                |
| Minimum order quantity               | 1 pc                |
| Sales key                            | BF01                |
| Product key                          | BF1BBA              |
| Catalog page                         | Page 188 (C-2-2019) |
| GTIN                                 | 4017918134914       |
| Weight per piece (including packing) | 34.12 g             |
| Weight per piece (excluding packing) | 31.8 g              |
| Customs tariff number                | 85444290            |
| Country of origin                    | PL                  |

# SAC-3P- 1,5-PUR/M 8FR-2L - Sensor/actuator cable



1671069

<https://www.phoenixcontact.com/us/products/1671069>

## Technical data

### Product properties

|                      |                       |
|----------------------|-----------------------|
| Product type         | Sensor/actuator cable |
| Number of positions  | 3                     |
| Application          | Standard              |
| No. of cable outlets | 1                     |
| Shielded             | no                    |
| Coding               | A                     |

### Insulation characteristics

|                      |    |
|----------------------|----|
| Overvoltage category | II |
| Degree of pollution  | 3  |

### Material specifications

|                                        |                                             |
|----------------------------------------|---------------------------------------------|
| Flammability rating according to UL 94 | HB                                          |
| Seal material                          | NBR                                         |
| Material of grip body                  | TPU, hardly inflammable, self-extinguishing |
| Contact material                       | CuSn                                        |
| Contact surface material               | Ni/Au                                       |
| Contact carrier material               | TPU GF                                      |
| Material for screw connection          | Zinc die-cast, nickel-plated                |

### Electrical properties

|                       |                            |
|-----------------------|----------------------------|
| Contact resistance    | $\leq 5 \text{ m}\Omega$   |
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Nominal voltage $U_N$ | 24 V DC                    |
| Nominal current $I_N$ | 4 A                        |
| Protective circuit    | unwired                    |

### Mechanical properties

#### Mechanical data

|                             |            |
|-----------------------------|------------|
| Insertion/withdrawal cycles | $\geq 100$ |
|-----------------------------|------------|

### Signaling

|                        |        |
|------------------------|--------|
| Status display         | 2 LEDs |
| Status display present | Yes    |

### Connection data

#### Conductor connection

|                   |                        |
|-------------------|------------------------|
| Tightening torque | 0.2 Nm (M8 connectors) |
|-------------------|------------------------|

### Connector

# SAC-3P- 1,5-PUR/M 8FR-2L - Sensor/actuator cable



1671069

<https://www.phoenixcontact.com/us/products/1671069>

## Connection 1

|      |                |
|------|----------------|
| Type | free cable end |
|------|----------------|

## Connection 2


|                     |                  |
|---------------------|------------------|
| Type                | Socket angled M8 |
| Number of positions | 3                |
| Coding type         | A                |

## Cable/line

|              |       |
|--------------|-------|
| Cable length | 1.5 m |
|--------------|-------|

## PUR halogen-free black [PUR]

### Dimensional drawing



|                                             |                                       |
|---------------------------------------------|---------------------------------------|
| Cable weight                                | 18 kg/km                              |
| UL AWM Style                                | 20549 / 10493 (80°C/300 V)            |
| Number of positions                         | 3                                     |
| Shielded                                    | no                                    |
| Cable type                                  | PUR halogen-free black [PUR]          |
| Conductor structure signal line             | 32x 0.10 mm                           |
| AWG signal line                             | 24                                    |
| Conductor cross section                     | 3x 0.25 mm <sup>2</sup> (Signal line) |
| Wire diameter incl. insulation              | 1.17 mm ±0.02 mm                      |
| External cable diameter                     | 3.60 mm ±0.15 mm                      |
| Outer sheath, material                      | PUR                                   |
| External sheath, color                      | black-gray RAL 7021                   |
| Conductor material                          | Bare Cu litz wires                    |
| Material wire insulation                    | PP                                    |
| Single wire, color                          | brown, blue, black                    |
| Thickness, insulation                       | ≥ 0.21 mm (Core insulation)           |
| Thickness, outer sheath                     | approx. 0.50 mm                       |
| Overall twist                               | 3 wires, twisted                      |
| Length of twist, overall twist              | 40 mm                                 |
| Max. conductor resistance                   | ≤ 78 Ω/km (at 20 °C)                  |
| Insulation resistance                       | ≥ 100 GΩ*km (at 20 °C)                |
| Nominal voltage, cable                      | ≤ 300 V                               |
| Test voltage                                | ≥ 3000 V                              |
| Smallest bending radius, fixed installation | 18 mm                                 |

# SAC-3P- 1,5-PUR/M 8FR-2L - Sensor/actuator cable



1671069

<https://www.phoenixcontact.com/us/products/1671069>

|                                               |                                                                                                                                                                                           |
|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Smallest bending radius, movable installation | 36 mm                                                                                                                                                                                     |
| Max. bending cycles                           | 10000000                                                                                                                                                                                  |
| Halogen-free                                  | in accordance with DIN VDE 0472 part 815                                                                                                                                                  |
| Flame resistance                              | in accordance with UL 758/1581 FT2<br>DIN EN 60332-2-2 (20 s)                                                                                                                             |
| Resistance to oil                             | in accordance with DIN EN 60811-2-1                                                                                                                                                       |
| Other resistance                              | hydrolysis and microbe resistant<br>Highly resistant to acids, alkaline solutions and solvents<br>Resistant to salt water<br>partly UV-resistant (in accordance with DIN EN ISO 4892-2-A) |
| Special properties                            | Flexible cable conduit capable<br>Silicone-free<br>Free of substances which would hinder coating with paint or varnish                                                                    |
| Ambient temperature (operation)               | -40 °C ... 80 °C (cable, fixed installation)<br>-25 °C ... 80 °C (Cable, flexible installation)                                                                                           |

## Environmental and real-life conditions

### Ambient conditions

|                                 |                                  |
|---------------------------------|----------------------------------|
| Degree of protection            | IP65<br>IP67<br>IP68             |
| Ambient temperature (operation) | -25 °C ... 90 °C (Plug / socket) |

## Standards and regulations

### M8

|                          |                 |
|--------------------------|-----------------|
| Standard designation     | M8 connector    |
| Standards/specifications | IEC 61076-2-104 |

# SAC-3P- 1,5-PUR/M 8FR-2L - Sensor/actuator cable


1671069

<https://www.phoenixcontact.com/us/products/1671069>




## Drawings

Dimensional drawing




Socket M8 x 1, angled, with LED

Circuit diagram



Schematic diagram



Pin assignment M8 socket, 3-pos., view female side

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1671069>

|                                                                                                                                              |                                |                                |                   |                               |
|----------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|--------------------------------|-------------------|-------------------------------|
| <div> <b>UL Listed</b><br/>Approval ID: FILE E 221474</div> |                                |                                |                   |                               |
|                                                                                                                                              | Nominal voltage U <sub>N</sub> | Nominal current I <sub>N</sub> | Cross section AWG | Cross section mm <sup>2</sup> |
|                                                                                                                                              | 24 V                           | 4 A                            | -                 | -                             |

|                                                                                                                                               |                                |                                |                   |                               |
|-----------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|--------------------------------|-------------------|-------------------------------|
| <div> <b>cUL Listed</b><br/>Approval ID: FILE E 221474</div> |                                |                                |                   |                               |
|                                                                                                                                               | Nominal voltage U <sub>N</sub> | Nominal current I <sub>N</sub> | Cross section AWG | Cross section mm <sup>2</sup> |
|                                                                                                                                               | 24 V                           | 4 A                            | -                 | -                             |

|                                                                                                                                                     |  |  |  |  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
| <div> <b>EAC-RoHS</b><br/>Approval ID: RU D-DE.HB35.B.00387</div> |  |  |  |  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|

|                     |  |  |  |  |
|---------------------|--|--|--|--|
| <b>cULus Listed</b> |  |  |  |  |
|---------------------|--|--|--|--|

# SAC-3P- 1,5-PUR/M 8FR-2L - Sensor/actuator cable



1671069

<https://www.phoenixcontact.com/us/products/1671069>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27060311 |
| ECLASS-12.0 | 27060311 |
| ECLASS-13.0 | 27060311 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001855 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

Environmental product compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)