

1673465

https://www.phoenixcontact.com/us/products/1673465

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Box mounting base, with single locking latch, height 52 mm, without screw connection, 1x Pg16, with protective covers

Commercial data

Item number	1673465
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	BF55
Product key	BF7AAC
Catalog page	Page 496 (C-4-2013)
GTIN	4017918152239
Weight per piece (including packing)	266.57 g
Weight per piece (excluding packing)	266.57 g
Customs tariff number	85389099
Country of origin	DE



https://www.phoenixcontact.com/us/products/1673465



Technical data

Notes

General	For contact inserts HC-B10, BB18, DD42, M, K8/24
---------	--

Product properties

Product type	Housing with locking latch
Housing type	Box mounting bases
Application	Standard
Туре	B10
No. of cable outlets	1
Type of the screw connection	1x Pg16
Protective cover	yes
Cable outlet	left (view of the opened single locking latch)
Pg screw connection	none

Dimensions

Dimensional drawing	3 93 05.5 05.5 05.5 05.5 05.5 05.5 05.5 05.
Width	52 mm
Height	52 mm
Length	93 mm

Material specifications

Seal material	NBR
Housing material	die-cast aluminum
Housing surface material	Powder-coated, gray
Material, protective cover	PA
Locking latch material	Stainless steel, handle: PA

Mechanical properties

Mechanical data

Type of the screw connection	1x Pg16
Locking type	Latch

Mounting

Assembly note	For half and full screw connections

Environmental and real-life conditions

Ambient conditions



1673465

https://www.phoenixcontact.com/us/products/1673465

Degree of protection	IP65 (When plugged in)
	IP54 (with closed protective cover)
Ambient temperature (operation)	-40 °C 125 °C





https://www.phoenixcontact.com/us/products/1673465



Drawings

Dimensional drawing





Dimensional drawing



1673465

https://www.phoenixcontact.com/us/products/1673465

Classifications

ECLASS

	ECLASS-11.0	27440202
	ECLASS-13.0	27440202
UN	NSPSC	
	UNSPSC 21.0	31261501



1673465

https://www.phoenixcontact.com/us/products/1673465

Environmental product compliance

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%



https://www.phoenixcontact.com/us/products/1673465



Accessories

G-INS-PG16-S68N-PNES-GY - Cable gland

1411144

https://www.phoenixcontact.com/us/products/1411144



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 10 mm ... 14 mm, shielding: no, connecting thread: Pg16, color: silver-grey RAL 7001

G-INS-PG16-S68N-NNES-S - Cable gland

1411174

https://www.phoenixcontact.com/us/products/1411174



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 10 mm ... 14 mm, shielding: no, connecting thread: Pg16, color: silver, with O-ring



https://www.phoenixcontact.com/us/products/1673465



G-INSEC-PG16-S68N-NNES-S - Cable gland

1411199

https://www.phoenixcontact.com/us/products/1411199



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 10 mm ... 14 mm, shielding: yes, connecting thread: Pg16, color: silver, with O-ring

HC-BS-PG16 - Screw plug

1674516

https://www.phoenixcontact.com/us/products/1674516



Screw plug, material for screw connection: Brass, nickel-plated, connecting thread: Pg16, color: silver

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com