


HC-M-04-MOD-BU - Contact insert module



1676789

<https://www.phoenixcontact.com/pc/products/1676789>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON contact insert module, 4-pos., for HC-M-04-ST-KOAX... coaxial contacts

Commercial data

Item number	1676789
Packing unit	2 pc
Minimum order quantity	2 pc
Product key	BF7ACB
Catalog page	Page 563 (C-4-2015)
GTIN	4017918129385
Weight per piece (including packing)	8.75 g
Weight per piece (excluding packing)	8.75 g
Customs tariff number	85369010
Country of origin	DE

HC-M-04-MOD-BU - Contact insert module



1676789
<https://www.phoenixcontact.com/pc/products/1676789>

Technical data

Notes

General	For HEAVYCON housings type B6 to B48, HC-M-B...MF-... module carrier frame required, crimp contacts HC-M-04-KOAX... (crimp contacts not included in the scope of delivery)
---------	--

Product properties

Product type	Coaxial insert, modular
Series	HC-M-04-KOAX
Application	Signal
Number of positions	4
Connection profile	4xKOAX
Contact numbering	1 - 4
Number of module slots	1
Contact material type	turned

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated voltage (III/3)	50 V
Rated surge voltage	3 kV
Rated current	1.5 A
Contact resistance, phase conductor	≤ 3 mΩ
Contact resistance, inner conductor	≤ 10 mΩ
Insulation resistance	≥ 10 GΩ

Connection data

Connection technology

Connection technology	Soldering and crimp connection
-----------------------	--------------------------------

Dimensions

Dimensional drawing	
Width	34.2 mm
Height	32.6 mm
Length	14.6 mm

Mechanical characteristics

HC-M-04-MOD-BU - Contact insert module



1676789

<https://www.phoenixcontact.com/pc/products/1676789>

Contact diameter	4.8 mm
------------------	--------

Material specifications

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Au
Contact carrier material	PC

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

Mounting

Assembly note	For housing heights ≥ 52 mm. Plug-in connections may only be operated only when there is no load/voltage.
	For HC-M-04-ST-KOAX... contacts

HC-M-04-MOD-BU - Contact insert module


1676789

<https://www.phoenixcontact.com/pc/products/1676789>



Drawings

Dimensional drawing



Female insert

HC-M-04-MOD-BU - Contact insert module



1676789

<https://www.phoenixcontact.com/pc/products/1676789>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com