

HC-A 10-EBUC - Contact insert

1676983

<https://www.phoenixcontact.com/no/products/1676983>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

HEAVYCON female insert, A10 series, 10-pos., crimp connection



Commercial data

Item number	1676983
Packing unit	10 pc
Minimum order quantity	1 pc
Sales key	31BBF
Product key	BF7ABB
Catalog page	Page 519 (C-2-2019)
GTIN	4017918129606
Weight per piece (including packing)	38.07 g
Weight per piece (excluding packing)	35.51 g
Customs tariff number	85366990
Country of origin	DE

HC-A 10-EBUC - Contact insert

1676983

<https://www.phoenixcontact.com/no/products/1676983>



Technical data

Notes

General	for flexible conductors with or without ferrules
General	Connectors may be operated only when there is no load/voltage.
General	For HEAVYCON housing of type D15

Mounting

Assembly instructions	To ensure correct use, installation in housing with IP54 protection or better is required
-----------------------	---

Product properties

Type	D15
Product type	Contact insert with a fixed no. of positions
Number of positions	10
Connection profile	10+PE
Contact numbering	1 - 10
Number of connections per position	1
Contact material type	turned
Series	HC-A

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Dimensions

Dimensional drawing	
Width	23 mm
Height	30 mm
Length	56.5 mm
Drill hole distance, horizontal	49.5 mm
Drill hole distance, vertical	16 mm

Mechanical characteristics

Contact diameter	2.5 mm
------------------	--------

Connection data

Connection technology

Connection technology	Crimp connection
Number of connections per position	1

HC-A 10-EBUC - Contact insert

1676983

<https://www.phoenixcontact.com/no/products/1676983>



Connection in acc. with standard	IEC / EN
----------------------------------	----------

Conductor connection

Conductor cross section	0.5 mm ² ... 4 mm ²
Connection cross section AWG	20 ... 12
Tightening torque	0.7 Nm ... 1 Nm (PE connection) 0.5 Nm ... 0.8 Nm (Mounting screws for mounting in the HEAVYCON housing)
Stripping length of the individual wire	8 mm

Electrical properties

Rated voltage (III/3)	250 V
Rated surge voltage	4 kV
Rated current	16 A

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

Material specifications

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ag (alternatively Au)
Contact carrier material	PA

Environmental and real-life conditions


Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C (including heating up of contacts)
---------------------------------	--


Standards and regulations

Constructional and testing regulations	DIN VDE 0627/86
	DIN VDE 0110/02.79
	DIN VDE 0110-1/04.97
	IEC 60664-1, DIN IEC 60512
	IEC 60352
Tests	DIN VDE 0627/86
	DIN VDE 0110/02.79
	DIN VDE 0110-1/04.97
	IEC 60664-1, DIN IEC 60512
	IEC 60352

Drawings



Derating diagram: HC-A...C series



Female insert


HC-A 10-EBUC - Contact insert

1676983

<https://www.phoenixcontact.com/no/products/1676983>



Dimensional drawing




Mounting cutout when used without housing

1676983

<https://www.phoenixcontact.com/no/products/1676983>

Schematic diagram



Connector pin assignment, connection side

HC-A 10-EBUC - Contact insert



1676983

<https://www.phoenixcontact.com/no/products/1676983>

Classifications

ECLASS

ECLASS-11.0	27440205
ECLASS-13.0	27440205

ETIM

ETIM 8.0	EC000438
----------	----------

UNSPSC

UNSPSC 21.0	39121500
-------------	----------

HC-A 10-EBUC - Contact insert



1676983

<https://www.phoenixcontact.com/no/products/1676983>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT AS
Strømsveien 344
N-1081 Oslo
+47 22 07 68 00
norge@phoenixcontact.com